

MICROSAR OS

Technical Reference

Version 9.01

Status	Released
Document ID	OS01.0280

Document Information

History

Author	Date	Version	Remarks
Rmk	2012-06-26	6.00	creation based on AUTOSAR 3.0 version
Shk	2013-09-18	6.01	SingleSource template applied and variants for ASR3.x, ASR4.x, SafeContext and non-SafeContext prepared
Biv	2014-02-04	6.02	MultiCore references corrected
Zfa	2014-05-05	6.03	Updated timer description
Asl	2014-08-14	8.00	Examples chapter excluded TimingAnalyzer removed Updated counter related macros and configuration
Asl	2014-10-16	8.01	Added PeripheralRegion API Added Non-Trusted Function API Added CheckMPUAccess API
Asl	2015-01-29	9.00	Updated interpretation of OsSecondsPerTick and OsCounterTicksPerBase
Rk	2015-06-17	9.01	Added MICROSAR OS Timing Hooks Added table of terms to the glossary Added the information that forcible termination is currently not supported

Reference Documents

No.	Title	Version
[1]	AUTOSAR_SWS_OS.pdf AUTOSAR OS specification; This document is available in PDF-format on the internet at the AUTOSAR homepage (http://www.autosar.org)	V5.0.0
[2]	AUTOSAR_TR_BSWModuleList.pdf	1.6.0
[3]	OSEK/VDX Operating System Specification This document is available in PDF-format on the Internet at the OSEK/VDX homepage (http://www.osek-vdx.org)	2.2.3
[4]	TechnicalReference_Microsar_Os_Multicore.pdf	1.00
[5]	TechnicalReference_MicrosarOS_xxxx.pdf Technical reference of Vector MICROSAR OS; Hardware specific part	--
[6]	OIL: OSEK Implementation Language This document is available in PDF-format on the Internet at the OSEK/VDX homepage (http://www.osek-vdx.org)	2.3
[7]	Tutorial_osCAN.pdf Tutorial for the MICROSAR OS OSEK/AUTOSAR Realtime Operating System	1.00
[8]	autosar.xsd AUTOSAR XML schema	4.0.3

Scope of the Document

MICROSAR OS is an operating system, compliant with the AUTOSAR OS and OSEK standards. The general aspects of all Scalability Classes, SC1 – SC4, are described in this document. For each implementation, the hardware specific part is described in a separate document [4].

The implementation is based on the AUTOSAR OS specification [1].

It is also based on the OSEK OS specification 2.2 described in the document [3].

This documentation assumes that the reader is familiar with both the OSEK OS specification and the AUTOSAR OS specification.

This documentation describes only the operating system and the code generation tool.

OSEK is a registered trademark of Continental Automotive GmbH (until 2007: Siemens AG).



Caution

We have configured the programs in accordance with your specifications in the questionnaire. Whereas the programs do support other configurations than the one specified in your questionnaire, Vector's release of the programs delivered to your company is expressly restricted to the configuration you have specified in the questionnaire.

Contents

1	Component History	14
2	Introduction	15
2.1	Architecture Overview	15
3	Functional Description	17
3.1	Features.....	17
3.2	Main Functions.....	17
3.2.1	Timer and Alarms	18
3.2.1.1	Time Base	19
3.2.1.1.1	Counter Macros.....	19
3.2.1.1.2	Temporal Range of Alarms	19
3.2.1.2	Timer Interrupt Routine.....	19
3.2.1.2.1	Counter API.....	19
3.2.2	Stack Handling	20
3.2.2.1	Task Stack.....	20
3.2.2.2	Interrupt Stack	20
3.2.2.3	Stack Monitoring.....	21
3.2.2.4	Stack Sharing	21
3.2.2.4.1	Basic Tasks on the same Priority.....	22
3.2.2.4.2	Basic non-preemptive Tasks not calling SCHEDULE.....	22
3.2.2.4.3	Basic Tasks, sharing an internal Resource and not calling SCHEDULE	22
3.2.2.5	Stack Usage	23
3.2.3	Interrupt Handling.....	23
3.2.3.1	Interrupt Categories.....	23
3.2.3.1.1	Category 1:	23
3.2.3.1.2	Category 2:	24
3.2.3.2	Usage of the Interrupt API before StartOS.....	24
3.2.4	Timing Protection	25
3.2.4.1	Reaction on Protection Failure	25
3.2.4.2	Timing Measurement.....	25
3.2.4.2.1	Timing measurement configuration for a specific task/ISR	26
3.2.4.2.2	Global configuration of timing measurement	26
3.2.4.3	Hook functions	27
3.2.5	Memory Protection	27
3.2.6	Schedule Tables.....	28
3.2.6.1	Synchronization.....	28
3.2.6.1.1	Starting a synchronizable Schedule Table	28

3.2.6.1.2	Autostart.....	28
3.2.6.1.3	Suspending a Schedule Table and keeping its Synchronization	29
3.2.6.1.4	Providing a Global Time	29
3.2.6.1.5	Exact Synchronization.....	29
3.2.6.1.6	Limits of the Synchronization Algorithm	30
3.2.6.1.7	Details about using NextScheduleTable	31
3.2.6.1.8	Concurrent Actions	31
3.2.6.2	High-Resolution Schedule Tables.....	31
3.2.6.2.1	Setup	32
3.2.6.3	Cyclical Expiry Point Actions	32
3.2.7	Service Protection.....	32
3.2.7.1	Missing TerminateTask	32
3.2.7.2	Call of System Services with Interrupts disabled	32
3.2.8	Trusted Functions.....	33
3.2.8.1	Generated Stub Functions.....	33
3.3	Error Handling	35
3.3.1	Error Messages.....	35
3.3.2	OSEK / AUTOSAR OS Error Numbers	35
3.3.3	MICROSAR OS Error Numbers	36
3.3.3.1	Error Numbers of Group Task Management / (1).....	37
3.3.3.2	Error Numbers of Group Interrupt Handling / (2).....	39
3.3.3.3	Error Numbers of Group Resource Management / (3).....	41
3.3.3.4	Error Numbers of Group Event Control / (4)	42
3.3.3.5	Error Numbers of Group Alarm Management / (5)	44
3.3.3.6	Error Numbers of Group Operating System Execution Control / (6).....	46
3.3.3.7	Error Numbers of Schedule Table Control / (7)	47
3.3.3.8	Error Numbers of Group Counter API / (8).....	51
3.3.3.9	Error Numbers of Group Timing Protection and Timing Measurement / (9)....	52
3.3.3.10	Platform specific error codes (A)	54
3.3.3.11	Error Numbers of Group Application API (B).....	54
3.3.3.12	Error Numbers of Group Semaphores (C)	55
3.3.3.13	Error Numbers of Group MultiCore related functions (D)	56
3.3.3.14	Error Numbers of Group TrustedFunctions (E)	56
3.3.3.15	Error Numbers of Group IOC (F)	57
3.3.4	ErrorInfoLevel.....	57
3.3.5	Reactions on Error Situations.....	57
4	Installation	58
4.1	Installation Requirements	58
4.2	Installation Disk	58
4.3	OIL Configurator	59

4.3.1	INI Files of the OIL Tool	59
4.3.2	OIL Implementation Files.....	59
4.3.3	Code Generator	59
4.4	OSEK Operating System.....	59
4.4.1	Installation Paths.....	59
4.5	XML Configurations.....	60
4.5.1	Parameter Definition Files	60
5	Integration	61
5.1	Scope of Delivery	61
5.1.1	Static Files.....	61
5.1.2	Dynamic Files.....	61
5.1.2.1	Code Generator GENxxxx.....	61
5.1.2.1.1	Generated file libconf	61
5.1.2.2	Application Template Generator GENTMPL	62
5.2	Include Structure	62
6	API Description	63
6.1	Standard API - Overview	63
6.2	API Functions defined by Vector - Overview.....	66
6.3	API Macros	67
6.4	Timing Measurement API	68
6.4.1	GetTaskMaxExecutionTime	68
6.4.2	GetISRMaxExecutionTime	68
6.4.3	GetTaskMaxBlockingTime	69
6.4.4	GetISRMaxBlockingTime	70
6.4.5	GetTaskMinInterArrivalTime	70
6.4.6	GetISRMinInterArrivalTime.....	71
6.5	Implementation specific Behavior	72
6.5.1	Interrupt Handling.....	72
6.5.1.1	EnableAllInterrupts	72
6.5.1.2	DisableAllInterrupts	73
6.5.1.3	ResumeAllInterrupts.....	74
6.5.1.4	SuspendAllInterrupts	75
6.5.1.5	ResumeOSInterrupts.....	75
6.5.1.6	SuspendOSInterrupts.....	76
6.5.2	Resource Management	77
6.5.2.1	GetResource	77
6.5.2.2	ReleaseResource.....	78
6.5.3	Execution Control.....	79
6.5.3.1	StartOS	79

6.5.3.2	ShutdownOS	80
6.6	Hook Routines.....	81
6.6.1	Standard Hooks.....	81
6.6.1.1	StartupHook	81
6.6.1.2	PreTaskHook.....	82
6.6.1.3	PostTaskHook	82
6.6.1.4	ErrorHook.....	83
6.6.1.5	ShutdownHook.....	83
6.6.1.6	ProtectionHook.....	84
6.6.2	ISR Hooks.....	84
6.6.2.1	UserPreISRHook.....	84
6.6.2.2	UserPostISRHook	85
6.6.3	Alarm Hook	86
6.6.3.1	PreAlarmHook (currently not supported)	86
6.6.4	MICROSAR OS Timing Hooks	86
6.6.4.1	Hooks for arrival	87
6.6.4.1.1	OS_VTH_ACTIVATION	87
6.6.4.1.2	OS_VTH_SETEVENT	87
6.6.4.1.3	OS_VTH_TRANSFER_SEMA.....	88
6.6.4.2	Hook for context switch	89
6.6.4.2.1	OS_VTH_SCHEDULE	89
6.6.4.3	Hooks for locking.....	90
6.6.4.3.1	OS_VTH_GOT_RES.....	90
6.6.4.3.2	OS_VTH_REL_RES.....	91
6.6.4.3.3	OS_VTH_REQ_SPINLOCK	91
6.6.4.3.4	OS_VTH_GOT_SPINLOCK	92
6.6.4.3.5	OS_VTH_REL_SPINLOCK.....	93
6.6.4.3.6	OS_VTH_TOOK_SEMA.....	94
6.6.4.3.7	OS_VTH_REL_SEMA.....	94
6.6.4.3.8	OS_VTH_DISABLEDINT	95
6.6.4.3.9	OS_VTH_ENABLEDINT	96
6.7	Non-Trusted Functions	96
6.7.1	Functionality	96
6.7.2	API	97
6.8	MPU Access Checking API.....	97
6.9	Peripheral Regions.....	98
6.9.1	Reading functions	98
6.9.2	Writing functions.....	99
6.9.3	Modifying functions	100
7	Configuration.....	101

7.1	Configuration and generation process	101
7.1.1	XML Configuration.....	101
7.1.2	OIL Configurator	102
7.2	Configuration Variants	102
7.3	Configuration of the XML / OIL Attributes.....	102
7.3.1	OS.....	103
7.3.1.1	APIOptimization / OSOSAPIOptimization	107
7.3.1.2	ProtectionHookReaction / OsOSProtectionHookReaction	107
7.3.1.3	TimingMeasurement / OsOSTimingMeasurement	108
7.3.1.4	PeripheralRegion / OsOSPeripheralRegion.....	109
7.3.2	Task	110
7.3.2.1	AUTOSTART / OsTaskAutostart	111
7.3.2.2	TIMING_PROTECTION / OsTaskTimingProtection	112
7.3.2.3	Task attributes concerning the timing analyzer	113
7.3.3	Counter	114
7.3.4	Alarm	115
7.3.4.1	ACTION / OsAlarmAction	116
7.3.4.2	AUTOSTART / OsAlarmAutostart	117
7.3.5	Resource.....	118
7.3.6	Event.....	119
7.3.7	ISR.....	119
7.3.7.1	UseSpecialFunctionName / OsIsrUseSpecialFunctionName	120
7.3.7.2	TIMING_PROTECTION / OsIsrTimingProtection.....	121
7.3.7.2.1	LOCKINGTIME / OsIsrResourceLock	122
7.3.7.3	ISR Attributes concerning the Timing Analyzer	123
7.3.8	COM	123
7.3.9	NM	124
7.3.10	APPMODE / OsAppMode.....	124
7.3.11	Application / OsApplication.....	124
7.3.11.1	Trusted Functions.....	125
7.3.11.2	HAS_RESTARTTASK	126
7.3.12	Scheduletable	126
7.3.12.1	AUTOSTART / OsScheduleTableAutostart	127
7.3.12.2	EXPIRY_POINT / OsScheduleTableExpiryPoint.....	128
7.3.12.3	Expiry point action ADJUST	129
7.3.12.4	Expiry point action ACTIVATETASK	129
7.3.12.5	Expiry point action SETEVENT	129
7.3.12.6	LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION / OsScheduleTableSync	130

8 System Generation 132

8.1	Code Generator	132
8.1.1	Generated Files.....	132
8.1.2	Automatic Documentation	132
8.1.3	Conditional Generation.....	133
8.1.4	Generated files backup	133
8.2	Application Template Generator	133
8.3	Compiler.....	133
8.3.1	Include Paths	133
9	AUTOSAR Standard Compliance	134
9.1	Deviations	134
9.2	Limitations.....	134
9.2.1	API Function OS_GetVersionInfo	134
9.2.2	Forcible Termination	134
9.2.3	AUTOSAR Debug support.....	134
9.2.4	Port Interface.....	134
9.2.5	NULL Pointer Checks.....	134
9.3	Clarifications	134
9.3.1	CallTrustedFunction if owner application is not APPLICATION_ACCESSIBLE.....	134
10	Debugging Support.....	136
10.1	Kernel aware Debugging	136
10.2	Version and Variant Coding	136
11	Glossary and Abbreviations	138
11.1	Abbreviations	138
11.2	Terms	139
12	Contact.....	140

Illustrations

Figure 2-1	AUTOSAR 3.x Architecture Overview	15
Figure 2-2	AUTOSAR architecture	15
Figure 3-1	Functional parts	18
Figure 3-2	Counter Macros	19
Figure 7-1	System overview of software parts	101
Figure 7-2	Relation between Physical Units, Counter Units and Driver Units	115

Tables

Table 3-1	Supported SWS features	17
Table 3-2	Not supported SWS features	17
Table 3-3	Interdependence between the OS attribute <code>TimingMeasurement</code> and the task/ISR attribute <code>TIMING_PROTECTION</code>	27
Table 3-4	OSEK/AUTOSAR OS error numbers	35
Table 3-5	Implementation specific error numbers	36
Table 3-6	Error types	37
Table 3-7	API functions of group Task Management / (1)	37
Table 3-8	Error numbers of group Task Management / (1)	39
Table 3-9	API functions of group Interrupt Handling / (2)	40
Table 3-10	Error numbers of group Interrupt Handling / (2)	40
Table 3-11	API functions of group Resource Management / (3)	41
Table 3-12	Error numbers of group Resource Management / (3)	42
Table 3-13	API functions of group Event Control / (4)	42
Table 3-14	Error numbers of group Event Control / (4)	44
Table 3-15	API functions of group Alarm Management / (5)	44
Table 3-16	Error numbers of group Alarm Management / (5)	46
Table 3-17	API functions of group Operating System Execution Control / (6)	46
Table 3-18	Error numbers of group Operating System Execution Control / (6)	47
Table 3-19	API functions of group Schedule Table Control / (7)	47
Table 3-20	Error numbers of group Schedule Table Control / (7)	51
Table 3-21	API functions of group Counter API / (8)	51
Table 3-22	Error numbers of group Counter API / (8)	52
Table 3-23	API functions of group Timing Protection and Timing Measurement / (9) ..	52
Table 3-24	Error numbers of group Timing Protection and Timing Measurement / (9) ..	54
Table 3-25	API functions of group Application API / (B)	55
Table 3-26	Error numbers of group Application API / (B)	55
Table 3-27	API functions of group Semaphores / (C)	56
Table 3-28	Error numbers of group Semaphores / (C)	56
Table 3-29	API functions of group TrustedFunctions (E)	57
Table 3-30	Error numbers of group TrustedFunctions (E)	57
Table 4-1	Installed components	58
Table 4-2	System configuration and generation tools	59
Table 5-1	Files generated by code generator GENxxxx	61
Table 5-2	Variables generated into the file libconf	62
Table 6-1	Standard API functions	66
Table 6-2	Vector API functions	66
Table 6-3	API function call macros	67
Table 6-4	Hook routine macros	67
Table 6-5	Dispatcher start macro	67
Table 6-6	GetTaskMaxExecutionTime	68

Table 6-7	GetISRMaxExecutionTime.....	69
Table 6-8	GetTaskMaxBlockingTime	70
Table 6-9	GetISRMaxBlockingTime.....	70
Table 6-10	GetTaskMinInterArrivalTime.....	71
Table 6-11	GetISRMinInterArrivalTime	72
Table 6-12	EnableAllInterrupts	73
Table 6-13	DisableAllInterrupts.....	74
Table 6-14	ResumeAllInterrupts	75
Table 6-15	SuspendAllInterrupts	75
Table 6-16	ResumeOSInterrupts	76
Table 6-17	SuspendOSInterrupts	77
Table 6-18	GetResource	78
Table 6-19	ReleaseResource	79
Table 6-20	StartOS.....	80
Table 6-21	ShutdownOS	81
Table 6-22	StartupHook.....	81
Table 6-23	PreTaskHook.....	82
Table 6-24	PostTaskHook.....	82
Table 6-25	ErrorHook	83
Table 6-26	ShutdownHook	84
Table 6-27	ProtectionHook.....	84
Table 6-28	UserPreISRHook	85
Table 6-29	UserPostISRHook	85
Table 6-30	PreAlarmHook	86
Table 6-31	OS_VTH_ACTIVATION	87
Table 6-32	OS_VTH_SETEVENT	88
Table 6-33	OS_VTH_TRANSFER_SEMA	89
Table 6-34	OS_VTH_SCHEDULE.....	90
Table 6-35	OS_VTH_GOT_RES	91
Table 6-36	OS_VTH_REL_RES.....	91
Table 6-37	OS_VTH_REQ_SPINLOCK.....	92
Table 6-38	OS_VTH_GOT_SPINLOCK.....	93
Table 6-39	OS_VTH_REL_SPINLOCK	93
Table 6-40	OS_VTH_TOOK_SEMA	94
Table 6-41	OS_VTH_REL_SEMA	95
Table 6-42	OS_VTH_DISABLEDINT	96
Table 6-43	OS_VTH_ENABLEDINT	96
Table 6-44	API osCallNonTrustedFunction.....	97
Table 6-45	osCheckMPUAccess API.....	98
Table 6-46	ReadPeripheral API	99
Table 6-47	WritePeripheral API	100
Table 6-48	ModifyPeripheral API	100
Table 7-1	OS attributes.....	107
Table 7-2	Sub-attributes of APIOptimization = Manual.....	107
Table 7-3	Sub-attributes of ProtectionHookReaction = SELECTED.....	108
Table 7-4	Sub-attributes of TimingMeasurement = TRUE.....	109
Table 7-5	Sub-attributes of PeripheralRegion	110
Table 7-6	Task attributes	111
Table 7-7	Sub-attributes of TASK->AUTOSTART=TRUE.....	112
Table 7-8	Sub-attributes of TASK->TIMING_PROTECTION=TRUE.....	113
Table 7-9	Task attributes concerning the timing analyzer.....	114
Table 7-10	Attributes of COUNTER.....	115
Table 7-11	Attributes of ALARM	116

Table 7-12	Sub-attributes of ACTION = ACTIVATETASK.....	116
Table 7-13	Sub-attributes of ACTION = SETEVENT	117
Table 7-14	Sub-attributes of ACTION = ALARMCALLBACK.....	117
Table 7-15	Sub-attributes of ACTION = ALARMCALLBACK.....	117
Table 7-16	Sub-attributes of AUTOSTART = TRUE	118
Table 7-17	Attributes of RESOURCE	119
Table 7-18	Sub-attributes of EVENT	119
Table 7-19	Attributes of ISR	120
Table 7-20	Sub-attributes of UseSpecialFunctionname / OslrUseSpecialFunctionName	120
Table 7-21	Sub-attributes of TIMING_PROTECTION / OslrTimingProtection.....	122
Table 7-22	Sub-attributes of LOCKINGTIME / OslrResourceLock	123
Table 7-23	ISR attributes concerning the timing analyzer	123
Table 7-24	Attributes of Appmode / OsAppMode	124
Table 7-25	Attributes of Application / OsApplication.....	125
Table 7-26	Sub-attributes for trusted functions	126
Table 7-27	Sub-attributes for Application->HAS_RESTARTTASK=TRUE	126
Table 7-28	Attributes of SCHEDULETABLE	127
Table 7-29	Sub-attributes for auto start of a schedule table	128
Table 7-30	Sub-attributes of expiry points.....	129
Table 7-31	Sub-attributes of expiry point action ADJUST	129
Table 7-32	Sub-attributes of expiry point action ACTIVATETASK	129
Table 7-33	Sub-attributes of expiry point action SETEVENT	130
Table 7-34	Sub-attributes SCHEDULETABLE-> LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION = TRUE	130
Table 10-1	Bit-definitions of the variant coding, ucSysVariant1	137
Table 10-2	Bit-definitions of the variant coding, osSysVariant2	137
Table 10-3	Bit definitions of the variant coding, osOrtiVariant	137
Table 11-1	Abbreviations.....	138
Table 11-2	Terms	139

1 Component History

The component history gives an overview over the important milestones that are supported in the different versions of the component.

This chapter is included in any MICROSAR component documentation. For the OS, the history on the intended level is not relevant as MICROSAR OS implements all mandatory requirements of AUTOSAR OS.

2 Introduction

This document describes the functionality, API and configuration of the general part of the AUTOSAR BSW module OS as specified in [1].

Supported AUTOSAR Release:	4.0.3	
Supported Configuration Variants:	pre-compile	
Vendor ID:	OS_VENDOR_ID	30 decimal (= Vector-Informatik, according to HIS)
Module ID:	OS_MODULE_ID	1 decimal (according to ref. [2])

2.1 Architecture Overview

The following figure shows where the OS is located in the AUTOSAR architecture.




Figure 2-1 AUTOSAR 3.x Architecture Overview

Figure 2-2 AUTOSAR architecture

The MICROSAR OS is an operating system based on the AUTOSAR OS standard V5.0.0 (ref. [1]) and on OSEK OS standard 2.2.3 (ref. [3]).

This MICROSAR OS operating system is a real time operating system, which was specified for the usage in electronic control units on a range of small to large microprocessors. MICROSAR OS has attributes which differ from commonly known operating systems and which allow a very efficient implementation even on systems with low resources of RAM and ROM.

As a requirement, there is no dynamic creation of new tasks at runtime; all tasks have to be defined before compilation. The operating system has no dynamic memory management and there is no shell for the control of tasks by hand.

The operating system and the application are compiled and linked together to one file, which is loaded into an emulator or is burned into an EPROM or Flash EEPROM.

3 Functional Description

3.1 Features

The features listed in this chapter cover the complete functionality specified in [1].

The "supported" and "not supported" features are presented in the following two tables. For further information of not supported features, also see chapter 9.

The following features described in [1] are supported:

Supported Feature

The Vector MICROSAR OS implements all mandatory features described in the chapter about System Scalability within [1]. However, some minor restrictions apply, see chapter 9 in this document.

Table 3-1 Supported SWS features

The following features described in [1] are supported in MultiCore implementations. However, they are currently not described in this document, but in the additional documentation [4].

Conditionally Supported Feature

MultiCore

Inter OSApplication Communication (IOC)

Table 3-2 Not supported SWS features

The OSEK / AUTOSAR OS specifications leave many points open on implementation. Every OSEK / AUTOSAR OS implementation for a specific microcontroller has to define the open points to achieve an optimal solution for the processor. The operating system has to fit the target microprocessor and the C-compiler. The programming model of the C-compiler is as important as the hardware of the processor.

3.2 Main Functions

The operating system is started by the application. The startup module (which is not part of the operating system) calls the function `main`. In the main function, the user has to call the API function `StartOS`. `StartOS` will initialize the operating system, install the interrupt routine for the alarm handling, and then call the scheduler. `StartOS` will never return to the main function.

The function of the scheduler is to evaluate the task with the highest priority in the `READY` state and call this task. If the task was previously pre-empted by another higher priority task, the scheduler resumes the task.

The operating system is controlled by external events. External events can be events from interrupt routines, from the alarm management, or from schedule tables (Alarms and schedule tables are also driven by interrupt service routines). Therefore, any external event will result in the change of task states.




Figure 3-1 Functional parts

Interrupt routines are under the control of the application programmer. An OSEK operating system allows a fast and efficient interrupt handling, so interrupts have a short latency time. It is possible to call certain system functions from interrupt routines. It is necessary that the operating system has knowledge of any existing interrupt routines.

3.2.1 Timer and Alarms

All time-based actions are performed in OSEK using counters, alarms, and schedule tables. Counters are part of the kernel and are incremented by a specific hardware resource or by means of the system service `IncrementCounter`. In case of a time-based counter, the counter is incremented periodically. Alarms and schedule tables have fixed references to counters. MICROSAR OS supports up to 256 counters.

An alarm, if activated, has a certain value. If the referenced counter reaches the given value, a defined action is performed. The action to each alarm is defined by the OIL Configurator and is compiled into the ROM. The alarm value is passed as a parameter to the functions `SetRelAlarm` or `SetAbsAlarm`.

A schedule table, if activated, has a certain starting value. If the referred counter reaches the given value, the first defined action is performed. The further actions are defined relative to this first action. These relative starting times are defined together with the action by the OIL Configurator and compiled into ROM. The starting value is passed as a parameter to the functions `StartScheduleTableRel` or `StartScheduleTableAbs`.

3.2.1.1 Time Base

3.2.1.1.1 Counter Macros

To support the portability of OSEK, application alarm related functions, for example `SetRelAlarm`, should be called using macros for the calculation of ticks based on millisecond or seconds:

```
SetRelAlarm (Alarm1, OS_xx2TICKS_<CounterName> (1200), OS_xx2TICKS_<CounterName> (1200));
```

The macros `OS_TICKS2xx_<CounterName>()` (whereas `xx` denotes NS, US, MS or SEC; described by the AUTOSAR standard) may be used to convert tick values (as returned for example by `GetElapsedTime()` and `GetCounterValue()`) to into a second based timer unit. Additionally, MICROSAR OS provides the inverse macros `OS_xx2TICKS_<CounterName>()` for conversion into the opposite direction (see Figure 2-2).




Figure 3-2 Counter Macros



Caution

Depending on the hardware settings, certain nanosecond times may not be representable accurately.

Therefore, if large times, very small times or very high precision is needed, use AUTOSAR OS `OsTimeConstant` instead (see 7.3.3).

3.2.1.1.2 Temporal Range of Alarms

The temporal range of an alarm depends on the Counter, which drives the alarm. The important configuration attributes here are `OsSecondsPerTick` and `OsCounterMaxAllowedValue` (see 7.3.3).

3.2.1.2 Timer Interrupt Routine

The timer interrupt routines are category 2 ISRs and are part of the operating system. The configuration is done automatically by the OS using information that has to be defined in the OIL Configurator.

3.2.1.2.1 Counter API

To obtain the counter specific limits (e.g. `maxallowedvalue`) the function `GetAlarmBase` can be used.

1.1.1.1.1.1 Initialization

Former versions of osCAN and MICROSAR OS provided the API functions:

```
StatusType InitCounter<CounterName>(TickType ticks);
```

These functions have been removed, as they do not conform to the standardized counter API described in [1]. Instead, counters are always initialized to 0 during `StartOS()`.

1.1.1.1.1.2 Read Counter

MICROSAR OS provides the API functions `GetCounterValue` and `GetElapsedValue` as defined by [1].

Former versions of osCAN and MICROSAR OS provided the API functions:

```
TickType GetCounterValue<CounterName>(void);
```

These functions have been removed, as they do not conform to the standardized counter API described in [1]. It is recommended to use the API function `GetCounterValue` defined by AUTOSAR Standard instead.

1.1.1.1.1.3 Increment Counter

```
StatusType IncrementCounter(CounterType CounterName);
```

This function is the AUTOSAR OS standardized function to trigger a counter.



Example

The ISR that triggers the counter must be of category 2.

```
ISR(MyCounterISR)
{
    IncrementCounter(MyCounter);
}
```

Former versions of osCAN and MICROSAR OS provided the API function

```
void CounterTrigger<CounterName>(void);
```

These functions have been removed, as they do not conform to the standardized counter API described in [1]. It is recommended to use the API function `IncrementCounter` defined by AUTOSAR Standard instead.

3.2.2 Stack Handling

3.2.2.1 Task Stack

Each task has its own stack. The task stack holds all local data and return addresses of the task. In addition, the register context of the task is saved onto the stack if the task is preempted. If the task is transferred to the running state again, the register context is removed from the task stack to restore the previously saved registers.

3.2.2.2 Interrupt Stack

The implementation of interrupt stacks depends on the hardware, and is described in ref. [4].

3.2.2.3 Stack Monitoring

To use this feature, set `STACKMONITORING = TRUE` in the configuration.

If enabled, MICROSAR OS initializes the last useable element of each stack with an indicator value.

This indicator is then checked with each task switch or ISR exit. A change of the element value indicates a stack overflow by the task or ISR. In this case, the system calls the `ErrorHook` (if configured), the `ShutdownHook` (if configured) and enters the shutdown state.



Info

It is highly recommended to use this feature during development



Note

MICROSAR OS checks the indicator value only at task switches and on a return from an ISR. Therefore, stack overflows are not detected immediately. Detection might be delayed arbitrary in case of a stack overflow in a hook routine. Some implementations of MICROSAR OS implement additional checks of the indicator value, see [4]. If memory protection is configured, stack overflows in tasks and ISRs of non-trusted applications are found immediately by the memory protection if the stack is followed by an area with no access rights.

In case a stack fault is detected by memory protection (in SC3 or SC4 systems), the `ProtectionHook` is called with parameter `E_OS_PROTECTION_MEMORY`. If a stack fault is detected by stack monitoring, and a `ProtectionHook` is configured, MICROSAR OS goes into shutdown after the `ProtectionHook`.

3.2.2.4 Stack Sharing

MICROSAR OS assumes that a task always starts on an empty stack. Afterwards, the stack stays valid until the task terminates. Even when the task is preempted for a long time, the stack must not be altered. With this assumption, a group of different basic tasks can use the same memory region for their stack region, when only one of them can start and the rest cannot.

The following subchapters present the configuration settings detected by MICROSAR OS to enable stack sharing for a group of tasks. Please note that stack sharing is never possible for extended tasks, as the major feature of this type of task is the usage of the API function `WaitEvent`. While the extended task waits for an event to occur, any other task might become active, so the basic assumption presented above is not valid.

In case a group of tasks shares a memory region for their stacks, the user can still set the `TASK` attribute `StackSize` for each of the tasks. The biggest setting for `StackSize` in the group of tasks determines the size of the memory region that is reserved by MICROSAR OS.

**Info**

In Scalability Class 3 and 4 these stack sharing mechanisms are only used for tasks which are assigned to the same Application.

3.2.2.4.1 Basic Tasks on the same Priority

Basic tasks cannot start as long as another basic task on the same priority level has started and not yet finished. Therefore, these tasks can share one memory region for their stacks. This is automatically detected by MICROSAR OS, and whenever two or more basic tasks share the same priority level, they use the same memory region for their stack

3.2.2.4.2 Basic non-preemptive Tasks not calling SCHEDULE

Basic non-preemptive tasks can only be preempted if they call the system service `Schedule`. If they do not call this system service, they can share the same memory region for their stacks. Unfortunately, it is not possible for MICROSAR OS to detect automatically before compilation if `Schedule` is called or not. For this reason, the task object in the OIL Configurator provides the attribute `NotUsingSchedule`. By selecting this attribute (setting it to `TRUE`), the user guarantees that the task does not call `Schedule`. So a group of non-preemptive basic tasks that all have the attribute `NotUsingSchedule` set to `TRUE` share the same memory region for their stacks.

When the OS attribute `STATUS` is set to `EXTENDED` and the OS attribute `OSInternalChecks` is selected (set to `TRUE`), MICROSAR OS checks with each call of the system service `Schedule` if the attribute `NotUsingSchedule` was selected for the calling task. In the case that `NotUsingSchedule` was selected but the respective task still calls `Schedule`, an error message is produced.

3.2.2.4.3 Basic Tasks, sharing an internal Resource and not calling SCHEDULE

Basic tasks using an internal resource can only be preempted by other tasks sharing the same resource if they call the system service `Schedule`. So if they do not call this system service, they can share the same memory region for their stacks. Unfortunately, it is not possible for MICROSAR OS to detect automatically before compilation if `Schedule` is called or not. For this reason, the task object in the OIL Configurator provides the attribute `NotUsingSchedule`. By selecting this attribute (setting it to `TRUE`), the user guarantees that the task does not call `Schedule`. So a group of basic tasks that share the same internal resource and all have the attribute `NotUsingSchedule` set to `TRUE` share the same memory region for their stacks.

When the OS attribute `STATUS` is set to `EXTENDED` and the OS attribute `OSInternalChecks` is selected (set to `TRUE`), MICROSAR OS checks with each call of the system service `Schedule` if the attribute `NotUsingSchedule` was selected for the calling task. In the case that `NotUsingSchedule` was selected but the respective task still calls `Schedule`, an error message is produced.

3.2.2.5 Stack Usage

If `StackUsageMeasurement` is set to `TRUE`, the OS fills all available stacks with the indicator value `0xAA` during `StartOS` (startup times will be slower). This allows measuring the amount of stack used since `StartOS` by counting the amount of bytes that have not been overwritten yet.

The following function is available to determine the amount of used stack:

```
osuint16 osGetStackUsage(TaskType taskId)
```

- > Argument: Task number
- > Return value: Maximum stack usage (bytes) by task since call of `StartOS()`

Additional implementations specific functions may be available. Please see the hardware specific part of the documentation of this implementation [4].



Caution

Dependent on the stack size, the measurement operation can take a long time.

3.2.3 Interrupt Handling

Implementation specific details about interrupt handling are described in the hardware specific part of this implementation [4].



Caution

Knowledge about the interrupt handling is very important. If interrupt routines are used it is essential to read this chapter.

3.2.3.1 Interrupt Categories

The OSEK OS specification defines two groups of interrupts.

3.2.3.1.1 Category 1:

Interrupts of category 1 are in general not allowed to use API functions; as such, these routines can be programmed without restrictions and are completely independent from the kernel. The programming conventions depend on the utilized compiler and assembler.

Category 1 interrupts can be enabled before call of `StartOS()`. If interrupts of category 1 and 2 cannot be disabled separately, all interrupts must be disabled.

Interrupts of category 1 are allowed to call the interrupt API as an exception to the rule presented above. If the interrupt API is used and the category 1 interrupts are enabled before the call of `StartOS`, the user has to take care about variable initialization of the interrupt API, as described in chapter [3.2.3.2](#).

1.1.1.1.4 Exceptions and SC2, SC3, SC4

According to the AUTOSAR-Standard, category 1 interrupts should be avoided with SC2, SC3 and SC4. MICROSAR OS does not allow category 1 interrupts with `TimingProtection`. Because non-maskable interrupts need to be configured to category 1, some MICROSAR OS implementations allow exceptions even with timing protection.

The user may write "normal" interrupt code in an exception routine, which returns to the application. Please note that this sort of exception routines will cause the exception handler to add runtime to the account of the interrupted task or ISR.

3.2.3.1.2 Category 2:

Interrupts of category 2 may use certain restricted API functions. Interrupts of category 2 can be programmed as normal C functions using the macro `ISR(name)`. The C function is called by the operating system. The necessary preparation for the interrupt routine is done automatically by a generated function.

```
ISR (AnInterruptRoutine)
{
    /* code with API calls */
}
```



Caution

Category 2 interrupts must be disabled until call of `StartOS()`! This also applies for the timer interrupts, i.e. this interrupt must be stopped by the user at a software reset.

To ensure data consistency, the operating system needs to disable category 2 interrupts during critical sections of code. Therefore, applications must not use non-maskable interrupts as category 2 interrupts.

3.2.3.2 Usage of the Interrupt API before StartOS

The usage of the interrupt API functions is in general allowed before the operating system is started. The affected functions are:

- > `DisableAllInterrupts`, `EnableAllInterrupts`
- > `SuspendAllInterrupts`, `ResumeAllInterrupts`
- > `SuspendOSInterrupts`, `ResumeOSInterrupts`

However, these functions use some internal variables that have to be initialized to zero before the first call of the interrupt API. Typically, this initialization is performed by the startup code (which might be delivered with the compiler). In case no startup code is used, the function `osInitialize()` needs to be called. `osInitialize` initializes the variables which are used in the interrupt API.

3.2.4 Timing Protection

The timing protection is implemented in the Scalability Classes 2 and 4. This chapter provides some hints on the functionality according to the AUTOSAR OS standard [1] and describes additional functionality provided by Vector MICROSAR OS. To enable the timing protection of a task or ISR, the OIL-attribute `TIMING_PROTECTION` of the respective task or ISR needs to be configured, as described in chapters 7.3.2.2 and 7.3.7.2 . (AUTOSAR XML: `OsTaskTimingProtection/OsIsrTimingProtection`).



Caution

The runtime of all tasks and ISRs is observed, however parts of the time for task switch and interrupt entry/exit cannot be monitored by the timing protection. Therefore, some extra time for task switches and interrupt entry/exit needs to be considered in the configuration of the timing protection.



Caution

Timing Protection is implemented with interrupts. If the application manually disables interrupts anywhere, the timing protection cannot work as expected. In order to enable and disable interrupts, the application **must** use the following API functions:

- > `DisableAllInterupts, EnableAllInterrupts`
- > `SuspendAllInterrupts, ResumeAllInterrupts`
- > `SuspendOSInterrupts, ResumeOSInterrupts`



Caution

The timing protection works very precise. However, if an OS API function is called by a task/ISR, the OS may enter a critical section; if a timing protection violation is detected while the system is in a critical section, the call of the protection hook may be delayed until the end of the critical section. Note, that critical sections in AUTOSAR OS are very short.

3.2.4.1 Reaction on Protection Failure

To provide a more efficient version of the OS, it is possible to select in OIL which reactions to the ProtectionHook are possible.

If only Shutdown is selected, SC2 runs with the best performance.

3.2.4.2 Timing Measurement

MICROSAR OS is not only able to provide timing protection but allows using the same functionality for timing measurement. If timing measurement is performed for a specific task or ISR, the OS measures the following times for that task or ISR:

- > the maximum run time since `StartOS`

- > the maximum locking times for resources and interrupts since StartOS
- > the minimum time distance between two arrivals since StartOS

The debugger can read the result of the timing measurement via ORTI. Alternatively, the application may use the timing measurement API as described in chapter 6.4.

The OS attribute `TimingMeasurement` and the task/ISR attribute `TIMING_PROTECTION` are provided to setup timing protection and measurement.

The hardware timers and internal data structures to store measured times are limited in size. When this limit is exceeded by any measured time (e.g. of a resource or interrupt lock), the `ErrorHook` function is called and the system goes into shutdown state.

3.2.4.2.1 Timing measurement configuration for a specific task/ISR

Timing measurement can be configured individually for each task and ISR. As timing protection requires the OS to measure the timing values, timing measurement is performed for all tasks and ISRs that have timing protection configured by means of the attribute `TIMING_PROTECTION`. By selecting the sub attribute `OnlyMeasure`, the OS disables the timing protection but still measures the timing values. Please note that this configuration might be overridden by means of the global configuration, described in the next chapter.

3.2.4.2.2 Global configuration of timing measurement

In order to save configuration time, the timing measurement can be configured globally for all tasks and ISRs. MICROSAR OS provides the OIL-attribute `TimingMeasurement` (AUTOSAR XML: `OsOSTimingMeasurement`) for that purpose. That attribute provides the possibilities to:

- > Disable the timing measurement globally. This is an optimization to save memory and runtime of the timing measurement. Please set the attribute `TimingMeasurement` to `FALSE` (deselect it) for this configuration.
- > Collect timing data for all tasks and ISRS. The collected timing values can be used to perform scheduleability analysis and to set up the timing protection later on. For this configuration, please set the attribute `TimingMeasurement` to `TRUE` (select it) and choose `OnlyMeasureAll` for the value of the sub attribute `GlobalConfig`.
- > Perform timing measurement as configured for the task or ISR. Set the attribute `TimingMeasurement` to `TRUE` (select it) and select `AsSelected` for the value of the subattribute `GlobalConfig` to achieve this.
- > Ignore the task/ISR attribute `OnlyMeasure` (perform timing measurement and protection as if this attribute was set to `FALSE`). For this configuration, please set the attribute `TimingMeasurement` to `TRUE` (select the attribute) and select `ProtectAndMeasureAll` for the value of the subattribute `GlobalConfig`.

The chapter 7.3.2.2 provides a description of the attribute `TIMING_PROTECTION` for tasks while chapter 7.3.7.2 provides the respective description for ISRs. Chapter 7.3.1.4 provides a description of the attribute `TimingMeasurement`. The table below documents the interdependence between the OS-attribute `TimingMeasurement` and the task/ISR-Attribute `TIMING_PROTECTION`.

OS		TASK/ISR		
Timing-Measurement	Global-Config	TIMING_PROTECTION		
		FALSE	TRUE	
			OnlyMeasure FALSE	TRUE
FALSE ¹		No timing protection, no timing measurement,	Timing protection but no timing measurement	Timing protection but no timing measurement, warning as the sub attribute OnlyMeasure is overridden
TRUE	Only-Measure-All	No timing protection but timing measurement	No timing protection but timing measurement, warning as the sub attribute OnlyMeasure is overridden	No timing protection but timing measurement
	AsSelected	No timing protection and no timing measurement	Timing protection and measurement	No Timing protection but timing measurement
	ProtectAnd-MeasureAll	No timing protection but timing measurement	Timing protection and measurement	Timing protection and measurement, warning as the sub attribute OnlyMeasure is overridden.

Table 3-3 Interdependence between the OS attribute `TimingMeasurement` and the task/ISR attribute `TIMING_PROTECTION`

3.2.4.3 Hook functions

The runtime of the hook functions `PreTaskHook` and `PostTaskHook` (Chapters 6.6.2 and 6.6.3) is considered to belong to the runtime of the currently active task.



Caution

Depending on the implementation, the execution of the `ProtectionHook` might be delayed until the `PreTaskHook` or `PostTaskHook` has finished. In case of a protection violation during the `PostTaskHook` while a task state change into the states `SUSPENDED` or `WAITING`, the call of the `ProtectionHook` gets lost. Therefore, the `PreTaskHook` and the `PostTaskHook` should be used for debugging purposes only. If these functions are used in safety critical applications, extra care is necessary.

The runtime of the hook functions `UserPreIsrHook` and `UserPostIsrHook` (Chapters 6.6.7 and 6.6.8) is considered to belong to the runtime of the currently active ISR.

3.2.5 Memory Protection

MICROSAR OS uses the MPU of the microcontroller to implement memory protection as described in [1]. Former versions of MICROSAR OS fulfilled the AUTOSAR requirement OS195 and prevented write access to Task/ISR private data areas even within an

¹ Optimization: The timing measurement API is unavailable

OSApplication. This behaviour is defined as optional by AUTOSAR and not implemented in most current versions of MICROSAR OS. It is explicitly mentioned in [5] if supported.

3.2.6 Schedule Tables

MICROSAR OS implements schedule tables as defined by the AUTOSAR standard. The document [1] provides the base description of schedule tables and their usage. This chapter is meant as an extension that clarifies and corrects some points, provides details about points left open and describes corrections and extensions by MICROSAR OS.

AUTOSAR defines schedule tables for all scalability classes, but synchronization to a global time only for SC2 and SC4. MICROSAR OS offers some additional error checking to the AUTOSAR standard.

3.2.6.1 Synchronization

In SC2 and SC4 or the High-Resolution Schedule Tables option, it is possible to synchronize a schedule table to a global time source. The schedule table must be marked with the OIL attribute `LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION`.

3.2.6.1.1 Starting a synchronizable Schedule Table

One way to start a synchronizable schedule table is to use the functions `StartScheduleTableRel(Tablename, TimeOffset)` and `StartScheduleTableAbs(Tablename, Time)`. The time parameters refer to the local time and not to the global time. It is assumed that the schedule table will not have an offset to global time: when synchronization starts, the start of the schedule table is moved to global time zero. Note that the schedule table always starts at the stated start time. A call of `SyncScheduleTable` does not influence this start time. Synchronization starts after execution of the first expiry point.

The recommended way to start a synchronizable schedule table is to use the combination of `StartScheduleTableSynchron(Tablename)` and `SyncScheduleTable()`. The first expiry point is executed at global time 0. The schedule table starts execution after a global time is available, i.e. after calling `SyncScheduleTable()` for the schedule table. If `SyncScheduleTable()` is never called for the schedule table, the schedule table is never executed. The following algorithm describes a possibility to set up a timeout:

Set up an alarm to the timeout time. When the alarm expires and `GetScheduleTableStatus()` indicates that the schedule table is still waiting, call `SyncScheduleTable()` with an arbitrary time. Note: if the call to `SyncScheduleTable()` is done in an interrupt, it may occur between the two API calls, and thus gets overridden by the arbitrary time.

3.2.6.1.2 Autostart

For an automatic start of a schedule table on startup of the OS, the attribute `AUTOSTART` must be set. The sub-attribute `TYPE` defines how the start is performed. The possibilities are: `ABSOLUT`, `RELATIVE` and `SYNCHRON`. These types of autostart are similar to the normal start of a schedule table using `StartScheduleTableAbs`, `StartScheduleTableRel` or `StartScheduleTableSynchron`. For `ABSOLUT` and `RELATIVE`, an absolute or relative start time needs to be provided. In case of `SYNCHRON`,

the schedule table starts after `SyncScheduleTable` has been called and the global time reaches zero.

Note, that just like for `StartScheduleTableSynchron()`, the schedule table will wait forever if `SyncScheduleTable()` is never called.

3.2.6.1.3 Suspending a Schedule Table and keeping its Synchronization

The AUTOSAR standard does not define a way to suspend the execution of a schedule table and keep its synchronization for later restart. The suggested approach is to use `NextScheduleTable()` to append a schedule table that effectively does nothing.

Currently, AUTOSAR does not define a way to retrieve the internal schedule table time (neither the currently estimated global time nor the time relative to the first expiry point of the schedule table).

3.2.6.1.4 Providing a Global Time

The current global time is handed to the schedule table via `SyncScheduleTable()`. If a deviation of the schedule table to the global time is found, the schedule table starts to synchronize at the next expiry point that allows synchronization.

The global time must be a continuous range of integers: So e.g. FlexRay's time tuple (cycle, macroticks) cannot directly be used as global time, but must be converted.

The provided global time must have the same resolution as the local time and the same period as the schedule table time (i.e. the `LENGTH` of the schedule table). If this is not the case, it must be converted before being handed to `SyncScheduleTable()`.



Example

Converting the FlexRay time:

Be `gMacroPerCycle` the number of macroticks per cycle, `cycle` the current cycle number, `macroticks` the current macrotick number and `f` is the factor to convert the FlexRay tick length the HW counter tick length:

```
GlobalTime = (gMacroPerCycle * cycle + macroticks) * f
```

3.2.6.1.5 Exact Synchronization

There is always a time span between reading the global time and handing it to the operating system. Therefore, synchronization is never absolutely exact.

If an interrupt interferes, the time span may be unexpectedly large. While this may be ignorable if the resolution is large compared with the interrupt running times, it is noticeable when using a fine grained global time, for example in conjunction with High-Resolution Schedule Tables, or if some (higher prior) interrupts have long running times. It is desirable to be undisturbed by (higher prior) interrupts during synchronization.

The AUTOSAR Standard demands, that calling any API functions is not allowed in between function pairs

```
DisableAllInterrupts/EnableAllInterrupts,
SuspendAllInterrupts/ResumeAllInterrupts,
SuspendOSInterrupts/ResumeOSInterrupts.
```

MICROSAR OS makes an exception from the standard in this point: `SyncScheduleTable()` can be called in between these function pairs.

Therefore, a Sync procedure may look like the following example:

```
DisableAllInterrupts();
now=getCurrentGlobalTime();
SyncScheduleTable(MyScheduleTable, now);
EnableAllInterrupts();
```



Caution

This is unnecessary if `SyncScheduleTable()` is called from an interrupt which does not allow nesting.

Also note, that `SuspendAllInterrupts()/DisableAllInterrupts()` still allow timing protection interrupts (if timing protection is used).

3.2.6.1.6 Limits of the Synchronization Algorithm

The synchronization algorithm as described by the AUTOSAR standard only corrects deviations of the past – it does not make assumptions about deviations of the present or the future. Differences in clock speed (between local time and global time) are not completely compensated.

Simplified synchronization algorithm: When `SyncScheduleTable` is called, the difference between the local schedule table time and the provided global time is computed and stored internally. Nothing more happens until an expiry point expires. Then, the times between subsequent expiry points are adapted. The adaptation stops once the computed deviation is compensated or a new global time is provided. In case new deviations between the global and local time occur, they are considered after the next call of `SyncScheduleTable` in the same way as just described.

As a result of this algorithm, a permanent deviation in the speed of global and local clock might not be compensated completely.



Example

The local schedule table time² runs 10 % slower than the global time. Whenever the global time reaches a multiple of 100, the function `SyncScheduleTable` is called to provide the global time to the schedule table. Both times start simultaneously at zero. When the global time reaches 100, the local time is 90 because of the 10 % difference. `SyncScheduleTable` is called, and computes a difference of 10. We assume now that the difference is compensated until the next call of `SyncScheduleTable` occurs. The local time is then: $90 + 10 + 90 = 190$ while the global time is 200. Again we have the same difference, so 10 needs to be corrected. The same occurs for all subsequent calls of `SyncScheduleTable`, too.

² The local time is based on the MCU's internal clock.

Although the computed difference between current time values of global and local time is corrected, the same difference occurs in the next synchronization step. However, using synchronization the deviation stays constant. Without synchronization, it would accumulate.

3.2.6.1.7 Details about using `NextScheduleTable`

The AUTOSAR standard leaves open certain details of using `NextScheduleTable` with synchronizable schedule tables. The following describes the implementation of `NextScheduleTable` MICROSAR OS.

If two schedule tables are chained using the API function `NextScheduleTable()`, the second schedule table takes over the synchronized schedule table time of the predecessor³.

When switching to a schedule table that does not allow synchronization, the remaining difference to the global time is saved: upon switching to a schedule table that allows synchronization it will immediately start to synchronize.

3.2.6.1.8 Concurrent Actions

If a task is activated at an expiry point, and an event for this task is set at the same expiry point, always all tasks will be activated before events are set. However, if two schedule tables are using the same counter; one of these schedule tables activates a task and the other schedule table sets an event for this task at the same time, the behaviour is undefined.

3.2.6.2 High-Resolution Schedule Tables

AUTOSAR schedule tables are driven by a counter (hardware or software), and thus offer the same resolution. While it is possible to configure a higher resolution for the counter, this increases also the interrupt load. High-Resolution Schedule Tables offer a microsecond resolution or better⁴ without unnecessary additional interrupt load: At each expiry point, a timer interrupt is reprogrammed so it will be reactivated exactly at the following expiry point⁵.

Note that high resolution schedule tables are not supported by all MICROSAR OS implementations.

It is possible to use standard schedule tables and High-Resolution Schedule Tables at the same time. High-Resolution Schedule Tables support the full AUTOSAR API, including synchronization (see 3.2.5.1) and are particularly suited for FlexRay.

³ Therefore, if the two schedule tables have a different `LENGTH`, switching from one to the other is undefined: it may work, but may also lead to unexpected results. This is not checked at runtime (and cannot be checked at generation time).

⁴ The actually achievable best resolution depends on the hardware, hardware settings and application

⁵ while the activation of the schedule table handler is done as exact as the underlying counter (the hardware) allows it, a certain time span will expire until the expiry point is actually processed. Interrupts, non-preemptive tasks and interrupt disabling times impose an additional jitter.

3.2.6.2.1 Setup

To create a High-Resolution Schedule Table, create a Schedule Table and choose any High-Resolution Counter as the underlying counter. This counter is available only on the MICROSAR OS implementations that support high resolution schedule tables; it is automatically available if supported.

3.2.6.3 Cyclical Expiry Point Actions

Cyclical expiry point actions are a Vector specific extension of the AUTOSAR Standard to ease the configuration of schedule table actions. In case an expiry point action shall be executed cyclicly within a schedule table, the user may select the sub-attribute `Cyclic`. This allows him to define a cycle time in the sub-attribute `CycleTime`. This informs the generator that the expiry point action shall occur repeatedly with the configured cycle time starting at the offset of the expiry point, the action belongs to.

In case, the sub-attributes `Cyclic` and `CycleTime` have been configured, the generator of the OS copies the expiry point actions to the configured locations within the schedule table before it generates the schedule table. In case, there is already an expiry point at a location where a cyclical expiry point action shall occur, the cyclical action is simply added to the actions of that expiry point. In case there is no expiry point configured at the location where a cyclical expiry point action shall occur, the generator invents an expiry point. Please note that generator invented expiry points do not allow synchronization as there is no configuration of the synchronization step width possible.

3.2.7 Service Protection

Service Protection is relevant for SC3 and SC4. Some features of the Service Protection effecting also SC1 and SC2 are described below.

3.2.7.1 Missing TerminateTask

SC1 and SC2:

In the scalability classes SC1 and SC2, a missing call of `TerminateTask` at the end of a task is detected only if the OS attribute `STATUS` is set to `EXTENDED`. In case, a missing call of `TerminateTask` is detected, MICROSAR OS calls the `ErrorHook` with the error number `E_OS_MISSINGEND` and after that calls `ShutdownOS`. (A release of resources is not performed for SC1 and SC2.)

3.2.7.2 Call of System Services with Interrupts disabled

SC1 and SC2:

In the scalability classes SC1 and SC2, the call of a system service with disabled interrupts is detected only if the OS attribute `STATUS` is set to `EXTENDED`. This detection is only possible when the OSEK system services for interrupt disabling and enabling are used exclusively. The reason is that most of the system services can be called from interrupt level, where at least some interrupts are disabled by the hardware.

In the case that a call of a system service with disabled interrupts is detected, the error hook is called with the error number `E_OS_DISABLEDINT` and the system service is not performed. The system service returns `E_OS_DISABLEDINT`.

This detection is quite similar to the detection of a system call with disabled interrupts in osCAN/OSEK OS, but in osCAN, this test was performed only when the attribute `OSInternalChecks` was set to `Additional` and the error number reported was `E_OS_SYS_DIS_INT`.

3.2.8 Trusted Functions

Trusted functions are available for SC3 and SC4 only. MICROSAR OS OSEK/AUTOSAR provides two possibilities to call trusted functions: by direct call of API function `CallTrustedFunction` or by using generated stub functions.

It is possible to mix applications using direct calls and applications using generated stub functions.



Caution

Inside trusted functions there is full access to all memory. Therefore, each trusted function with address arguments for return values must check the access rights of the caller before writing results through an address argument. The API provides the functions `CheckTaskMemoryAccess` and `CheckISRMemoryAccess` for address checking.

3.2.8.1 Generated Stub Functions

The generation of stubs for trusted functions is a Vector specific extension of the AUTOSAR OS standard to ease the usage of trusted functions.

To enable stub generation for an application, the `TRUSTED` attribute of this application and the sub-attribute `GenerateStub` must be set to `TRUE`.

In this case, a caller stub with the name `Call_<name>` is generated for each trusted function of the application, where `<name>` is the name of the trusted function. The generated stub function `Call_<name>` packs its parameters into a structure as needed by the standard API function `CallTrustedFunction` and calls that API function. Another generated stub function performs an unpacking of the parameters so that the user's trusted function does not need to get all the parameters via one pointer, but can have a set of parameters and a return value like any legal C-function.

In case the sub-attribute `GenerateStub` is set to `TRUE`, the user has to define the parameters and the return value of the trusted function as well. The sub-attribute `Params` shall contain a comma-separated list of type and parameter name (as they would occur in a function definition in C). The sub-attribute `ReturnType` shall define the return type of the function.

The stubs are generated into the file `trustfct.c`.

See [10.8](#) for an example using generated stub functions for trusted applications.

**Caution**

The generator does not produce prototypes for the trusted functions to be called by the trusted function stubs. The prototypes shall be provided by the writer of these functions and included into the file `usrotyp.h`. Parameter types and the return type need to be defined there also in case they are no simple types of the C-language. The file `usrotyp.h` is described in chapter 5.2.

3.3 Error Handling

3.3.1 Error Messages

If the kernel detects errors, the OSEK error handling is called. The hook routine `ErrorHook` is called if selected.

Depending on the situation in which an error was detected the error handling will return to the current active task or the system will be shut down.

3.3.2 OSEK / AUTOSAR OS Error Numbers

The OSEK specification defines several error numbers that are returned by the API functions. A certain error number has different meanings for different API functions. The user has to know the API function to interpret the error number correctly.

With the AUTOSAR OS specification, the range of error numbers was extended. The following table shows all specified error numbers.

Error Code		Description
0	E_OK	Service executed successfully
1	E_OS_ACCESS	Several APIs: general access of object failure
2	E_OS_CALLEVEL	Several APIs: service accessed from wrong context
3	E_OS_ID	Several APIs: service called with wrong ID
4	E_OS_LIMIT	Several APIs: service called too often
5	E_OS_NOFUNC	Several APIs: (warning) service not executed
6	E_OS_RESOURCE	Several APIs: service called with occupied resource
7	E_OS_STATE	Several APIs: object is in wrong state
8	E_OS_VALUE	Several APIs: passed parameter has wrong value
9	E_OS_SERVICEID	Several APIs: service can not be called
10	E_OS_ILLEGAL_ADDRESS	Several APIs: invalid address passed
11	E_OS_MISSINGEND	Several APIs: task terminated without TerminatTask
12	E_OS_DISABLEDINT	Several APIs: service called with disabled interrupts
13	E_OS_STACKFAULT	Stack monitoring detected fault
14	E_OS_PROTECTION_MEMORY	Memory access violation
15	E_OS_PROTECTION_TIME	Execution time budget exceeded
16	E_OS_PROTECTION_ARRIVAL	Arrival before the timeframe expired
17	E_OS_PROTECTION_LOCKED	Task/ISR blocked too long (e.g. by disabled interrupts)
18	E_OS_PROTECTION_EXCEPTION	A trap occurred

Table 3-4 OSEK/AUTOSAR OS error numbers

The additional implementation specific error numbers are defined as:

Error Code		Description
20	E_OS_SYS_ASSERTION	This error is generated if the kernel detects an internal inconsistency. The reason and an exact explanation is described below.
21	E_OS_SYS_ABORT	This error is generated if the kernel has to shut down the system but the reason was not an API function.
22	E_OS_SYS_DIS_INT	This error number is no longer used. It is replaced by the AUTOSAR OS conformant number E_OS_DISABLEDINT.
23	E_OS_SYS_API_ERROR	This error is generated if an error occurs in an API function and there is no error code specified in the OSEK specification. The reason and an exact explanation is described below.
24	E_OS_SYS_ALARM_MANAGEMENT	A general warning issued in certain cases involving the alarm management. Detailed description in the implementation specific manual
25	E_OS_SYS_WARNING	A general warning issued in certain cases. Detailed description in the implementation specific manual.

Table 3-5 Implementation specific error numbers

More implementation specific errors may be described in ref. [4].

3.3.3 MICROSAR OS Error Numbers

In addition to the OSEK error numbers, all MICROSAR OS implementations provide unique error numbers for an exact error description. All error numbers are defined as a 16-bit value. The error numbers are defined in the header file `osekerr.h` and are defined according to the following syntax:

```
0xgfee
| |+--- consecutive error number
| +---- number of function in the function group
+----- number of function group
```

The error numbers common to all MICROSAR OS implementations are described below. The implementation specific error numbers have a function group number $\geq 0xA000$ and are described in the document [4].

To access these error numbers the `ERRORHOOK` has to be enabled. The numbers are then accessible via the macro `OSErrorGetosCANError()`.

Error Types:

Error Type	Description
OSEK	OSEK / AUTOSAR error. After calling the <code>ErrorHook</code> , the program is continued.
assertion	System assertion error. After calling the <code>ErrorHook</code> the operating system is shut down. Assertion checking is enabled by setting the attribute <code>OSInternalChecks</code> to <code>Additional</code> and the attribute <code>STATUS</code> to <code>EXTENDED</code> in the OIL Configurator.

Error Type	Description
syscheck	System error. After calling the <code>ErrorHook</code> the operating system is shut down. Refer to the specific error for a description how to enable or disable error checking.

Table 3-6 Error types

3.3.3.1 Error Numbers of Group Task Management / (1)

Group (1) contains the functions:

API Function	Abbreviation	Function Number
ActivateTask	AT	1
TerminateTask	TT	2
ChainTask	HT	3
Schedule	SH	4
GetTaskState	GS	5
GetTaskID	GI	6
osMissingTerminateError	MT	7

Table 3-7 API functions of group Task Management / (1)

Error numbers of group (1):

Error Code		Description	
		Error Type	Reason
0x1101	osdErrATWrongTaskID	OSEK	Called with invalid task ID
0x1102	osdErrATWrongTaskPrio	assertion	Task has wrong priority level
0x1103	osdErrATMultipleActivation	OSEK	number of activation of activated task exceeds limit
0x1104	osdErrATIntAPIDisabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x1105	osdErrATAAlarmMultipleActivation	OSEK	Number of activation of activated task exceeds limit (task activation is performed by alarm-expiration or expiry point action)
0x1106	osdErrATNoAccess	OSEK	Calling application has no access rights for this task
0x1107	osdErrATCallContext	OSEK	Called from invalid call context
0x1108	osdErrATWrongAppState	OSEK	Referenced object is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x1201	osdErrTTDisabledInterrupts	OSEK	<code>TerminateTask</code> called with disabled interrupts
0x1202	osdErrTTResources	OSEK	<code>TerminateTask</code> called with occupied

Error Code		Description	
		Error Type	Reason
	Occupied		resources
0x1203	osdErrTTNotActivated	assertion	TerminateTask attempted for a task with activation counter == 0 (not activated)
0x1204	osdErrTTOnInterrupt Level	OSEK	TerminateTask called from an interrupt service routine
0x1205	osdErrTTNoImmediate TaskSwitch	assertion	TerminateTask has tried to start the Scheduler without success.
0x1206	osdErrTTCallContext	OSEK	Called from invalid call context
0x1208	osdErrTTWrongActiveTaskID	assertion	Task index is not valid during call of TerminateTask
0x1301	osdErrHTInterrupts Disabled	OSEK	ChainTask called with disabled interrupts
0x1302	osdErrHTResources Occupied	OSEK	ChainTask called with occupied resources
0x1303	osdErrHTWrongTaskID	OSEK	New task has invalid ID
0x1304	osdErrHTNotActivated	assertion	Tried to terminate a task which have an activation counter which is zero
0x1305	osdErrHTMultiple Activation	OSEK	Number of activation of new task exceeds limit
0x1306	osdErrHTOnInterrupt Level	OSEK	ChainTask called on interrupt level
0x1307	osdErrHTWrongTask Prio	assertion	ChainTask was called from wrong priority level
0x1308	osdErrHTNoImmediate TaskSwitch	assertion	ChainTask has tried to activate the Scheduler without success.
0x1309	osdErrHTCallContext	OSEK	Called from invalid call context
0x130A	osdErrHTNoAccess	OSEK	Calling application has no access rights for this task
0x130B	osdErrHTWrongAppState	OSEK	Referenced object is owned by an OSApplication which was terminated.
0x130D	osdErrHTWrongActiveTaskID	assertion	Task index is not valid during call of ChainTask
0x1401	osdErrSHInterrupts Disabled	OSEK	Schedule called with disabled interrupts
0x1402	osdErrSHOnInterrupt Level	OSEK	Schedule called on interrupt level
0x1403	osdErrSHScheduleNot Allowed	assertion	Schedule called from task with enabled stack sharing by setting NotUsingSchedule in the OIL Configurator
0x1405	osdErrSHResources Occupied	OSEK	Called with an occupied resource

Error Code		Description	
		Error Type	Reason
0x1406	osdErrSHCallContext	OSEK	Called from invalid call context
0x1409	osdErrSHWrongActiveTaskID	assertion	Task index is not valid during call of Schedule
0x1501	osdErrGSWrongTaskID	OSEK	Called with invalid task ID
0x1502	osdErrGSIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x1503	osdErrGSIllegalAddr	OSEK	Caller has no write access rights for address argument
0x1504	osdErrGSCallContext	OSEK	Called from invalid call context
0x1505	osdErrGSNoAccess	OSEK	Calling application has no access rights for this task
0x1506	osdErrGSWrongAppState	OSEK	Referenced object is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x1507	osdErrGSOddInvocation	assertion	Invocation of internal function osGetTaskState detected although ReducedStatusChecks was enabled
0x1601	osdErrGIIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x1602	osdErrGIIllegalAddr	OSEK	Caller has no write access rights for address argument.
0x1603	osdErrGICallContext	OSEK	Called from invalid call context
0x1604	osdErrGIOddInvocation	assertion	Invocation of internal function osGetTaskID detected although ReducedStatusChecks was enabled
0x1701	osdErrMTMissing TerminateTask	syscheck	Exit of task without the call of TerminateTask or ChainTask. This error is detected in EXTENDED STATUS only.

Table 3-8 Error numbers of group Task Management / (1)

3.3.3.2 Error Numbers of Group Interrupt Handling / (2)

Group (2) contains the functions:

API Function	Abbreviation	Function Number
EnableAllInterrupts	EA	4
DisableAllInterrupts	DA	5
ResumeOSInterrupts	RI	6
SuspendOSInterrupts	SI	7
osUnhandledException	UE	8

API Function	Abbreviation	Function Number
osSaveDisableLevelNested	SD	9
osRestoreEnableLevelNested	RE	A
osSaveDisableGlobalNested	SG	B
osRestoreEnableGlobalNested	RG	C
ResumeAllInterrupts	RA	D
SuspendAllInterrupts	SA	E
GetISRID	II	2
Interrupt Exit (SC3 only)	IX	3

Table 3-9 API functions of group Interrupt Handling / (2)

Error numbers of group (2):

Error Code		Description	
		Error Type	Reason
0x2401	osdErrEAIntAPIWrong Sequence	assertion	DisableAllInterrupts not called before
0x2501	osdErrDAIntAPI Disabled	assertion	Interrupts are disabled with functions provided by OSEK
0x2801	osdErrUEUnhandled Exception	syscheck	An unhandled exception or interrupt was detected. This error check is always enabled.
0x2901	osdErrSDWrongCounter	assertion	Wrong counter value detected
0x2A01	osdErrREWongCounter	assertion	Wrong counter value detected
0x2B01	osdErrSGWrongCounter	assertion	Wrong counter value detected
0x2C01	osdErrRGWrongCounter	assertion	Wrong counter value detected
0x2201	osdErrIIIntAPI Disabled	OSEK	GetISRID was called with interrupts disabled.
0x2202	osdErrIICallContext	OSEK	Called from invalid call context
0x2301	osdErrIXResources Occupied	OSEK	An ISR of category 2 was left with resources still occupied.
0x2302	osdErrIXIntAPI Disabled	OSEK	An ISR of category 2 was left with interrupts disabled by DisableAllInterrupts, SuspendAllInterrupts or SuspendOSInterrupts

Table 3-10 Error numbers of group Interrupt Handling / (2)

3.3.3.3 Error Numbers of Group Resource Management / (3)

Group (3) contains the functions:

API Function	Abbreviation	Function Number
GetResource	GR	1
ReleaseResource	RR	2

Table 3-11 API functions of group Resource Management / (3)

Error numbers of group (3):

Error Code		Description	
		Error Type	Reason
0x3101	osdErrGRWrongResourceID	OSEK	Invalid resource ID
0x3102	osdErrGRPRIORITYOccupied	assertion	Ceiling priority of the specified resource already in use
0x3103	osdErrGRResourceOccupied	OSEK	Resource already occupied
0x3104	osdErrGRNoAccessRights	assertion	Task has no access to the specified resource
0x3105	osdErrGRWrongPrio	OSEK	Specified resource has a wrong priority. Possible reason: the task has no access rights to this resource.
0x3106	osdErrGRIntAPIDisabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x3107	osdErrGRNoAccess	OSEK	Calling application has no access rights for this resource
0x3108	osdErrGRCallContext	OSEK	Called from invalid call context
0x3109	osdErrGRISRNoAccessRights	OSEK	Calling ISR has no access rights for this resource
0x310B	osdErrGRWrongTaskID	assertion	Task index is not valid during call of GetResource
0x3201	osdErrRRWrongResourceID	OSEK	Invalid resource ID
0x3202	osdErrRRCeilingPriorityNotSet	assertion	Ceiling priority of the resource not found in the ready bit field
0x3203	osdErrRRWrongTask	assertion	Resource occupied by a different task
0x3204	osdErrRRWrongPrio	OSEK	Specified resource has a wrong priority. Possible reason: the task has no access rights to this resource.
0x3206	osdErrRRNotOccupied	OSEK	The specified resource is not occupied by the task
0x3207	osdErrRRWrongSequence	OSEK	At least one other resource must be released before

Error Code		Description	
		Error Type	Reason
0x3208	osdErrRRIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x3209	osdErrRRNoAccess	OSEK	Calling application has no access rights for this resource
0x320A	osdErrRRCallContext	OSEK	Called from invalid call context
0x320B	osdErrRRISRNoAccess Rights	OSEK	Calling ISR has no access rights for this resource
0x320D	osdErrRRNoReadyTaskFound	assertion	No valid priority found when calling ReleaseResource
0x320E	osdErrRRWrongTaskID	assertion	Task index is not valid during call of ReleaseResource
0x320F	osdErrRRWrongHighRdyPrio	assertion	No valid high ready priority task index during call of ReleaseResource

Table 3-12 Error numbers of group Resource Management / (3)

3.3.3.4 Error Numbers of Group Event Control / (4)

Group (4) contains the functions:

API Function	Abbreviation	Function Number
SetEvent	SE	1
ClearEvent	CE	2
GetEvent	GE	3
WaitEvent	WE	4

Table 3-13 API functions of group Event Control / (4)

Error numbers of group (4):

Error Code		Description	
		Error Type	Reason
0x4101	osdErrSEWrongTaskID	OSEK	Invalid task ID
0x4102	osdErrSENotExtended Task	OSEK	Cannot SetEvent to basic task
0x4103	osdErrSETaskSuspended	OSEK	Cannot SetEvent to task in SUSPENDED state. The error code might occur in case of API call SetEvent or in case of alarm/schedule table action to set an event.
0x4104	osdErrSEWrongTask Prio	assertion	Wrong task priority detected

Error Code		Description	
		Error Type	Reason
0x4105	osdErrSEIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x4106	osdErrSECallContext	OSEK	Called from invalid call context
0x4107	osdErrSENoAccess	OSEK	Calling application has no access rights for this task
0x4108	osdErrSEWrongAppState	OSEK	Referenced task is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x4201	osdErrCENotExtended Task	OSEK	A basic task cannot clear an event
0x4202	osdErrCEOnInterrupt Level	OSEK	ClearEvent called on interrupt level
0x4203	osdErrCEIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x4204	osdErrCECallContext	OSEK	Called from invalid call context
0x4301	osdErrGEWrongTaskID	OSEK	Invalid task ID
0x4302	osdErrGENotExtended Task	OSEK	Cannot GetEvent from basic task
0x4303	osdErrGETaskSuspended	OSEK	Cannot GetEvent from a task in SUSPENDED state
0x4304	osdErrGEIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x4305	osdErrGEIllegalAddr	OSEK	Caller has no write access rights for address argument
0x4306	osdErrGECallContext	OSEK	Called from invalid call context
0x4307	osdErrGENoAccess	OSEK	Calling application has no access rights for this task
0x4308	osdErrGEWrongAppState	OSEK	Referenced task is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x4309	osdErrGEOddInvocation	assertion	Invocation of internal function osGetEvent detected although ReducedStatusChecks was enabled
0x4401	osdErrWENotExtended Task	OSEK	WaitEvent called by basic task
0x4402	osdErrWEResources Occupied	OSEK	WaitEvent called with occupied resources
0x4403	osdErrWEInterrupts Disabled	OSEK	WaitEvent called with disabled interrupts
0x4404	osdErrWEOnInterrupt Level	OSEK	WaitEvent called on interrupt level
0x4405	osdErrWECallContext	OSEK	Called from invalid call context

Table 3-14 Error numbers of group Event Control / (4)

3.3.3.5 Error Numbers of Group Alarm Management / (5)

Group (5) contains the functions:

API Function	Abbreviation	Function Number
GetAlarmBase	GB	1
GetAlarm	GA	2
SetRelAlarm	SA	3
SetAbsAlarm	SL	4
CancelAlarm	CA	5
osWorkAlarm	WA	6

Table 3-15 API functions of group Alarm Management / (5)

Error numbers of group (5):

Error Code		Description	
		Error Type	Reason
0x5101	osdErrGBWrongAlarmID	OSEK	Invalid alarm ID
0x5102	osdErrGBIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x5103	osdErrGBIllegalAddr	OSEK	Caller has no write access rights for address argument
0x5104	osdErrGBCallContext	OSEK	Called from invalid call context
0x5105	osdErrGBNoAccess	OSEK	Calling application has no access rights for this alarm
0x5106	osdErrGBWrongAppState	OSEK	Referenced object is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x5201	osdErrGAWrongAlarmID	OSEK	Invalid alarm ID
0x5202	osdErrGANotActive	OSEK	Alarm not active
0x5203	osdErrGAIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x5204	osdErrGAIlegalAddr	OSEK	Caller has no write access rights for address argument
0x5205	osdErrGACallContext	OSEK	Called from invalid call context
0x5206	osdErrGANoAccess	OSEK	Calling application has no access rights for this alarm
0x5207	osdErrGAWrongAppState	OSEK	Referenced alarm is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE

Error Code		Description	
		Error Type	Reason
0x5301	osdErrSAWrongAlarmID	OSEK	Invalid alarm id
0x5302	osdErrSAAAlreadyActive	OSEK	Alarm already active
0x5303	osdErrSAWrongCycle	OSEK	Specified cycle is out of range
0x5304	osdErrSAWrongDelta	OSEK	Specified delta is out of range
0x5305	osdErrSAIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x5306	osdErrSAZeroIncrement	OSEK	SetRelAlarm was called with the parameter increment set to zero. (This is no longer allowed with AUTOSAR OS)
0x5307	osdErrSACallContext	OSEK	Called from invalid call context
0x5308	osdErrSANoAccess	OSEK	Calling application has no access rights for this alarm
0x5309	osdErrSAWrongAppState	OSEK	Referenced alarm is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x5401	osdErrSLWrongAlarmID	OSEK	Invalid alarm ID
0x5402	osdErrSLAlreadyActive	OSEK	Alarm already active
0x5403	osdErrSLWrongCycle	OSEK	Specified cycle is out of range
0x5404	osdErrSLWrongStart	OSEK	Specified start is out of range
0x5405	osdErrSLIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x5406	osdErrSLCallContext	OSEK	Called from invalid call context
0x5407	osdErrSLNoAccess	OSEK	Calling application has no access rights for this alarm
0x5408	osdErrSLWrongAppState	OSEK	Referenced alarm is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x5501	osdErrCAWrongAlarmID	OSEK	Invalid alarm ID
0x5502	osdErrCANotActive	OSEK	Alarm not active
0x5503	osdErrCAIntAPI Disabled	OSEK	Interrupts are disabled with functions provided by OSEK
0x5504	osdErrCAAAlarmInternal	syscheck	Internal error detected while alarm was cancelled. This error is only detected when OSInternalChecks is set to Additional.
0x5505	osdErrCACallContext	OSEK	Called from invalid call context
0x5506	osdErrCANoAccess	OSEK	Calling application has no access rights for this alarm
0x5507	osdErrCAWrongAppState	OSEK	Referenced alarm is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE

Error Code		Description	
		Error Type	Reason
0x5601	osdErrWAWrongIDonHeap	assertion	Wrong alarm ID in heap data structure for alarm management
0x5602	osdErrWAHeapOverflow	assertion	Overflow in internal data structure for alarm management
0x5603	osdErrWAUnknownAction	assertion	Invalid alarm action type during processing of an expired alarm
0x5604	osdErrWAWrongCounterID	assertion	Invalid counter ID during processing of an expired alarm with OsAlarmAction=OsAlarmIncrementCounter.

Table 3-16 Error numbers of group Alarm Management / (5)

3.3.3.6 Error Numbers of Group Operating System Execution Control / (6)

Group (6) contains the functions:

API Function	Abbreviation	Function Number
osCheckStackOverflow	SO	1
osSchedulePrio	SP	2
osGetStackUsage	SU	3
osCheckLibraryVersionAndVariant	CL	4
osErrorHook	EH	5
StartOS	ST	6
osSchedInsertTask	QI	7
osSchedRemoveRunningTask	QR	8
osSchedOnHomePrio	QS	9
osSchedOccupyInternalResource	QO	A

Table 3-17 API functions of group Operating System Execution Control / (6)

Error numbers of group (6):

Error Code		Description	
		Error Type	Reason
0x6101	osdErrSOSStackOverflow	syscheck	Task stack overflow detected. This error is only detected when the OIL attribute WithStackCheck is set to TRUE.
0x6201	osdErrSPInterruptsEnabled	assertion	Scheduler called with enabled interrupts
0x6301	osdErrSUWrongTaskID	assertion	Called with invalid task ID

Error Code		Description	
		Error Type	Reason
0x6401	osdErrCLWrongLibrary	syscheck	Wrong library linked to application. This error check is always enabled.
0x6501	osdErrEHInterrupts Enabled	assertion	ErrorHook called with enabled interrupts
0x6601	osdErrSTMemoryError	assertion	StartOS failed while initializing memory.
0x6602	osdErrSTNoImmediate TaskSwitch	assertion	StartOS tried to activate the Scheduler without success.
0x6603	osdErrSTWrongAppMode	syscheck	StartOS was called with an invalid parameter value. This error is only detected if the attribute STATUS is set to EXTENDED.

Table 3-18 Error numbers of group Operating System Execution Control / (6)

3.3.3.7 Error Numbers of Schedule Table Control / (7)

Group (7) contains the functions:

API Function	Abbreviation	Function Number
StartScheduleTableRel	SR	1
StartScheduleTableAbs	SS	2
StopScheduleTable	SP	3
GetScheduleTableStatus	SG	4
NextScheduleTable	SN	5
osWorkScheduleTable	WS	6
SyncScheduleTable (SC2 and SC4)	SY	7
SetScheduleTableAsync (SC2 and SC4)	AY	8
StartScheduleTableSynchron (SC2 and SC4)	TS	C

Table 3-19 API functions of group Schedule Table Control / (7)

Error numbers of group (7):

Error Code		Description	
		Error Type	Reason
0x7101	osdErrSRWrongID	OSEK	StartScheduleTableRel was called with an invalid schedule table ID.
0x7102	osdErrSRAlready RunningOrNext	OSEK	StartScheduleTableRel was called for a schedule table that is already running or next.
0x7103	osdErrSRZeroOffset	OSEK	StartScheduleTableRel was called

Error Code		Description	
		Error Type	Reason
			with the parameter Offset set to zero.
0x7104	osdErrSROffsetTooBig	OSEK	StartScheduleTableRel was called with the parameter Offset bigger than MAXALLOWEDVALUE of the respective counter.
0x7105	osdErrSRIntAPI Disabled	OSEK	StartScheduleTableRel was called with disabled interrupts.
0x7106	osdErrSRCallContext	OSEK	Called from invalid call context
0x7107	osdErrSRNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7109	osdErrSRImplicite Sync	OSEK	StartScheduleTableRel was called for an implicitly synchronized ScheduleTable
0x710a	osdErrSRWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7201	osdErrSSWrongID	OSEK	StartScheduleTableAbs was called with an invalid schedule table ID.
0x7202	osdErrSSAlready RunningOrNext	OSEK	StartScheduleTableAbs was called for a schedule table, which is already running or next.
0x7203	osdErrSSTickvalueToo Big	OSEK	StartScheduleTableAbs was called with the parameter TickValue bigger than MAXALLOWEDVALUE of the respective counter.
0x7204	osdErrSSIntAPI Disabled	OSEK	StartScheduleTableAbs was called with disabled interrupts.
0x7205	osdErrSSCallContext	OSEK	Called from invalid call context
0x7206	osdErrSSNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7207	osdErrSSWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7301	osdErrSPWrongID	OSEK	StopScheduleTable was called with an invalid schedule table ID.
0x7302	osdErrSPNotRunning	OSEK	StopScheduleTable was called for a schedule table, which is in stopped or next state.
0x7303	osdErrSPIntAPI Disabled	OSEK	StopScheduleTable was called with disabled interrupts.
0x7304	osdErrSPCallContext	OSEK	Called from invalid call context
0x7305	osdErrSPNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7306	osdErrSPUnknownCase	Assertion	An internal error occurred

Error Code		Description	
		Error Type	Reason
0x7307	osdErrSPWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7401	osdErrSGWrongID	OSEK	GetScheduleTableStatus was called with an invalid schedule table ID.
0x7402	osdErrSGIntAPI Disabled	OSEK	GetScheduleTableStatus was called with disabled interrupts
0x7403	osdErrSGCallContext	OSEK	Called from invalid call context
0x7404	osdErrSGNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7405	osdErrSGIllegalAddr	OSEK	Caller has no write access rights for address argument
0x7406	osdErrSGWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7407	osdErrSGOddInvocation	assertion	Invocation of internal function osGetScheduleTableStatus detected although ReducedStatusChecks was enabled
0x7501	osdErrSNWrongCurrentID	OSEK	NextScheduleTable was called with an invalid schedule table ID for the parameter ScheduleTableID_current.
0x7502	osdErrSNWrongNextID	OSEK	NextScheduleTable was called with an invalid schedule table ID for the parameter ScheduleTableID_next.
0x7503	osdErrSNNotRunning	OSEK	NextScheduleTable was called to chain a schedule table after another schedule table, that is currently not running.
0x7504	osdErrSNAlreadyRunningOrNext	OSEK	NextScheduleTable was called to chain a running schedule table after another schedule table.
0x7505	osdErrSNDifferentCounters	OSEK	NextScheduleTable was called to chain two schedule tables, which are driven by different counters.
0x7506	osdErrSNIntAPI Disabled	OSEK	NextScheduleTable was called with interrupts disabled.
0x7507	osdErrSNCallContext	OSEK	Called from invalid call context
0x7508	osdErrSNNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7509	osdErrSNWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7601	osdErrWSUnknownAction	assertion	An invalid action was found in a schedule

Error Code		Description	
		Error Type	Reason
			table
0x7602	osdErrWSUnknownReaction	assertion	An internal error occurred
0x7603	osdErrWSWrongID	assertion	No valid schedule table index in osWorkScheduleTable
0x7701	osdErrSYCallContext	OSEK	Called from invalid call context
0x7702	osdErrSYWrongID	OSEK	Called with wrong schedule table ID
0x7703	osdErrSYNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7704	osdErrSYIntAPIDisabled	OSEK	Called with interrupts disabled
0x7705	osdErrSYSTNotRunning	OSEK	The Schedule table is currently not running
0x7706	osdErrSYGlobalTimeTooBig	OSEK	The Global Time is larger than the LENGTH of the schedule table
0x7707	osdErrSYSyncKindNotExplicit	OSEK	SyncScheduleTable was called for a Schedule table that is not explicitly synchronized.
0x7708	osdErrSYWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7801	osdErrAYCallContext	OSEK	Called from invalid call context
0x7802	osdErrAYWrongID	OSEK	Called with wrong schedule table ID
0x7803	osdErrAYNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7804	osdErrAYIntAPIDisabled	OSEK	Called with interrupts disabled
0x7805	osdErrAYWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x7C01	osdErrTSCallContext	OSEK	Called from invalid call context
0x7C02	osdErrTSWrongID	OSEK	Called with invalid schedule table id.
0x7C03	osdErrTSNoAccess	OSEK	Calling application has no access rights for this schedule table
0x7C04	osdErrTSIntAPIDisabled	OSEK	Called with interrupts disabled
0x7C05	osdErrTSSAlreadyRunning	OSEK	The schedule table is already running or scheduled to run after a currently running schedule table
0x7C06	osdErrTSGlobalTimeTooBig	OSEK	The offset to Global Time is larger than the LENGTH of the schedule table
0x7C08	osdErrTSSyncKindNotExplicit	OSEK	StartScheduleTableSynchron was called for a Schedule table that is not

Error Code		Description	
		Error Type	Reason
			explicitly synchronized.
0x7C09	osdErrTSWrongAppState	OSEK	Referenced schedule table is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE

Table 3-20 Error numbers of group Schedule Table Control / (7)

3.3.3.8 Error Numbers of Group Counter API / (8)

Group (8) contains the functions:

API Function	Abbreviation	Function Number
IncrementCounter	IC	1
GetCounterValue	GC	3
GetElapsedValue	GV	4

Table 3-21 API functions of group Counter API / (8)

Error numbers of group (8):

Error Code		Description	
		Error Type	Reason
0x8101	osdErrICWrongCounterID	OSEK	IncrementCounter was called for an invalid counter or a hardware counter.
0x8102	osdErrICIntAPIDisabled	OSEK	IncrementCounter was called with interrupts disabled.
0x8103	osdErrICCallContext	OSEK	Called from invalid call context
0x8104	osdErrICNoAccess	OSEK	Calling application has no access rights for this counter
0x8105	osdErrICWrongAppState	OSEK	Referenced counter is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x8301	osdErrGCCallContext	OSEK	Called from invalid call context.
0x8302	osdErrGCIntAPIDisabled	OSEK	Called with disabled interrupts
0x8303	osdErrGCWrongID	OSEK	Parameter CounterID is invalid
0x8304	osdErrGCNoAccess	OSEK	Counter not accessible by the caller
0x8305	osdErrGCIllegalAddr	OSEK	Location the reference parameter Value points to is not writable for the calling application
0x8306	osdErrGCWrongAppState	OSEK	Referenced ISR is owned by an OSApplication that is not in state APPLICATION_ACCESSIBLE
0x8307	osdErrGCOddInvocation	assertion	Invocation of internal function

Error Code		Description	
		Error Type	Reason
			osGetCounterValue detected although ReducedStatusChecks was enabled
0x8401	osdErrGVCallContext	OSEK	Called from invalid call context.
0x8402	osdErrGVIntAPIDisabled	OSEK	Called with disabled interrupts
0x8403	osdErrGVWrongID	OSEK	Parameter CounterID is invalid
0x8404	osdErrGVNoAccess	OSEK	Counter not accessible by the caller
0x8405	osdErrGVIllegalAddr	OSEK	Location a reference parameter points to is not writable for the calling application
0x8406	osdErrGVWrongAppState	OSEK	Referenced ISR is owned by an OSApplication that is not in state APPLICATION_ACCESSIBLE
0x8407	osdErrGVIllegalValue	OSEK	The passed value is illegal
0x8408	osdErrGVIllegalPointers	OSEK	The pointers for out parameters Value and Elapsed Value are identical.
0x8409	osdErrGVOddInvocation	assertion	Invocation of internal function osGetElapsedValue detected although ReducedStatusChecks was enabled

Table 3-22 Error numbers of group Counter API / (8)

3.3.3.9 Error Numbers of Group Timing Protection and Timing Measurement / (9)

Group (9) contains the functions:

API Function	Abbreviation	Function Number
GetTaskMinInterArrivalTime	TM	0
BlockingTimeMonitoring	BM	7
GetTaskMaxExecutionTime	TE	8
GetISRMaxExecutionTime	IE	9
GetTaskMaxBlockingTime	TB	A
GetISRMaxBlockingTime	IB	B
ExecutionTimeMonitoring	ET	D
GetISRMinInterArrivalTime	MI	F

Table 3-23 API functions of group Timing Protection and Timing Measurement / (9)

Error numbers of group (9):

Error Code		Description	
		Error Type	Reason
0x9001	osdErrTMWrongTaskID	OSEK	Called with wrong TASK ID
0x9002	osdErrTMNoAccess	OSEK	The calling application has no access rights for the TASK
0x9003	osdErrTMIllegalAddr	OSEK	The caller has no access rights for the memory region
0x9004	osdErrTMWrongAppState	OSEK	Referenced task is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x9702	osdErrBMResAlreadyMeasured	assertion	A blocking time measurement was started that is already running. This might happen if timing protection is active and SuspendAllInterrupts is called after DisableAllInterrupts has already been called.
0x9703	osdErrBMInvalidProcessInStart	assertion	Internal error: attempt to start Block Timing Protection with an invalid task or ISR
0x9704	osdErrBMInvalidProcessInStop	assertion	Internal error: attempt to stop Block Timing Protection with an invalid task or ISR
0x9705	osdErrBMInvalidResource	assertion	Attempt to monitor blocking time for an invalid resource detected.
0x9801	osdErrTEWrongTaskID	OSEK	GetTaskMaxExecutionTime was called with an invalid task identifier
0x9802	osdErrTENoAccess	OSEK	The calling application has no access rights for this task
0x9803	osdErrTEIllegalAddr	OSEK	The caller has no access rights for this memory region
0x9804	osdErrTEWrongAppState	OSEK	Referenced task is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x9901	osdErrIEWrongISRID	OSEK	GetISRMaxExecutionTime was called with an invalid ISR identifier
0x9902	osdErrIENoAccess	OSEK	The calling application has no access rights for this ISR
0x9903	osdErrIEIllegalAddr	OSEK	The caller has no access rights for this memory region.
0x9904	osdErrIEWrongAppState	OSEK	Referenced ISR is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x9A01	osdErrTBWrongTaskID	OSEK	Called with wrong Task ID
0x9A02	osdErrTBWrongBlockType	OSEK	Called with wrong blocking type
0x9A03	osdErrTBWrongResourceID	OSEK	Called with wrong resource ID

Error Code		Description	
		Error Type	Reason
0x9A04	osdErrTBNoAccessToTask	OSEK	The calling application has no access rights for the task
0x9A05	osdErrTBNoAccessToResource	OSEK	The calling application has no access rights for the resource
0x9A06	osdErrTBIllegalAddr	OSEK	The caller has no access rights for this memory region
0x9A07	osdErrTBWrongAppState	OSEK	Referenced task is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x9B01	osdErrIBWrongISRID	OSEK	Called with wrong ISR ID
0x9B02	osdErrIBWrongBlockType	OSEK	Called with wrong blocking type
0x9B03	osdErrIBWrongResourceID	OSEK	Called with wrong resource ID
0x9B04	osdErrIBNoAccessToISR	OSEK	The calling application has no access rights for the ISR
0x9B05	osdErrIBNoAccessToResource	OSEK	The calling application has no access rights for the resource
0x9B06	osdErrIBIllegalAddr	OSEK	The caller has no access rights for the memory region
0x9B07	osdErrIBWrongAppState	OSEK	Referenced ISR is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE
0x9D01	osdErrETNoCurrentProcess	assertion	Execution Time Monitoring has detected an invalid process ID
0x9F01	osdErrMIWrongISRID	OSEK	Called with wrong ISR ID
0x9F02	osdErrMINoAccess	OSEK	The calling application has no access rights for the ISR
0x9F03	osdErrMIIllegalAddr	OSEK	The caller has no access rights for the memory region
0x9F04	osdErrMIWrongAppState	OSEK	Referenced ISR is owned by an OSApplication which is not in state APPLICATION_ACCESSIBLE

Table 3-24 Error numbers of group Timing Protection and Timing Measurement / (9)

3.3.3.10 Platform specific error codes (A)

Group (A) contains platform specific error numbers. Please refer to [5] for further detail.

3.3.3.11 Error Numbers of Group Application API (B)

Group (B) contains the functions:

API Function	Abbreviation	Function Number
GetApplicationState	AS	1
AllowAccess	AA	2
TerminateApplication	TA	4

Table 3-25 API functions of group Application API / (B)

Error numbers of group (B):

Error Code		Description	
		Error Type	Reason
0xB101	osdErrASCallContext	OSEK	Called from invalid call context.
0xB102	osdErrASIntAPIDisabled	OSEK	Called with disabled interrupts
0xB103	osdErrASWrongAppID	OSEK	Called with invalid OSApplication ID
0xB104	osdErrASOddInvocation	assertion	Invocation of internal function <code>osGetApplicationState</code> detected although <code>ReducedStatusChecks</code> was enabled
0xB201	osdErrAACallContext	OSEK	Called from invalid call context.
0xB202	osdErrAAIntAPIDisabled	OSEK	Called with disabled interrupts
0xB203	osdErrAAWrongState	OSEK	Currently active application is not in state <code>APPLICATION_RESTARTING</code>
0xB401	osdErrTAWrongRestart Option	OSEK	Invalid restart option
0xB402	osdErrTACallContext	OSEK	Called from invalid call context
0xB403	osdErrTAIntAPI Disabled	OSEK	Called with interrupts disabled
0xB404	osdErrTAWrongAppID	OSEK	Called with wrong OSApplication ID.
0xB405	osdErrTANoAccess	OSEK	Caller has not sufficient access rights to terminate the given OSApplication.
0xB406	osdErrTAWrongAppState	OSEK	Referenced application is in wrong state.
0xB407	osdErrTAInvalidTaskState	assertion	Task state corrupt in <code>TerminateApplication</code>

Table 3-26 Error numbers of group Application API / (B)

3.3.3.12 Error Numbers of Group Semaphores (C)

**Note**

This group is only available for implementations that have been ordered with the feature Semaphores.

Group (C) contains the functions:

API Function	Abbreviation	Function Number
osGetSemaphore	GM	1
osReleaseSemaphore	RS	2

Table 3-27 API functions of group Semaphores / (C)

Error numbers of group (C):

Error Code		Description	
		Error Type	Reason
0xC101	osdErrGMWrongSemaphoreID	OSEK	GetSemaphore called with wrong Semaphore ID
0xC102	osdErrGMOnInterruptLevel	OSEK	Called on Interrupt Level
0xC103	osdErrGMNotExtendedTask	OSEK	Called from a Basic Task
0xC104	osdErrGMResourcesOccupied	OSEK	Called while resources are occupied
0xC105	osdErrGMInterruptsDisabled	OSEK	Interrupts are disabled with functions provided by OSEK
0xC201	osdErrRSWrongSemaphoreID	OSEK	ReleaseSemaphore called with wrong Semaphore ID
0xC203	osdErrRSAlreadyReleased	OSEK	Tried to release a semaphore that is not occupied
0xC204	osdErrRSWrongTaskPriority	assertion	Task has wrong priority level
0xC205	osdErrRSInterruptsDisabled	OSEK	Interrupts are disabled with functions provided by OSEK

Table 3-28 Error numbers of group Semaphores / (C)

3.3.3.13 Error Numbers of Group MultiCore related functions (D)

Group (D) is reserved for MultiCore implementations. MultiCore specific detail is currently contained in the additional documentation. Please refer to [4] for further detail.

3.3.3.14 Error Numbers of Group TrustedFunctions (E)

Group (E) contains the functions:

API Function	Abbreviation	Function Number
CallTrustedFunction	CT	3

Table 3-29 API functions of group TrustedFunctions (E)

Error numbers of group (E):

Error Code		Description	
		Error Type	Reason
0xE301	osdErrCTWrongFctIdx	OSEK	Invalid function index for trusted function
0xE302	osdErrCTCallContext	OSEK	Called from invalid call context
0xE303	osdErrCTIntAPI Disabled	OSEK	Called with interrupts disabled

Table 3-30 Error numbers of group TrustedFunctions (E)

3.3.3.15 Error Numbers of Group IOC (F)

Group (F) is reserved for implementations supporting IOC. IOC specific detail is currently contained in the platform specific documentation. Please refer to [5] for further detail.

3.3.4 ErrorInfoLevel

Every MICROSAR OS implementation offers an additional service for error treatment. To use this feature the OS properties `EXTENDED_STATUS` and `ERRORHOOK` have to be enabled. The OS property `ErrorInfoLevel` has to be set on `Modulnames`.

When this is done the macros `OSErrorGetosCANModuleName()` and `OSErrorGetosCANLineNumber()` are enabled. Usage of the macros is as follows:

- > `OSErrorGetosCANModuleName()`: Returns the name of the file in which the error occurred.
- > `OSErrorGetosCANLineNumber()`: Returns the line number in which the error occurred.

3.3.5 Reactions on Error Situations

Depending on the error that has occurred, different reactions are performed:

- > Errors detected from wrong usage of API functions: Call of `ErrorHook` and return to the calling task or interrupt routine.
- > Errors detected in the kernel: Call of `ErrorHook` and call of `ShutdownOS` (which calls `ShutdownHook`).

4 Installation

The MICROSAR OS package might be delivered together with other MICROSAR embedded software. In this case, the OS is already included in the delivered package, and no separate installation is necessary. If MICROSAR OS is delivered stand alone, it comes up with an installation program, which installs the operating system source files and the OIL Configurator. To use the OS with ARXML configurations, the DaVinci configurator must be installed in addition.

4.1 Installation Requirements

The installation program and the OIL Configurator are 32-bit Windows programs.

Requirements:

- > Microsoft Windows95, Windows98, Windows NT, Windows 2000, Windows XP, Windows Vista, Windows 7
- > 64 MByte of free disk space (for a complete installation)

4.2 Installation Disk

All parts of the OSEK system, the OIL Configurator, and the code generator are delivered with a Windows installation program. The installation program copies all files onto the local hard disk and sets all paths in the INI files. The installation program asks the user for an installation path; this path is the root path for all installed components. The selected path is referred to in the following as `root`. The delivered installation uses the path `C:\OSEK` as the default `root` path.

There are two possible installation styles than can be selected:

- > MICROSAR style: compatible with Vector AUTOSAR stack
- > osCAN style: compatible with osCAN

The installation paths are determined depending on the selected style

The installed components are:

Components	osCAN style	MICROSAR style
OIL Configurator	root\OILTOOL	root\Generators\Tools\OilTool
OSEK system	root\HwPlatform	root\BSW\Os

Table 4-1 Installed components

4.3 OIL Configurator



Info

Please note that 'OIL Configurator' and 'OIL Tool' are used as synonyms in this document.

The OIL Configurator is a common tool for different OSEK implementations. The implementation specific parts are the code generator and the OIL implementation files for the code generator.

Components	osCAN style	MICROSAR style
OIL Configurator	root\OILTOOL	root\Generators\Tools\OilTool
OIL implementation files	root\OILTOOL\GEN	root\Generators\Os
Code generator	root\OILTOOL\GEN	root\Generators\Os

Table 4-2 System configuration and generation tools

4.3.1 INI Files of the OIL Tool

The OIL Configurator has two INI files, which are in the directory of the OIL Configurator:

- > OILGEN.INI
- > OILCFG.INI

4.3.2 OIL Implementation Files

The implementation files are copied onto the local hard disk by the installation program. The OIL tool has knowledge about these files through the INI file `OILGEN.INI` (the correct path is set by the installation program).

The implementation files are described in the hardware specific part of this manual [4].

4.3.3 Code Generator

The code generator `GENxxxx.EXE` is copied onto the local hard disk by the installation program. The code generator is defined in the INI-file `OILGEN.INI`. ('xxxx' has to be replaced by a hardware dependent abbreviation)

4.4 OSEK Operating System

4.4.1 Installation Paths

The delivered operating system parts are organized in different subdirectories.

The following structure is used by osCAN style installations:

> root\HwPlatform\APPL\Compiler\Derivative	Sample applications
> root\HwPlatform\BIN	executable files (e.g. make tool)
> root\HwPlatform\bswmd_files	XML parameter description files

> root\HwPlatform\DOC	Documentation
> root\HwPlatform\INCLUDE	OSEK include files
> root\HwPlatform\LIB	OSEK library (only if a library is available)
> root\HwPlatform\SRC	OSEK sources (C and Assembler)

The following structure is used by MICROSAR style installations:

> root\Demo\Os	Sample applications
> root\Generators\Os	executable files (e.g. make tool)
> root\Generators\Components_Schemes\ Os_<platform and derivate>_bswmd \bswmd	XML parameter description files
> root\Doc\TechnicalReferences	Documentation
> root \Doc\UserManuals	
> root\BSW\Os	OSEK include files
> root\BSW\Os	OSEK library (only if a library is available)
> root\BSW\Os	OSEK sources (C and Assembler)

4.5 XML Configurations

AUTOSAR uses for configuration files the XML format. An XML Schema (ref. [8]) defines the structure. For each derivative there is an ECU Parameter Definition File (file extension is `arxml`) which defines all attributes (standard attribute and vendor/platform specific attributes).

The Vector implementation of AUTOSAR OS uses the OIL [6] configuration file format or ECU Configuration files. A conversion of ECUC files to OIL, as it was necessary in former versions of MICROSAR OS, is not required any more.

4.5.1 Parameter Definition Files

Parameter Definition Files for the implementation can be found in the directory `root\HwPlatform\BSWMD_files` (osCAN style) or

`root\Generators\Components\_Schemes\Os_<platform and derivate>_bswmd\bswmd` (MICROSAR style).

The files have the name `OS_<platform and derivate>_bswmd.arxml`.

5 Integration

This chapter gives necessary information for the integration of the MICROSAR OS into an application environment of an ECU.

5.1 Scope of Delivery

The delivery of the OS contains the files that are described in the chapters 5.1.1 and 5.1.2:

5.1.1 Static Files

The static file list is described in the platform specific technical reference [4]

5.1.2 Dynamic Files

The dynamic files are generated by the code generator GENxxxx (xxxx is replaced by hardware platform name).

5.1.2.1 Code Generator GENxxxx

File Name	Description
tcb.c	tcb contains the task control block and other OS object
tcb.h	task and other OS object related information, like task Ids – definitions required by static include files (e.g. array sizes)
tcbpost.h	task and other OS object related information, like task Ids – declarations that require static include files (e.g. typedef's)
trustfct.h	Header containing trusted function information
trustfct.c	Trusted function data and generated stubs
libconf	Information for usage in makefiles, not available on all platforms, see chapter 5.1.2.1.1
<OILFileName>.ort	Generated if kernel aware debugging with the ORTI interface is enabled,

Table 5-1 Files generated by code generator GENxxxx

In addition to the files listed in Table 5-1, some hardware dependent files are generated which are described in the hardware specific technical reference [4].

5.1.2.1.1 Generated file libconf

The file libconf is meant for the inclusion into makefiles. It sets some variables in accordance to general configuration settings of MICROSAR OS to inform the make process about them. Dependent on the platform, the file may contain more information or be even unavailable, so please see the hardware specific technical reference [4].

The table below describes the generated variables.

Variable	Meaning
LIB	Is set to 1 in case MICROSAR OS is configured to library variant. Is set to 0 if not.
STATUS_LEVEL	Reflects the setting of the configuration attribute STATUS of MICROSAR OS. Possible values: EXTENDED_STATUS = 1 STANDARD_STATUS = 0
DEBUG_SUPPORT	Is set to 1 in case the configuration attribute ORTIDebugSupport of MICROSAR OS is selected. Is set to 0 if not.

Table 5-2 Variables generated into the file libconf

5.1.2.2 Application Template Generator GENTMPL

Former versions of MICROSAR OS and osCAN came with a template code generator which generates a main.c template file with empty implementations for the objects defined in the configuration. This is not supported any more in newer implementations.

5.2 Include Structure

The header files `tcb.h` and `tcbpost.h` are included into the file `os.h`. The user must include `os.h` in every module of his application. The headers `tcb.h` and `tcbpost.h` are included automatically. Always recompile all files after a new generation of `tcb.h` and `tcbpost.h`.

If an application is using trusted functions and the Vector extension “GenerateStubs”, an include file named `usrotyp.h` must be present in the include path. This file must contain all user specific data types used for trusted functions.

6 API Description

6.1 Standard API - Overview

This chapter gives an overview of all standard API functions defined for the OS. The following synonyms present the standard specifications:

- > ASR: AUTOSAR standard, reference [1]
- > OSEK: OSEK standard, reference [3]

These standard specifications contain the detailed API descriptions. In case part of an API function is implementation specific, the detailed API description is given in a further subchapter in this document.

API Function Prototype	Standard Specification		Scalability Class			
	OSEK	ASR	1	2	3	4
Task Handling						
StatusType ActivateTask (TaskType TaskID)	■		■	■	■	■
StatusType TerminateTask (void)	■		■	■	■	■
StatusType ChainTask (TaskType TaskID)	■		■	■	■	■
StatusType Schedule (void)	■		■	■	■	■
StatusType GetTaskID (TaskRefType TaskID)	■		■	■	■	■
StatusType GetTaskState (TaskType TaskID, TaskStateRefType State)	■		■	■	■	■
Event Control						
StatusType SetEvent (TaskType TaskID, EventMaskType Mask)	■		■	■	■	■
StatusType ClearEvent (EventMaskType Mask)	■		■	■	■	■
StatusType GetEvent (TaskType TaskID, EventMaskRefType Mask)	■		■	■	■	■
StatusType WaitEvent (EventMaskType Mask)	■		■	■	■	■
Interrupt Handling						
The behavior of the interrupt handling functions is implementation specific. For a detailed description see hardware specific technical reference [4].						
void EnableAllInterrupts (void)	■		■	■	■	■
void DisableAllInterrupts (void)	■		■	■	■	■
void ResumeAllInterrupts (void)	■		■	■	■	■
void SuspendAllInterrupts (void)	■		■	■	■	■
void ResumeOSInterrupts (void)	■		■	■	■	■
void SuspendOSInterrupts (void)	■		■	■	■	■

API Function Prototype		Standard Specification		Scalability Class			
		OSEK	ASR	1	2	3	4
Resource Management							
The behaviour of the resource management functions is implementation specific							
StatusType	GetResource (ResourceType ResID)	■		■	■	■	■
StatusType	ReleaseResource (ResourceType ResID)	■		■	■	■	■
Alarms							
StatusType	GetAlarmBase (AlarmType AlarmID, AlarmBaseRefType Info)	■		■	■	■	■
StatusType	GetAlarm (AlarmType AlarmID, TickRefType Tick)	■		■	■	■	■
StatusType	SetRelAlarm (AlarmType AlarmID, TickType Increment, TickType cycle)	■		■	■	■	■
StatusType	SetAbsAlarm (AlarmType AlarmID, TickType Start, TickType cycle)	■		■	■	■	■
StatusType	CancelAlarm (AlarmType AlarmID)	■		■	■	■	■
Execution Control							
void	StartOS (AppModeType Mode)	■		■	■	■	■
void	ShutdownOS (StatusType Error)	■		■	■	■	■
ISRTType	GetISRID (void)		■	■	■	■	■
AppModeType	GetActiveApplicationMode (void)	■		■	■	■	■
ApplicationType	GetApplicationID (void)		■			■	■
StatusType	TerminateApplication (ApplicationType Application, RestartType RestartOption)		■			■	■
StatusType	CallTrustedFunction (TrustedFunctionIndexType FunctionIndex, TrustedFunctionParameterRefType FunctionParams)		■			■	■
StatusType	GetApplicationState (ApplicationType Application, ApplicationStateRefType Value)		■			■	■
StatusType	AllowAccess (void)		■			■	■
Hook Routines							
The context for called hook routines is implementation specific. For a detailed description see see hardware specific technical reference [4].							
void	ErrorHook (StatusType Error)	■					
void	PreTaskHook (void)	■					
void	PostTaskHook (void)	■					
void	StartupHook (void)	■					
void	ShutdownHook (StatusType Error)	■					

API Function Prototype	Standard Specification		Scalability Class			
	OSEK	ASR	1	2	3	4
ProtectionReturnType ProtectionHook (StatusType Fatalerror)		■		■	■	■
void StartupHook_<App> (void)		■			■	■
void ErrorHook_<App> (StatusType Error)		■			■	■
void ShutdownHook_<App> (StatusType Fatalerror)		■			■	■
Schedule Tables						
StatusType StartScheduleTableRel (ScheduleTableType ScheduleTableID, TickType Offset)		■	■	■	■	■
StatusType StartScheduleTableAbs (ScheduleTableType ScheduleTableID, TickType Start)		■	■	■	■	■
StatusType StopScheduleTable (ScheduleTableType ScheduleTableID)		■	■	■	■	■
StatusType NextScheduleTable (ScheduleTableType ScheduleTableID_From, ScheduleTableType ScheduleTableID_To)		■	■	■	■	■
StatusType StartScheduleTableSynchron (ScheduleTableType ScheduleTableID)		■		■		■
StatusType SyncScheduleTable (ScheduleTableType ScheduleTableID, TickType Value)		■		■		■
StatusType SetScheduleTableAsync (ScheduleTableType ScheduleTableID)		■		■		■
StatusType GetScheduleTableStatus (ScheduleTableType ScheduleTableID, ScheduleTableStatusRefType ScheduleStatus)		■	■	■	■	■
Counters						
StatusType IncrementCounter (CounterType CounterID)		■	■	■	■	■
StatusType GetCounterValue (CounterType CounterID, TickRefType Value)		■	■	■	■	■
StatusType GetElapsedValue (CounterType CounterID, TickRefType Value, TickRefType ElapsedValue)		■	■	■	■	■
Access Rights Management						
AccessType CheckISRMemoryAccess (ISRType ISRID, MemoryStartAddressType Address, MemorySizeType Size)		■			■	■
AccessType CheckTaskMemoryAccess		■			■	■

API Function Prototype	Standard Specification		Scalability Class			
	OSEK	ASR	1	2	3	4
(TaskType TaskID, MemoryStartAddressType Address, MemorySizeType Size)						
ObjectAccessType CheckObjectAccess (ApplicationType ApplID, ObjectTypeType ObjectType, ...)		■			■	■
ApplicationType CheckObjectOwnership (ObjectTypeType ObjectType, ...)		■			■	■

Table 6-1 Standard API functions

6.2 API Functions defined by Vector - Overview

This chapter gives an overview of all API functions defined for the OS by Vector. Further chapters contain detailed descriptions of these API functions.

API Function Prototype	Scalability Class			
	1	2	3	4
Measurement API				
For a detailed description see chapter 6.4.				
StatusType GetTaskMaxExecutionTime (TaskType TaskID, osTPTimeRefType MaxTime)		■		■
StatusType GetISRMaxExecutionTime (ISRType TaskID, osTPTimeRefType MaxTime)		■		■
StatusType GetTaskMaxBlockingTime (TaskType TaskID, BlockTypeType BlockType, ResourceType ResourceID, osTPTimeRefType MaxTime)		■		■
StatusType GetISRMaxBlockingTime (ISRType ISRID, BlockTypeType BlockType, ResourceType ResourceID, osTPTimeRefType MaxTime)		■		■
StatusType osGetISRMinInterArrivalTime (ISRType ISRID, osTPTimeStampRefType MinTime)		■		■
StatusType osGetTaskMinInterArrivalTime (TaskType ISRID, osTPTimeStampRefType MinTime)		■		■
Hook Routines				
The context for called hook routines is implementation specific. For a detailed description see see hardware specific technical reference [4].				
void PreAlarmHook (void)	■	■	■	■

Table 6-2 Vector API functions

6.3 API Macros

For each API function, four macros are defined:

Macro	Description
<code>OS_APIabbreviation_ENTRY</code>	Called at start of the API function
<code>OS_APIabbreviation_EXIT</code>	Called at exit of the API function
<code>OS_APIabbreviation_START_CRITICAL</code>	Called at start of critical section in API (after disabling interrupts)
<code>OS_APIabbreviation_END_CRITICAL</code>	Called at end of critical section in API (before enabling interrupts)

Table 6-3 API function call macros

For each hook function, two macros are defined:

Macro	Description
<code>OS_Hookabbreviation_ENTRY</code>	Called at start of hook function
<code>OS_Hookabbreviation_EXIT</code>	Called at exit of hook function

Table 6-4 Hook routine macros

Before each call of the dispatcher, the following macro is defined:

Macro	Description
<code>OS_START_DISPATCH</code>	Called at start of dispatcher

Table 6-5 Dispatcher start macro

In the standard configuration, these macros are empty by including the file `EMPTYMAC.H`. By defining `osdTestMacros` to a value of 1 to 4, the include file `TESTMAC1.H` - `TESTMAC4.H` is included for user defined macros. The macro `osdTestMacros` has to be defined as a command line parameter of the C-compiler respectively in the development environment.

The macro values have to be globally defined when calling the compiler.



Caution

Depending on the specific implementation and application, not all macros are called.



Caution

The MICROSAR OS features of ORTI debug support and internal trace are implemented by using the files `TESTMAC1.H` and `TESTMAC2.H`, so these features do not work together with user-defined macros in another include file.

6.4 Timing Measurement API

6.4.1 GetTaskMaxExecutionTime

Prototype	
StatusType GetTaskMaxExecutionTime (TaskType TaskID, osTPTimeRefType MaxTime)	
Parameter	
TaskID	The task to be questioned
MaxTime	Maximum execution time, measured in all finished time frames.
Return code	
E_OK	No errors
E_OS_ID	The TaskID is not valid.
Functional Description	
The maximum execution time of finished executions of the questioned task since StartOS. The value is in ticks of the ExecutionTime hardware timer. The number of ticks per ms of this timer is printed into the HTML list file.	
Particularities and Limitations	
> Available in Scalability Classes 2 and 4. > This function is synchronous. > This function is reentrant. > This function is only available if the attribute <code>TimingMeasurement</code> is set to <code>TRUE</code> (is selected)	
Expected Caller Context	
> task or cat2 ISR	

Table 6-6 GetTaskMaxExecutionTime

6.4.2 GetISRMaxExecutionTime

Prototype	
StatusType GetISRMaxExecutionTime (ISRType TaskID, osTPTimeRefType MaxTime)	
Parameter	
TaskID	The task to be questioned
MaxTime	Maximum execution time of the respective ISR for all finished ISR activations.
Return code	
E_OK	No errors
E_OS_ID	The ISRID is not valid.

> task or cat2 ISR

Table 6-8 GetTaskMaxBlockingTime

6.4.4 GetISRMaxBlockingTime

Prototype	
<pre>StatusType GetISRMaxBlockingTime (ISRType ISRID, BlockTypeType BlockType, ResourceType ResourceID, osTPTimeRefType MaxTime)</pre>	
Parameter	
ISRID	The ISR to be questioned
BlockType	OS_ALL_INTERRUPTS, OS_OS_INTERRUPTS or OS_RESOURCE
ResourceID	If BlockType == OS_RESOURCE, ResourceID specifies the Resource
MaxTime	Maximum of all measured times.
Return code	
E_OK	No errors
E_OS_ID	The TaskID, the BlockType or the ResourceID are invalid.
Functional Description	
The maximum blocking time of finished locking sequences of the questioned ISR and the resource or interrupt lock type since StartOS. The value is in ticks of the BlockingTime hardware timer. The number of ticks per ms of this timer is printed into the HTML list file.	
Particularities and Limitations	
> Available in Scalability Classes 2 and 4. > This function is synchronous. > This function is reentrant. > This function is only available if the attribute TimingMeasurement is set to TRUE (is selected)	
Expected Caller Context	
> task or cat2 ISR	

Table 6-9 GetISRMaxBlockingTime

6.4.5 GetTaskMinInterArrivalTime

Prototype	
<pre>StatusType GetTaskMinInterArrivalTime (TaskType TaskID, osTPTimeStampRefType MinTime)</pre>	
Parameter	
TaskID	The task to be questioned
MinTime	Minimum time between two task arrivals

Return code	
E_OK	No errors
E_OS_ID	The <code>TaskID</code> is not valid.
E_OS_ACCESS	No access rights to task (SC4 only)
E_OS_ILLEGAL_ADDRESS	Memory address of <code>MinTime</code> not writeable (SC4 only)
Functional Description	
Returns the minimum time span between two arrivals of a task (see [1]) as measured since StartOS. The value is in ticks of the InterArrivalTime hardware timer. The number of ticks per ms of this timer is printed into the HTML list file.	
Particularities and Limitations	
> Available in Scalability Classes 2 and 4. > This function is synchronous. > This function is reentrant. > This function is only available if the attribute <code>TimingMeasurement</code> is set to <code>TRUE</code> (is selected)	
Expected Caller Context	
> task or cat2 ISR	

Table 6-10 GetTaskMinInterArrivalTime

6.4.6 GetISRMinInterArrivalTime

Prototype	
<pre>StatusType GetISRMinInterArrivalTime (ISRType IsrID, osTPTimestampRefType MinTime)</pre>	
Parameter	
IsrID	The ISR to be questioned
MinTime	Minimum time between two ISR arrivals
Return code	
E_OK	No errors
E_OS_ID	The <code>ISRID</code> is not valid.
E_OS_ACCESS	No access rights for this ISR (SC4 only)
E_OS_ILLEGAL_ADDRESS	Memory address of <code>MinTime</code> not writeable (SC4 only)
Functional Description	
Returns the minimum time span between two arrivals of an ISR (see [1]) as measured since StartOS. The value is in ticks of the InterArrivalTime hardware timer. The number of ticks per ms of this timer is printed into the HTML list file.	

Particularities and Limitations
> Available in Scalability Classes 2 and 4. > This function is synchronous. > This function is reentrant. > This function is only available if the attribute <code>TimingMeasurement</code> is set to <code>TRUE</code> (is selected)
Expected Caller Context
> task or cat2 ISR

Table 6-11 GetISRMinInterArrivalTime

6.5 Implementation specific Behavior

The behaviour of the functions listed in this chapter is implementation specific.

6.5.1 Interrupt Handling

In general the usage of the interrupt API functions is allowed before the operating system is started. The affected functions are:

- > `DisableAllInterupts`
- > `EnableAllInterrupts`
- > `SuspendAllInterrupts`
- > `ResumeAllInterrupts`
- > `SuspendOSInterrupts`
- > `ResumeOSInterrupts`

The implementation specific behaviour is of these functions is described in [5].

6.5.1.1 EnableAllInterrupts

Prototype	
<code>void EnableAllInterrupts (void)</code>	
Parameter	
--	--
Return code	
void	--

Functional Description

This service restores the state saved by `DisableAllInterrupts`.

This service is a counterpart of `DisableAllInterrupts` service, which has to be called before, and its aim is the completion of the critical section of code. No API service calls are allowed within this critical section.

The implementation should adapt this service to the target hardware providing a minimum overhead. Usually, this service enables recognition of interrupts by the central processing unit.

This function might be implemented using a global interrupt flag or an interrupt level register.

Particularities and Limitations

- > When using before `StartOS`, the function `osInitialize` must be called first to initialize the variables which are used in the interrupt API.
- > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.

Expected Caller Context

> --

Table 6-12 `EnableAllInterrupts`

6.5.1.2 `DisableAllInterrupts`

Prototype

```
void DisableAllInterrupts ( void )
```

Parameter

--	--
----	----

Return code

Void	--
------	----

Functional Description

This service disables all interrupts for which the hardware supports disabling. The state before is saved for the `EnableAllInterrupts` call.

This service is intended to start a critical section of the code. This section shall be finished by calling the `EnableAllInterrupts` service. No API service calls are allowed within this critical section.

The implementation should adapt this service to the target hardware providing a minimum overhead. Usually, this service disables recognition of interrupts by the central processing unit.

Note that this service does not support nesting. If nesting is needed for critical sections e.g. for libraries `SuspendOSInterrupts/ResumeOSInterrupts` or `SuspendAllInterrupt/ResumeAllInterrupts` should be used.

This function might be implemented using a global interrupt flag or an interrupt level register.

Particularities and Limitations
> When using before <code>StartOS</code>, the function <code>osInitialize</code> must be called first to initialize the variables which are used in the interrupt API. > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.
Expected Caller Context
> --

Table 6-13 DisableAllInterrupts

6.5.1.3 ResumeAllInterrupts

Prototype
<code>void ResumeAllInterrupts (void)</code>
Parameter
--
Return code
void
Functional Description
This service restores the recognition status of all interrupts saved by the <code>SuspendAllInterrupts</code> service. This service is the counterpart of <code>SuspendAllInterrupts</code> service, which has to have been called before, and its aim is the completion of the critical section of code. No API service calls beside <code>SuspendAllInterrupts/ResumeAllInterrupts</code> pairs and <code>SuspendOSInterrupts/ResumeOSInterrupts</code> pairs are allowed within this critical section. The implementation should adapt this service to the target hardware providing a minimum overhead. <code>SuspendAllInterrupts/ResumeAllInterrupts</code> can be nested. In case of nesting pairs of the calls <code>SuspendAllInterrupts</code> and <code>ResumeAllInterrupts</code> the interrupt recognition status saved by the first call of <code>SuspendAllInterrupts</code> is restored by the last call of the <code>ResumeAllInterrupts</code> service. This function might be implemented using a global interrupt flag or an interrupt level register.
Particularities and Limitations
> When using before <code>StartOS</code>, the function <code>osInitialize</code> must be called first to initialize the variables which are used in the interrupt API. > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.

Expected Caller Context
> --

Table 6-14 ResumeAllInterrupts

6.5.1.4 SuspendAllInterrupts

Prototype	
void SuspendAllInterrupts (void)	
Parameter	
--	--
Return code	
void	--
Functional Description	
This service saves the recognition status of all interrupts and disables all interrupts for which the hardware supports disabling. This service is intended to protect a critical section of code from interruptions of any kind. This section shall be finished by calling the ResumeAllInterrupts service. No API service calls beside SuspendAllInterrupts/ResumeAllInterrupts pairs and SuspendOSInterrupts/ResumeOSInterrupts pairs are allowed within this critical section. The implementation should adapt this service to the target hardware providing a minimum overhead. This function might be implemented using a global interrupt flag or an interrupt level register.	
Particularities and Limitations	
> When using before StartOS, the function osInitialize must be called first to initialize the variables which are used in the interrupt API. > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.	
Expected Caller Context	
> --	

Table 6-15 SuspendAllInterrupts

6.5.1.5 ResumeOSInterrupts

Prototype	
void ResumeOSInterrupts (void)	
Parameter	
--	--
Return code	
void	--

Functional Description

This service restores the recognition status of interrupts saved by the `SuspendOSInterrupts` service.

This service is the counterpart of `SuspendOSInterrupts` service, which has to have been called before, and its aim is the completion of the critical section of code. No API service calls beside `SuspendAllInterrupts/ResumeAllInterrupts` pairs and `SuspendOSInterrupts/ResumeOSInterrupts` pairs are allowed within this critical section.

The implementation should adapt this service to the target hardware providing a minimum overhead.

`SuspendOSInterrupts/ResumeOSInterrupts` can be nested. In case of nesting pairs of the calls `SuspendOSInterrupts` and `ResumeOSInterrupts` the interrupt recognition status saved by the first call of `SuspendOSInterrupts` is restored by the last call of the `ResumeOSInterrupts` service.

This function might be implemented using a global interrupt flag or an interrupt level register

Particularities and Limitations

- > When using before `StartOS`, the function `osInitialize` must be called first to initialize the variables which are used in the interrupt API.
- > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.

Expected Caller Context

> --

Table 6-16 `ResumeOSInterrupts`

6.5.1.6 `SuspendOSInterrupts`

Prototype

```
void SuspendOSInterrupts ( void )
```

Parameter

--	--
----	----

Return code

void	--
------	----

Functional Description

This service saves the recognition status of interrupts of category 2 and disables the recognition of these interrupts.

This service is intended to protect a critical section of code. This section shall be finished by calling the `ResumeOSInterrupts` service. No API service calls beside `SuspendAllInterrupts/ResumeAllInterrupts` pairs and `SuspendOSInterrupts/ResumeOSInterrupts` pairs are allowed within this critical section.

The implementation should adapt this service to the target hardware providing a minimum overhead. It is intended only to disable interrupts of category 2. However, if this is not possible in an efficient way more interrupts may be disabled.

This function might be implemented using a global interrupt flag or an interrupt level register.

Particularities and Limitations

- > When using before `StartOS`, the function `osInitialize` must be called first to initialize the variables which are used in the interrupt API.
- > The function must not be used within handlers of non-maskable interrupts as this can violate the consistency of internal variables.

Expected Caller Context

- > --

Table 6-17 `SuspendOSInterrupts`

6.5.2 Resource Management

The affected functions are:

- > `GetResource`
- > `ReleaseResource`

The implementation specific behaviour of these functions is described in [4].

6.5.2.1 GetResource

Prototype

```
StatusType GetResource ( ResourceType ResID )
```

Parameter

ResID	Reference to resource
-------	-----------------------

Return code

E_OK	No error
E_OS_ID	Resource ResID is invalid
E_OS_ACCESS	Attempt to get a resource which is already occupied by any task or ISR, or the statically assigned priority of the calling task or interrupt routine is higher than the calculated ceiling priority.

Functional Description

This call serves to enter critical sections in the code that are assigned to the resource referenced by `ResID`. A critical section shall always be left using `ReleaseResource`.

Nested resource occupation is only allowed if the inner critical sections are completely executed within the surrounding critical section (strictly stacked, Restrictions when using resources). Nested occupation of one and the same resource is also forbidden!

It is recommended that corresponding calls to `GetResource` and `ReleaseResource` appear within the same function.

It is not allowed to use services which are points of rescheduling for non preemptable tasks (`TerminateTask`, `ChainTask`, `Schedule` and `WaitEvent`) in critical sections. Additionally, critical sections are to be left before completion of an interrupt service routine.

Generally speaking, critical sections should be short.

The service may be called from an ISR and from task level.

Depending on the possibility to manipulate interrupt levels, this function may be used on interrupt level or not and may be implemented differently.

If used on task level, the behavior and functionality is always the same (according to the specification).

Particularities and Limitations

> --

Expected Caller Context

> Task level or cat2 ISR

Table 6-18 `GetResource`

6.5.2.2 `ReleaseResource`

Prototype

```
StatusType ReleaseResource ( ResourceType ResID )
```

Parameter

<code>ResID</code>	Reference to resource
--------------------	-----------------------

Return code

<code>E_OK</code>	No error
<code>E_OS_ID</code>	Resource <code>ResID</code> is invalid
<code>E_OS_NOFUNC</code>	Attempt to release a resource which is not occupied by any task or ISR, or another resource shall be released before.
<code>E_OS_ACCESS</code>	Attempt to release a resource that has a lower ceiling priority than the statically assigned priority of the calling task or interrupt routine.

Functional Description
ReleaseResource is the counterpart of <code>GetResource</code> and serves to leave critical sections in the code that are assigned to the resource referenced by <code>ResID</code>. For information on nesting conditions, see particularities of <code>GetResource</code>. The service may be called from an ISR and from task level. Depending on the possibility to manipulate interrupt levels, this function may be used on interrupt level or not and may be implemented differently. If used on task level, the behavior and functionality is always the same (according to the specification).
Particularities and Limitations
> --
Expected Caller Context
> Task level or cat2 ISR

Table 6-19 ReleaseResource

6.5.3 Execution Control

The affected functions are:

- > StartOS
- > ShutdownOS

The implementation specific behavior of these functions is described in [4].

6.5.3.1 StartOS

Prototype	
void StartOS (AppModeType Mode)	
Parameter	
Mode	application mode
Return code	
void	--
Functional Description	
The user can call this system service to start the operating system in a specific mode. Only allowed outside of the operating system, therefore implementation specific restrictions may apply. After calling <code>StartOS</code> the program never returns to the call level of <code>StartOS</code>.	
Particularities and Limitations	
>	--

Expected Caller Context

> C main function

Table 6-20 StartOS

6.5.3.2 ShutdownOS

Prototype

```
void ShutdownOS ( StatusType Error )
```

Parameter

Error	error occurred
-------	----------------

Return code

void	--
------	----

Functional Description

The user can call this system service to abort the overall system (e.g. emergency off). The operating system also calls this function internally, if it has reached an undefined internal state and is no longer ready to run.

If a `ShutdownHook` is configured the hook routine `ShutdownHook` is always called (with `Error` as argument) before shutting down the operating system.

If `ShutdownHook` returns, further behaviour of `ShutdownOS` is implementation specific.

In case of a system where OSEK OS and OSEKtime OS coexist, `ShutdownHook` has to return.

`Error` needs to be a valid error code supported by OSEK OS. In case of a system where OSEK OS and OSEKtime OS coexist, `Error` might also be a value accepted by OSEKtime OS. In this case, if enabled by an OSEKtime configuration parameter, OSEKtime OS will be shut down after OSEK OS shutdown.

After this service the operating system is shut down.

Allowed at task level, ISR level, in `ErrorHook` and `StartupHook`, and also called internally by the operating system.

If the operating system calls `ShutdownOS` it never uses `E_OK` as the passed parameter value.

After the call of `ShutdownHook` MICROSAR OS disables all interrupts and will never return to the call level. The `ShutdownHook` is called with disabled interrupts.

Particularities and Limitations

> --

Expected Caller Context
> --

Table 6-21 ShutdownOS

6.6 Hook Routines

MICROSAR OS calls several hook routines. These may be hook routines as described in the OSEK or Autosar standard. Additionally, MICROSAR provides Hook routines for ISR entry/exit, Alarm time and timing supervision (MICROSAR OS Timing Hooks).

These hook routines are described in the subchapters below.

The subchapters describe the prototypes of the called hook routines and their calling contexts. The current stack in the hook routines is implementation specific and described in [4].

6.6.1 Standard Hooks

The hook routines described in the subchapters are defined by the OSEK and Autosar standards.

All these hook routines need to be implemented by the user if they are enabled in the configuration. The OS calls these hook routines with interrupts disabled (if not stated otherwise).

6.6.1.1 StartupHook

Prototypes	
void StartupHook (void) /* general startup hook */	
void StartupHook_<App> (void) /* application specific startup hook */	
Parameter	
--	--
Return code	
void	--
Functional Description	
The user may call the initialization routines for hardware drivers.	
Particularities and Limitations	
> --	
Call Context	
> interrupt or task context	
> The <code>StartupHook</code> routine is called while the operating system is initialized.	

Table 6-22 StartupHook

6.6.1.2 PreTaskHook

Prototype	
void PreTaskHook (void)	
Parameter	
--	--
Return code	
void	--
Functional Description	
The user can use the API function <code>GetTaskID</code> to determine the new task.	
Particularities and Limitations	
> --	
Call Context	
> interrupt or task context > <code>PreTaskHook</code> is called after a task is set into the RUNNING state (not into the READY state). > For particularities of using <code>PreTaskHook</code> when using timing protection, please see [4]	

Table 6-23 PreTaskHook

6.6.1.3 PostTaskHook

Prototype	
void PostTaskHook (void)	
Parameter	
--	--
Return code	
void	--
Functional Description	
The user can use the API function <code>GetTaskID</code> to determine the currently left task.	
Particularities and Limitations	
> --	
Call Context	
> interrupt or task context > <code>PostTaskHook</code> is called before a task is taken out of the RUNNING state. > For particularities of using the <code>PostTaskHook</code> when using timing protection, please see [4]	

Table 6-24 PostTaskHook

6.6.1.4 ErrorHook

Prototype	
<pre>void ErrorHook (StatusType ErrorCode) /* general error hook */ void ErrorHook_<App> (StatusType ErrorCode) /* appl. spec. error hook */</pre>	
Parameter	
ErrorCode	Error code of API which detected the error and called the error hook
Return code	
void	--
Functional Description	
The user may use the error number parameter to decide how to react on the error. Additional error information is available in the error hook if the attributes <code>USEGETSERVICEID</code> and <code>USEPARAMETERACCESS</code> are set to <code>TRUE</code>. This information can be accessed by access macros; for details refer to the OSEK specification [3]. All possible access macros are supported by MICROSAR OS. If <code>EXTENDED_STATUS</code> is enabled and <code>ErrorInfoLevel</code> is set to <code>Modulnames</code>, additional error information is available in the <code>ErrorHook</code>. The variable <code>osActiveTaskModule</code> is a pointer to the module name and the variable <code>osActiveTaskLineNumber</code> is the line number in the C module where the API function was called. Inspecting these two variables allows the user to locate the source code that caused the error message.	
Particularities and Limitations	
> --	
Call Context	
> interrupt or task context > <code>ErrorHook</code> is called every time an API function is called with wrong parameters or if the system detects an error (e.g. stack overflow).	

Table 6-25 ErrorHook

6.6.1.5 ShutdownHook

Prototype	
<pre>void ShutdownHook (StatusType ErrorCode) /* general shutdown hook */ void ShutdownHook_<App> (StatusType ErrorCode) /* appl. spec. shutdown hook */</pre>	
Parameter	
ErrorCode	Error code of API that detected the error and called the shutdown hook, or the parameter that was passed to <code>ShutdownOS</code> .
Return code	
void	--

Functional Description
The ShutdownHook is called by ShutdownOS
Particularities and Limitations
> --
Call Context
> interrupt or task context
> The system calls the ShutdownHook routine if the function ShutdownOS was called.

Table 6-26 ShutdownHook

6.6.1.6 ProtectionHook

Prototype	
ProtectionReturnType ProtectionHook (StatusType Fatalerror)	
Parameter	
Fatalerror	depending on the detected protection error
Return code	
ProtectionReturnType	The return value determines the strategy of further operation
Functional Description	
Called on occurrence of a protection error. The application code has to decide about the recovery strategy and pass an appropriate return value to the OS.	
Particularities and Limitations	
> In the scalability class SC1, no call of the <code>ProtectionHook</code> is supported.	
Call Context	
> interrupt or task context	
> The <code>ProtectionHook</code> is called if a TimingProtection failure (SC2, SC4), a memory protection failure (SC3, SC4), or processor exception (e.g. division by zero, illegal instruction etc.) is detected by MICROSAR OS.	

Table 6-27 ProtectionHook

6.6.2 ISR Hooks

6.6.2.1 UserPreISRHook

Prototype	
Void UserPreISRHook (ISRType isr)	
Parameter	
Isr	The identifier of the ISR that is about to be entered
Return code	
Void	--

Functional Description
Called just before entering an ISR routine of a category 2 interrupt.
This Hook is intended to be used as a development aid. For example, it may be used to measure interrupt run times.
This Hook is only available if the attribute CallISRHooks is set to <code>TRUE</code> .
Particularities and Limitations
> Only API functions that are allowed in cat2 ISRs are allowed to be called in the UserPreISRHook.
Call Context
> The UserPreISRHook runs in the exact same context as the ISR that is executed afterwards. This includes settings for interrupt nesting, timing protection, timing measurement and memory protection.
> All OS API functions, incl. GetISRID(), GetApplicationID(), CheckObjectAccess() etc, work just as if called from within the ISR

Table 6-28 UserPreISRHook

6.6.2.2 UserPostISRHook

Prototype	
Void UserPostISRHook (ISRType isr)	
Parameter	
Isr	The identifier of the ISR that was just left
Return code	
Void	--
Functional Description	
Called just after leaving an ISR routine of a category 2 interrupt. This Hook is intended to be used as a development aid. For example, it may be used to measure interrupt run times. This Hook is only available if the attribute CallISRHooks is set to <code>TRUE</code>.	
Particularities and Limitations	
The UserPostISRHook is called only after a regular return from the ISR routine. In particular: > If an ISR is interrupted by a higher priority ISR, the UserPostISRHook is not called before entering the new ISR. > If an ISR is killed, the UserPostISRHook is not called. > Only API functions that are allowed in cat2 ISRs are allowed to be called in the UserPostISRHook.	
Call Context	
> The UserPreISRHook runs in the exact same context as the ISR that was just executed. This includes settings for interrupt nesting, timing protection, timing measurement and memory protection. > All OS API functions, incl. GetISRID(), GetApplicationID(), CheckObjectAccess() etc, work just as if called from within the ISR	

Table 6-29 UserPostISRHook

6.6.3 Alarm Hook

6.6.3.1 PreAlarmHook (currently not supported)

Prototype	
void PreAlarmHook_<CounterName> (void)	
Parameter	
void	--
Return code	
void	--
Functional Description	
Called in the timer ISR just before the alarm handling of the OS.	
This Hook is only available if the timer attribute PreAlarmHook is set to <code>TRUE</code>	
Particularities and Limitations	
> Note that this feature is currently not supported. It will be available in future releases. > Only API functions that are allowed in cat2 ISRs are allowed to be called in the PreAlarmHook. > The execution time of the PreAlarmHook is not considered by the timing protection.	
Call Context	
> The PreAlarmHook runs in the same context as the system timer ISR. If an owner application is configured, the system timer ISR and the PreAlarmHook is executed with the application rights of this owner application. > Interrupts of category 2 are disabled during the execution of the PreAlarmHook.	

Table 6-30 PreAlarmHook

6.6.4 MICROSAR OS Timing Hooks

MICROSAR OS supports timing measurement and analysis by external tools. Therefore it provides timing hooks. Timing hooks inform the external tools about several events within the OS:

- Activation (arrival) of a task or ISR
- Context switch
- Locking of interrupts, resources or spinlocks

This documentation presents the respective hook routines in separate subchapters below.

The OS calls Timing hooks only if the user has configured them as described in Table 7-1, attribute TimingHooks. The user shall implement the hooks as macros in the configured header file. The OS provides empty definitions of these hooks. It uses the empty definition of a hook in case of an unavailable definition by the user. Because of the empty definition, the user needs not to implement all hooks.

6.6.4.1 Hooks for arrival

MICROSAR OS provides hooks that allow an external tool to trace all activations of task as well as further arrivals like the setting of an event or the release of a semaphore with transfer to another task.

This shall allow the external tool to visualize the arrivals and to measure the time between them in order to allow a schedulability analysis.

Mind that schedulability analysis requires the minimum time between arrivals while these hooks only provide measured values.

6.6.4.1.1 OS_VTH_ACTIVATION

Prototype	
<code>OS_VTH_ACTIVATION(TaskId, DestCoreId, CallerCoreId)</code>	
Parameter	
TaskId	Identifier of the task which is activated
DestCoreId	Identifier of the core on which the task is activated
CallerCoreId	Identifier of the core which performs the activation (has called ActivateTask, has called TerminateTask or has performed an alarm/schedule table action to activate a task)
Return code	
-	-
Functional Description	
This hook is called on the caller core when that core has successfully performed the activation of TaskId on the destination core. On single core systems both core IDs are always identical.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-31 OS_VTH_ACTIVATION

6.6.4.1.2 OS_VTH_SETEVENT

Prototype	
<code>OS_VTH_SETEVENT(TaskId, EventMask, StateChange, DestCoreId, CallerCoreId)</code>	
Parameter	
TaskId	Identifier of the task which receives this event
EventMask	A bit mask with the events which shall be set

StateChange	TRUE: The task state has changed from WAITING to READY FALSE: The task state hasn't changed
DestCoreId	Identifier of the core on which the task receives the event
CallerCoreId	Identifier of the core which performs the event setting (has called SetEvent or performed an alarm/schedule table action to set an event)
Return code	
-	-
Functional Description	
This hook is called on the caller core when that core has successfully performed the event setting on the destination core. On single core systems both core IDs are always identical.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-32 OS_VTH_SETEVENT

6.6.4.1.3 OS_VTH_TRANSFER_SEMA

Prototype	
OS_VTH_TRANSFER_SEMA(FromThreadId, ToTaskId, SemaId, DestCoreId, CallerCoreId)	
Parameter	
FromThreadId	Identifier of the thread (task; ISR) which releases the semaphore
ToTaskId	Identifier of the task which receives the semaphore
SemaId	Identifier of the semaphore to be transferred
DestCoreId	Identifier of the core on which the task gets the semaphore
CallerCoreId	Identifier of the core which releases the semaphore
Return code	
-	-
Functional Description	
This hook is called on the caller core when that core has successfully performed release of the semaphore while a task was waiting for that semaphore. On single core systems both core IDs are always identical.	

Particularities and Limitations
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The semaphore feature is optional, so this macro may not be necessary on all implementations of MICROSAR OS.
Call context
> The hook routine is called from within operating system API functions with interrupts disabled.

Table 6-33 OS_VTH_TRANSFER_SEMA

6.6.4.2 Hook for context switch

MICROSAR OS provides a hook routine allowing external tools to trace all context switches from task to ISR and back as well as between tasks. So external tools may visualize the information or measure the execution time of tasks and ISRs.

Mind that measured values may not reflect the worst case, which would be necessary for schedulability analysis.

6.6.4.2.1 OS_VTH_SCHEDULE

Prototype	
<pre>OS_VTH_SCHEDULE(FromThreadId, FromThreadReason, ToThreadId, ToThreadReason, CallerCoreId)</pre>	
Parameter	
FromThreadId	Identifier of the thread (task, ISR) which has run on the caller core before the switch took place
FromThreadReason	OS_VTHP_TASK_TERMINATION: The thread is a task, which has just been terminated. OS_VTHP_ISR_END: The thread is an ISR, which has reached its end. OS_VTHP_TASK_WAITEVENT: The thread is a task, which waits for an event. OS_VTHP_TASK_WAITSEMA: The thread is a task, which waits for the release of a semaphore. OS_VTHP_THREAD_PREEMPT: The thread is interrupted by another one, which has higher priority.
ToThreadId	The identifier of the thread, which will run from now on

ToThreadReason	OS_VTHP_TASK_ACTIVATION: The thread is a task, which was activated. OS_VTHP_ISR_START: The thread is an ISR, which will now start execution. OS_VTHP_TASK_SETEVENT: The thread is a task, which has just received an event it was waiting for. It resumes execution right behind the call of WaitEvent. OS_VTHP_GOTSEMA: The thread is a task, which has just got the semaphore it was waiting for. OS_VTHP_THREAD_RESUME: The thread is a task or ISR, which was preempted before and becomes running again as all higher priority tasks and ISRs do not run anymore.
CallerCoreId	Identifier of the core which performs the thread switch
Return code	
-	-
Functional Description	
This hook is called on the caller core when that core in case it performs a thread switch (from one task or ISR to another task or ISR). On single core systems both core IDs are always identical.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine	
Call context	
> The hook routine is called from within operating system internal functions with interrupts disabled.	

Table 6-34 OS_VTH_SCHEDULE

6.6.4.3 Hooks for locking

MICROSAR OS provides hooks, which allow an external tool to trace locks. This is important as locking times of tasks and ISRs influence the execution of other tasks and ISRs. The kind of influence is different for different locks and is presented below in the functional description of the respective hooks.

Please keep in mind that measured times for locking may not reflect the worst case.

6.6.4.3.1 OS_VTH_GOT_RES

Prototype	
OS_VTH_GOT_RES(ResId, CallerCoreId)	
Parameter	
ResId	Identifier of the resource which has been taken
CallerCoreId	Identifier of the core where GetResorce was called

Return code	
-	-
Functional Description	
The OS calls this hook on a successful call of the API function GetResource. The priority of the calling task or ISR has been increased so that other tasks and ISRs on the same core may need to wait until they can be executed.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-35 OS_VTH_GOT_RES

6.6.4.3.2 OS_VTH_REL_RES

Prototype	
OS_VTH_REL_RES(ResId, CallerCoreId)	
Parameter	
ResId	Identifier of the resource which has been released
CallerCoreId	Identifier of the core where ReleaseResource was called
Return code	
-	-
Functional Description	
The OS calls this hook on a successful call of the API function ReleaseResource. The priority of the calling task or ISR has been decreased so that other tasks and ISRs on the same core may become running as a result.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-36 OS_VTH_REL_RES

6.6.4.3.3 OS_VTH_REQ_SPINLOCK

Prototype	
OS_VTH_REQ_SPINLOCK(SpinlockId, CallerCoreId)	

Parameter	
SpinlockId	Identifier of the spinlock which has been requested
CallerCoreId	Identifier of the core where GetSpinlock was called
Return code	
-	-
Functional Description	
The OS calls this hook on an unsuccessful attempt to get a spinlock. The calling task or ISR enters a busy waiting state. Tasks or ISRs of lower priority have to wait until this task or ISR has taken and released the spinlock.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The hook is not called for optimized spinlocks > The hook is not called for operating system internal spinlocks > The hook is called only on multicore operating system implementations	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-37 OS_VTH_REQ_SPINLOCK

6.6.4.3.4 OS_VTH_GOT_SPINLOCK

Prototype	
OS_VTH_GOT_SPINLOCK(SpinlockId, CallerCoreId)	
Parameter	
SpinlockId	Identifier of the spinlock which has been taken
CallerCoreId	Identifier of the core where GetSpinlock or TryToGetSpinlock were called
Return code	
-	-
Functional Description	
The OS calls this hook whenever a spinlock has successfully been taken. If the task or ISR was not successful immediately (entered busy waiting state), this hook means that it leaves the busy waiting state. From now on no other task or ISR may get the spinlock until the current task or ISR has released it.	

Particularities and Limitations
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The hook is not called for optimized spinlocks > The hook is not called for operating system internal spinlocks > The hook is called only on multicore operating system implementations
Call context
> The hook routine is called from within operating system API functions with interrupts disabled.

Table 6-38 OS_VTH_GOT_SPINLOCK

6.6.4.3.5 OS_VTH_REL_SPINLOCK

Prototype	
OS_VTH_REL_SPINLOCK(SpinlockId, CallerCoreId)	
Parameter	
SpinlockId	Identifier of the spinlock which has been released
CallerCoreId	Identifier of the core where ReleaseSpinlock was called
Return code	
-	-
Functional Description	
The OS calls this hook on a release of a spinlock. Other tasks and ISR may take the spinlock now.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The hook is not called for optimized spinlocks > The hook is not called for operating system internal spinlocks > The hook is called only on multicore operating system implementations	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-39 OS_VTH_REL_SPINLOCK

6.6.4.3.6 OS_VTH_TOOK_SEMA

Prototype	
<code>OS_VTH_TOOK_SEMA(TaskId, SemaId, CallerCoreId)</code>	
Parameter	
TaskId	Identifier of the task which has taken the semaphore
SemaId	Identifier of the semaphore which has been taken
CallerCoreId	Identifier of the core where GetSemaphore was called
Return code	
-	-
Functional Description	
The OS calls this hook in the API function GetSemaphore if the semaphore was free before the call. If the semaphore was held by another task, the current task is transferred to the waiting state, which is signaled to the external tool by means of the OS_VTH_SCHEDULE hook as described in chapter 6.6.4.2.1.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The semaphore feature is optional, so this macro may not be necessary on all implementations of MICROSAR OS.	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-40 OS_VTH_TOOK_SEMA

6.6.4.3.7 OS_VTH_REL_SEMA

Prototype	
<code>OS_VTH_REL_SEMA(ThreadId, SemaId, CallerCoreId)</code>	
Parameter	
ThreadId	Identifier of the task or ISR which has released the semaphore
SemaId	Identifier of the semaphore which has been released
CallerCoreId	Identifier of the core where ReleaseSemaphore was called
Return code	
-	-

Functional Description
The OS calls this hook in the API function ReleaseSemaphore if the semaphore becomes free after the call. If a task is currently waiting for the semaphore, the API function GetSemaphore calls OS_VTH_TRANSFER_SEMA instead, as described in chapter 6.6.4.1.3.
Particularities and Limitations
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The semaphore feature is optional, so this macro may not be necessary on all implementations of MICROSAR OS.
Call context
> The hook routine is called from within operating system API functions with interrupts disabled.

Table 6-41 OS_VTH_REL_SEMA

6.6.4.3.8 OS_VTH_DISABLEDINT

Prototype	
OS_VTH_DISABLEDINT(IntLockId, CallerCoreId)	
Parameter	
IntLockId	OS_VTHP_CAT2INTERRUPTS: Interrupts have been disabled by means of the current interrupt level. That interrupt level has been changed in order to disable all category 2 interrupts, which also prevents task switch and alarm/schedule table management. OS_VTHP_ALLINTERRUPTS: Interrupts have been disabled by means of the global interrupt enable/disable flag. Additionally to the effects described above, also category 1 interrupts are disabled.
CallerCoreId	Identifier of the core where interrupts are disabled
Return code	
-	-
Functional Description	
The OS calls this hook if the application has called an API function to disable interrupts. The parameter IntLockId describes whether category 1 interrupts may still occur. Mind that the two types of interrupt locking (as described by the IntLockId) are independent from each other so that the hook may be called twice before the hook OS_VTH_ENABLEDINT is called, dependent on the application.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The hook is not called for operating system internal interrupt locks	

Call context
> The hook routine is called from within operating system API functions with interrupts disabled.

Table 6-42 OS_VTH_DISABLEDINT

6.6.4.3.9 OS_VTH_ENABLEDINT

Prototype	
OS_VTH_ENABLEDINT(IntLockId, CallerCoreId)	
Parameter	
IntLockId	OS_VTHP_CAT2INTERRUPTS: Interrupts had been disabled by means of the current interrupt level until this hook was called. The OS releases this lock right after the hook has returned. OS_VTHP_ALLINTERRUPTS: Interrupts had been disabled by means of the global interrupt enable/disable flag before this hook was called. The OS releases this lock right after the hook has returned.
CallerCoreId	Identifier of the core where interrupts are disabled
Return code	
-	-
Functional Description	
The OS calls this hook if the application has called an API function to enable interrupts. Mind that the two types of interrupt locking (as described by the IntLockId) are independent from each other so that interrupts may still be disabled by means of the other locking type after this hook has returned.	
Particularities and Limitations	
> The hook is expected to be implemented as a macro. > Reentrancy is possible on multicore systems with different caller core IDs > Call of any operating system API function is prohibited in this hook routine > The hook is not called for operating system internal interrupt locks	
Call context	
> The hook routine is called from within operating system API functions with interrupts disabled.	

Table 6-43 OS_VTH_ENABLEDINT

6.7 Non-Trusted Functions

Non-trusted functions are a VECTOR extension to the AUTOSAR OS specification. This concept allows non-trusted applications to provide service functions, which are callable by trusted or non-trusted tasks and ISRs, comparable to the AUTOSAR OS API CallTrustedFunction.

6.7.1 Functionality

The OS executes Non-trusted functions with the memory access rights and service protection rights of the owner application. These functions can access local data of the owner application

without the possibility to overwrite private data of other applications. Non-trusted functions have no access to the data on the callers stack.

6.7.2 API

Prototype	
<pre>StatusType osCallNonTrustedFunction(NonTrustedFunctionIndexType FunctionIndex, NonTrustedFunctionParameterRefType FunctionParams);</pre>	
Parameter	
FunctionIndex	Index of the function to be called.
FunctionParams	Pointer to the parameters for the function to be called. If no parameters are provided, a NULL pointer has to be passed.
Return code	
E_OK	No error
E_OS_SERVICEID	No function defined for this index
Functional Description	
Executes the non-trusted function referenced by FunctionIndex and passes argument FunctionParams. The non-trusted function must conform to the following C prototype: <pre>void NONTRUSTED_<name of the non-trusted function>(NonTrustedFunctionIndexType, NonTrustedFunctionParameterRefType);</pre> The arguments are the same as the arguments of CallNonTrustedFunction.	
Particularities and Limitations	
> The non-trusted function is called in user mode with memory protection enabled > The function has memory access rights of the owner application > The function has the service protection rights of the owner application	
Call context	
> Task, CAT2 ISR, trusted function, non-trusted function	

Table 6-44 API osCallNonTrustedFunction



Note

Vector MICROSAR OS implementations offer the possibility of stub function generation for trusted functions. This mechanism is **not** available for non-trusted functions.

6.8 MPU Access Checking API

MISCROSAR OS provides API, which returns whether the caller has access to a given address.

Prototype
<pre>uint8 osCheckMPUAccess(uint8* DestinationAddress)</pre>

Parameter	
DestinationAddress	The address to be checked for access
Return code	
uint8	0: Current Software part has write access 1: Current Software part has no write access
Particularities and Limitations	
> The value of DestinationAddress may be temporarily altered within this function (depending on the platform). > Due to data consistency, the function should not be used on addresses, which are shared among cores. > A protection violation may occur during this function. But this protection violation does not lead to a shutdown of the OS > This function cannot be called prior to StartOS	
Call context	
> ProtectionHook > Task trusted/non-trusted > ISR Cat2 trusted/non-trusted > ErrorHook > ShutdownHook, > trusted function > non trusted function > StartupHook	

Table 6-45 osCheckMPUAccess API

6.9 Peripheral Regions

On some platforms, there are memory mapped hardware registers, which are only accessible in privileged mode. To access this kind of registers even in non-trusted applications (i.e. non-privileged mode), MICROSAR OS provides Peripheral Regions.

To access such registers you have to configure a Peripheral Region and pass it's ID to the Peripheral Region API. The OS checks whether the caller has access to this region and performs the requested access operation.

The OS provides access functions for the following access types: 8, 16, and 32 bit.

6.9.1 Reading functions

Prototype	
osuint8	osReadPeripheral8 (osuint16 area, osuint32 address)
osuint16	osReadPeripheral16 (osuint16 area, osuint32 address)
osuint32	osReadPeripheral32 (osuint16 area, osuint32 address)

Parameter	
area	Identifier of peripheral regions to the read from
address	Address to be read from
Return code	
	The content of “address” interpreted as 8 bit, 16 bit or 32 bit value
Functional Description	
> reads either an 8 bit, or a 16 bit or a 32 bit value from “address” > The function performs accessing checks (whether the caller has accessing rights to the peripheral region and whether the address to be read from is within the configured range of the peripheral region) > The error hook is raised in case of an error > A shutdown is not issued in case of an error	
Particularities and Limitations	
> These functions may not be called from OS hooks	
Call context	
> These functions may be called from Task context > These functions may be called from category 2 ISR context > These functions can be called with interrupts enabled or with interrupts disabled	

Table 6-46 ReadPeripheral API

6.9.2 Writing functions

Prototype	
<pre>void osWritePeripheral18(osuint16 area, osuint32 address, osuint8 value) void osWritePeripheral16(osuint16 area, osuint32 address, osuint16 value) void osWritePeripheral32(osuint16 area, osuint32 address, osuint32 value)</pre>	
Parameter	
area	Identifier of peripheral regions to the read from
address	Address to write to
Value	Value to be written
Return code	
None	
Functional Description	
> Writes to either an 8 bit, or a 16 bit or a 32 bit value > The function performs accessing checks (whether the caller has accessing rights to the peripheral region and whether the address to be read from is within the configured range of the peripheral region) > The error hook is raised in case of an error > A shutdown is not issued in case of an error	

Particularities and Limitations
> These functions may not be called from OS hooks
Call context
> These functions may be called from Task context
> These functions may be called from category 2 ISR context
> These functions can be called with interrupts enabled or with interrupts disabled

Table 6-47 WritePeripheral API

6.9.3 Modifying functions

Prototype	
<pre>void osModifyPeripheral18(osuint16 area, osuint32 address, osuint8 clearmask, osuint8 setmask) void osModifyPeripheral16(osuint16 area, osuint32 address, osuint16 clearmask, osuint16 setmask) void osModifyPeripheral32(osuint16 area, osuint32 address, osuint32 clearmask, osuint32 setmask)</pre>	
Parameter	
area	Identifier of peripheral regions to the read from
address	Address to be modified
clearmask	Bitmask which is bitwise "ANDed" to "address"
setmask	Bitmask which is bitwise "ORed" to "address"
Return code	
None	
Functional Description	
> The function performs accessing checks (whether the caller has accessing rights to the peripheral region and whether the address to be read from is within the configured range of the peripheral region) > The error hook is raised in case of an error > A shutdown is not issued in case of an error > After the access checks has passed first the "clearmask" is ANDed to "address" and afterwards the "setmask" is ORed to it.	
Particularities and Limitations	
> These functions may not be called from OS hooks	
Call context	
> These functions may be called from Task context > These functions may be called from category 2 ISR context > These functions can be called with interrupts enabled or with interrupts disabled	

Table 6-48 ModifyPeripheral API

7 Configuration

Since AUTOSAR OS 3.0.0 specification, XML is used to define and describe an OS configuration. However, OIL is still supported as an alternative description language, especially if the OS shall be used stand-alone without any other AUTOSAR software modules.

All OSEK objects and their attributes have to be defined by one of these description languages.

7.1 Configuration and generation process




Figure 7-1 System overview of software parts

The figure above shows the complete configuration process of a MICROSAR OS. First all OS objects have to be defined. This can be done either by an AUTOSAR XML configuration tool or by the OIL Configurator (in OIL).

An OIL or XML file is the base of the code generation process. After code generation all files (OS source files, application files and generated OS configuration files) have to be compiled and linked to an executable.

7.1.1 XML Configuration

A configuration which is based on XML must conform to the AUTOSAR XML schema[8].

To edit a MICROSAR OS XML configuration the DaVinci Configurator Pro or Base of Vector Informatik GmbH can be used. Other tools that are able to edit AUTOSAR configurations may also be used.

The XML file that the tool produces has to be passed to the code generator to generate the configuration files.

7.1.2 OIL Configurator

The OIL specification is based on the document "OIL: OSEK Implementation Language – Version: 2.3" (ref. [6]). Additional Attributes are defined by Vector Informatik GmbH; the resulting version of OIL is 4.0.

The OIL Configurator is a Windows based program that is used to configure an OSEK application. The OIL Configurator reads and writes OIL files (OSEK Implementation Language). The usage of the OIL Configurator is described in the online help of the OIL Configurator.

The OIL Configurator has separate property tabs for each OSEK object type. Each object has several standard attributes that are defined in the OIL specification. Additional attributes that are implementation specific are described in the hardware specific document [4].

7.2 Configuration Variants

The OS supports the configuration variants

> VARIANT-PRE-COMPILE

The MICROSAR OS system is typically delivered with the source code. The kernel is implemented in several optimized variants, which are enabled from the OIL Configurator using C defines. The source code of the operating system has to be compiled if the configuration has changed. For some implementations, a library version of the operating system is also supplied. For different configurations, different libraries have to be linked to the application.

The configuration classes of the OS parameters depend on the supported configuration variants. For their definitions please see the `OS_<platform and derivate>_bswmd.arxml` file.

7.3 Configuration of the XML / OIL Attributes

Some of the attributes of an OSEK object are standard for all OSEK implementations, and some are specific for each implementation.

This chapter describes the attributes the user can set for each OSEK object. Please note that setting an attribute to `TRUE` is used as a synonym for selecting it and setting to `FALSE` is used as a synonym for deselecting it. The reason is that a selection in the OIL Configurator corresponds to setting the attribute to `TRUE` in the OIL file (this can be checked by opening the OIL file with a normal text editor).



Caution

If a library version of the operating system is used, some attributes or attribute values are not available or predefined.

7.3.1 OS

The OS object can only be defined once. The OS object controls general aspects of the operating system.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	n.a.	--	> OIL: Freely selectable name, not used by the code generator. > XML: Not available in XML
Comment	n.a.	--	Any comment.
CC	OsOSCC	BCC1, BCC2, ECC1, ECC2, AUTO	Conformance class.
STATUS	OsStatus	STANDARD, EXTENDED	Level for status (error) messages.
SCALABILITY CLASS	OsScalabilityClass	SC1, SC2, SC3, SC4, AUTO .	Scalability class.
SCHEDULE	OsOSSchedule	NON, FULL, MIXED, AUTO	Scheduling policy.
n.a.	OsHooks	hook routines as stated below (as Booleans)	> XML: Used as a container to store hook routine information. > OIL: not available
STARTUPHOOK	OsStartupHook	TRUE, FALSE	Selects if the hook routine <code>StartupHook</code> is called at system startup. > XML: This attribute is placed in container <code>OsHooks</code>
ERRORHOOK	OsErrorHook	TRUE, FALSE	Selects if the hook routine <code>ErrorHook</code> is called if an error occurs. > XML: This attribute is placed in container <code>OsHooks</code>
SHUTDOWNHOOK	OsShutdownHook	TRUE, FALSE	Selects if the hook routine <code>ShutdownHook</code> is called at system shutdown. > XML: This attribute is placed in container <code>OsHooks</code>
PRETASKHOOK	OsPreTaskHook	TRUE, FALSE	Selects if the hook routine <code>PreTaskHook</code> is called at every task switch. > XML: This attribute is placed in container <code>OsHooks</code>
POSTTASKHOOK	OsPostTaskHook	TRUE, FALSE	Selects if the hook routine <code>PostTaskHook</code> is called at every task switch. > XML: This attribute is placed in container <code>OsHooks</code>

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
PROTECTIONHOOK	OsProtectionHook	TRUE, FALSE	Selects if the hook routine <code>ProtectionHook</code> is called when a protection error is detected. This can only be selected in scalability classes SC2, SC3, and SC4. > XML: This attribute is placed in container <code>OsHooks</code>
CallISRHooks	OsOSCallISRHooks	TRUE, FALSE	Selects whether the routines <code>UserPreISRHook</code> and <code>UserPostISRHook</code> are called at the entry/exit of each ISR execution.
USEGETSERVICEID	OsUseGetServiceId	TRUE, FALSE	Enables the use of access macros for the service ID information in the error hook.
USEPARAMETER-ACCESS	OsUseParameterAccess	TRUE, FALSE	Enables the use of access macros for the context related information in the error hook.
USERESCHEDULER	OsUseResScheduler	TRUE, FALSE	This parameter is available, as the AUTOSAR standard requires it. Since AUTOSAR 4 the resource RES_SCHEDULER was removed as special case, therefore this attribute is silently ignored by MICROSAR OS.
STACKMONITORING	OsStackMonitoring	TRUE, FALSE	If selected, a stack check is performed with each task switch. This attribute is only available if the implementation supports stacks. (In <code>osCAN OSEK</code> implementations this feature was selected by the attribute <code>WithStackCheck</code> , which is now obsolete) See also chapter 3.2.2.3 for details.
StackUsageMeasurement	OsStackUsageMeasurement	TRUE, FALSE , AUTO	If selected, the stacks are filled with an indicator value during StartOS. This allows measuring the stack usage of tasks and ISRs. See also chapter 3.2.2.5. If AUTO is selected, <code>StackUsageMeasurement</code> uses the same setting as <code>STACKMONITORING</code> .
ErrorInfoLevel	OsOSErrorInfoLevel	STANDARD , Modulnames	If set to STANDARD , the operating system will report standard OSEK error codes and additional unique error numbers. If set to <code>Modulnames</code> , additional information about the error location will be reported. Setting to <code>Modulnames</code> increases ROM usage.
OSInternalChecks	OsOSInternalChecks	STANDARD , ADDITIONAL	If set to STANDARD , the operating system will perform standard OSEK error checking. If set to Additional , some additional checks will be performed. Setting to Additional will increase the execution time of API functions.
Compiler	OsOSCompiler	<i>Implementation specific</i>	The compiler can be chosen. If there is only one compiler this attribute is also set by default.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ORTIDebug Support	OsOSORTIDebug Support	TRUE, FALSE	The OS generator produces an ORTI file when this attribute/parameter is set. The attribute/parameter is only available on implementations supporting ORTI.
ORTIDebugLevel	OsOSORTIDebug Level	ORTI_20 , ORTI_21_Standard, ORTI_21_Additional ORTI_22_Standard, ORTI_22_Additional	This attribute/parameter provides the possibility to define an ORTI standard. The OS generator produces an ORTI file in accordance to the selected version of the standard. The OS supports the versions 2.1 and 2.2 of the standard in two variants. The “Standard” variant supports only those ORTI features, which do not cost overhead in runtime and memory consumption. The “Additional” variant also supports ORTI features with runtime and memory overhead. For the version 2.0 of the ORTI standard, the OS always provides the maximum information regardless of the overhead. The attribute/parameter is available only on implementations with ORTI support. Some implementations only support a subset of the selection alternatives.
APIOptimization	OsOSAPI Optimization	automatic, manual	> Automatic: The on / off switching of API functions is done automatically in dependency of the OS configuration. > Manual: The API functions may be switched on / off by user directly. See chapter 7.3.1.1 for information about the sub-attributes.
InternalTrace	OsOSInternal Trace	TRUE, FALSE	Switches the usage of the Internal trace feature of MICROSAR OS on or off. See chapter 7.3.1.2 for information about the sub-attributes.
UserConfigurationVersion	OsOSUserConfigurationVersion	1...65535	Version number of the OS configuration. This numeric value is not used by the OS, but enables the user to track changes in the configuration and validate the configuration version actually used in the ECUC. Therefore, it is suggested to increment this value each time the OS configuration is modified.
ProtectionHook Reaction	OsOSProtection HookReaction	ALL , SELECTED	MICROSAR OS allows limiting the allowed return values of the ProtectionHook. This can increase performance, because it reduces the amount of return information that must be saved for forcible termination. Note that the OS can only take advantage of this parameter if OsOSAPIOptimization/Manual/TerminateApplication=FALSE is set. See chapter 7.3.1.3 for information about the

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			sub-attributes.
Timing Measurement	OsOSTiming Measurement	TRUE , FALSE	Switches the Timing measurement feature of MICROSAR OS on or off. If this attribute is set to FALSE and timing measurement is selected for a task or ISR, that setting is ignored with a warning. See chapter 7.3.1.4 for information about the sub-attributes. Chapter 3.2.4.2 provides more detailed information about configuration of timing measurement.
TypeHeader Include	OsOSTypeHeader Include	TRUE , FALSE	If selected, the AUTOSAR type headers are included in the file os_cfg.h. This is included in the file os.h, which has to be included in all source files that use API functions of MICROSAR OS OSEK/AUTOSAR. The AUTOSAR type headers are not necessary for the usage of MICROSAR OS OSEK/AUTOSAR, so it is safe to deselect this attribute.
EnumeratedUnhandledISRs	OsOSEnumerated UnhandledISRs	TRUE , FALSE	Determines the handling of unassigned interrupt sources. The default of this attribute is FALSE. FALSE: This is the normal handling for unassigned interrupt sources. If no interrupt service routine is defined in OIL for an interrupt source the corresponding interrupt vector will be directed to one common unhandled exception handler. This is the recommended setting for the final application software. TRUE: During application development, there may be interrupts issued by unassigned interrupt sources. In such case it could be a big effort to determine the interrupt source. If this attribute is set to TRUE the interrupt vector of each unassigned interrupt source will be directed to an unhandled exception routine. If an unhandled exception occurs in that case, the interrupt source which causes this exception can easily be determined by the variable "osISRUnhandledException_Number". The corresponding interrupt source can be distinguished by having a look into the interrupt vector table which normally is generated to intvect.c. <i>This feature is optional. Please refer to [5] to find out whether a specific implementation of MICROSAR OS supports this feature.</i>
ConditionalGenerating	/MICROSAR/Board/BoardGeneral/BoardConditionalGenerating	TRUE , FALSE	Determines whether the OS code generator creates the files only if the relevant configuration has been modified since the last generator run (ConditionalGenerating = TRUE).

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			If ConditionalGenerating = FALSE, the OS files are always generated. For details about this attribute, see chapter 8.1.3.
PeripheralRegion	OsOSPeripheralRegion	-	List of Peripheral Regions. For details about this attribute, see chapter 7.3.1.4
TimingHooks	OsOSTimingHooks	-	The file name of the definition of the timing hooks. An empty string means that no timing hooks shall be called.

Table 7-1 OS attributes

7.3.1.1 APIOptimization / OSOSAPIOptimization

> If attribute is set to **MANUAL**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
<APIName>	OsOS<APIName>	<i>List of names of APIs (as Booleans)</i>	If the API function corresponding to the attribute name is used in the application, the attribute has to be selected.

Table 7-2 Sub-attributes of APIOptimization = Manual

> If attribute is set to **AUTOMATIC**:

If possible, the inclusion of used API functions is done automatically. Example: If no alarm is defined, all API functions for alarm management will be removed from the kernel.

7.3.1.2 ProtectionHookReaction / OsOSProtectionHookReaction

> If attribute is set to **ALL**:

This is the default case. The OS provides all mechanisms for all possible return values from the ProtectionHook. The OS monitors all states and data and can be able, for example, to kill tasks, ISRs or even complete applications.

> If attribute is set to **SELECTED**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
KILLTASKISR	OsOSKILLTASKISR	TRUE FALSE	If selected, the application is allowed to return the value <code>PRO_TERMINATETASKISR</code> in the protection hook. All necessary information will be monitored in the OS.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
KILLAPPL	OsOSKILLAPPL	TRUE FALSE	If selected, the application is allowed to return the value <code>PRO_TERMINATEAPPL</code> in the protection hook. All necessary information will be monitored in the OS.
KILLAPPL_RESTART	OsOSKILLAPPL_RESTART	TRUE FALSE	If selected, the application is allowed to return the value <code>PRO_TERMINATEAPPL_RESTART</code> in the protection hook. All necessary information will be monitored in the OS.
SHUTDOWN	OsOS SHUTDOWN	TRUE FALSE	If selected, the application is allowed to return the value <code>PRO_SHUTDOWN</code> in the protection hook. If for example only <code>SHUTDOWN</code> is selected, the OS is more efficient as the monitoring and housekeeping for tasks, ISRs, and applications is switched off.

Table 7-3 Sub-attributes of ProtectionHookReaction = SELECTED

**Caution**

Currently MICROSAR OS does not support killing. So only SHUTDOWN should be selected!

**Caution**

If the Protection hook returns a value that is not configured by means of the sub-attributes of `ProtectionHookReaction`, the OS performs a Shutdown.

**Note**

MICROSAR OS allows to use the return values

- `PRO_KILLTASKISR`,
- `PRO_KILLAPPL` and
- `PRO_KILLAPPL_RESTART`

In the protection hook as synonyms for

- `PRO_TERMINATETASKISR`,
- `PRO_TERMINATEAPPL` and
- `PRO_TERMINATEAPPL_RESTART`

as long as no macro `OS_SUPPRESS_PROTHOOK_OLD_RET_VALS` is defined.

7.3.1.3 TimingMeasurement / OsOSTimingMeasurement

If this attribute is set to `FALSE` no timing measurement is performed for any task or ISR.

This attribute can be set to `TRUE` in the scalability classes SC2 and SC4 only.

Please see also 3.2.4.2 and 7.3.2.2.

- > If this attribute is set to `TRUE`, the subattribute `GlobalConfig` allows to globally override theTask/ISR settings for Timing Protection and Timing Measurement:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
GlobalConfig	OsGlobalConfig	ProtectAndMeasureAll AsSelected OnlyMeasureAll	> ProtectAndMeasureAll: The OS provides timing measurement for all tasks and ISRs regardless of their setting in the attribute <code>TIMING_PROTECTION</code>. Timing protection however is provided only for all tasks and ISRs that have the attribute <code>TIMING_PROTECTION</code> set to <code>TRUE</code>. In case the subattribute <code>OnlyMeasure</code> is set to <code>TRUE</code>, that setting is ignored with a warning. In case the attribute <code>TIMING_PROTECTION</code> of a task or ISR is set to <code>FALSE</code>, the OS provides no timing protection. > AsSelected: The os provides timing protection for a task or ISR if that is configured, the attribute <code>OnlyMeasure</code> is honored. > OnlyMeasureAll: The OS does not provide timing protection for any Task or ISR. Instead, it provides timing measurement for all tasks and ISRs. In case a task or ISR is configured to have timing protection and has the subattribute <code>OnlyMeasure</code> set to <code>FALSE</code>, that setting is overridden with a warning.

Table 7-4 Sub-attributes of `TimingMeasurement = TRUE`

7.3.1.4 PeripheralRegion / OsOSPeripheralRegion

OIL Name	XML Name	Values	Description
StartAddress	OsOSStartAddress	-	Numeric value Specifies the start address of the peripheral region, which shall be configured.
EndAddress	OsOSEndAddress	-	Numeric value Specifies the end address of the peripheral region, which shall be configured.
Identifier	OsOSIdentifier	-	Area name Must be a unique C-identifier, which can be used in an application or BSW module to access the peripheral region.

OIL Name	XML Name	Values	Description
ACCESSING_APPLICATION	OsOSAccessingApplication	-	Grants access for this Peripheral Region. Multiple applications can be defined for the same Peripheral Region.

Table 7-5 Sub-attributes of `PeripheralRegion`**Caution**

The application is allowed to access memory addresses in the interval of `StartAddress` $\leq$ memory to be accessed $\leq$ `EndAddress`

The “`EndAddress`” value is included! All bytes of a peripheral access must fit into the peripheral region.

7.3.2 Task

In the section Task all tasks and their attributes have to be defined.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the task. This name is used as an argument to all task-related OSEK API functions (e.g. <code>ActivateTask</code>). The task function (or task body) has to be defined using the C macro <code>TASK()</code> (which appends the suffix <code>func</code> to the task name).
Comment	n.a.	--	Any comment.
TYPE	OsTaskTYPE	BASIC, EXTENDED, AUTO	Type of the task: either BASIC or EXTENDED. If set to AUTO, the type is calculated based on the settings for events and the activation count.
SCHEDULE	OsTaskSchedule	NON, FULL	Scheduling policy for this task.
PRIORITY	OsTaskPriority	-	The priority of the task. A higher number represents a higher priority (according to the OSEK specification). The priority may be set with gaps, though the gaps will be eliminated by the code generator. With BCC1 and ECC1, each level may only be assigned to one task. With BCC2 and ECC2, several tasks may be set on the same priority level.
ACTIVATION	OsTaskActivation	-	The number of activations that are recorded in the kernel while the task is possibly running or delayed by higher priority tasks. If <code>ACTIVATION</code> is set to a value bigger than 1, no events can be received.
AUTOSTART	OsTaskAutostart	-	If set to <code>TRUE</code> , the task will be activated at

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			startup of the operating system. See chapter 7.3.2.1 for details about the sub-attributes.
EVENT	OsTaskEventRef	-	Reference to an event that is used by this task. This attribute can only be used for extended tasks (the attribute <code>TYPE</code> might be set to <code>EXTENDED</code> or <code>AUTO</code>). This attribute can be used multiply if more than one <code>EVENT</code> has to be assigned. If events are used with this task, the attribute <code>ACTIVATION</code> cannot be bigger than 1.
RESOURCE	OsTaskResourceRef	-	Reference to a resource that is occupied by this task. This attribute can be used multiply if more than one <code>RESOURCE</code> shall be assigned.
StackSize	OsTaskStackSize	-	Task stack size in byte. This attribute is only available if the implementation supports configurable task stacks.
NotUsingSchedule	OsTaskNotUsingSchedule	TRUE , FALSE	In certain cases, stacks may be shared between different tasks. This depends on the usage of the API function <code>Schedule</code> . If the application programmer does not use <code>Schedule</code> , stacks may be shared. In this case, stack sharing may be enabled by the attribute <code>NotUsingSchedule</code> . This attribute is only available if the implementation supports stacks. See chapters 3.2.2.4.2 and 3.2.2.4.3 for the details.
TIMING_PROTECTION	OsTaskTimingProtection	-	Selects timing protection for the task. See chapter 7.3.2.2 for information about the sub-attributes.
ACCESSING_APPLICATION	OsTaskAccessingApplication	-	Defines access rights of an application for this task. This attribute can be defined multiply, so different applications might have access right to the same task. This attribute can be used in scalability classes SC3 and SC4 only.

Table 7-6 Task attributes

7.3.2.1 AUTOSTART / OsTaskAutostart

> OIL: If attribute set to `FALSE`:

No sub-attributes.

> XML: If this container is not present:

AUTOSTART switched off.

> If attribute is set to **TRUE**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
APPMODE	OsTaskAppMode Ref	-	Defines an application mode in which the task is started in automatically. This attribute might be defined several times to start the task in different application modes.

Table 7-7 Sub-attributes of TASK->AUTOSTART=TRUE

7.3.2.2 TIMING_PROTECTION / OsTaskTimingProtection

Please note that **TIMING_PROTECTION = TRUE** can only be selected in the scalability classes SC2 and SC4.

> If attribute is set to **FALSE**:

No sub-attributes.

> If this attribute is not defined in XML:

Timing protection is switched off.

The value of this attribute might be overridden by the OS attribute **TimingMeasurement**, as described in chapters 7.3.1.4 and 3.2.4.2

> If attribute is set to **TRUE**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
EXECUTION BUDGET	OsTaskExecution Budget	-	Defines the maximum execution time for the task
TIMEFRAME	OsTaskTimeFrame	-	Defines the minimum time between task activations
MAXOS INTERRUPT LOCKTIME	OsTaskOsInterrupt LockBudget	-	Maximum time OS interrupts are locked (by SuspendOSInterrupts)
MAXALL INTERRUPT LOCKTIME	OsTaskAllInterrupt LockBudget	-	Maximum time ALL interrupts are locked (by SuspendAllInterrupts or DisableAllInterrupts)
LOCKINGTIME = RESOURCELOCK	OsTaskResource Lock	-	Is intended to be a container for sub-attributes concerning the locking time of resources
LOCKINGTIME = RESOURCELOCK/ RESOURCE	Inside the container OsTaskResource Lock: OsTaskResource LockResourceRef	-	The resource for which the locking time is specified.
LOCKINGTIME = RESOURCELOCK/ RESOURCE	Inside the container	-	Maximum time the resource is locked (by

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
RESOURCELOCK TIME	OsTaskResource Lock: OsTaskResource LockBudget		GetResource)
OnlyMeasure	OsOnlyMeasure	TRUE FALSE	If set to FALSE , timing values of this task are measured and violations against the configured values lead to a call of the ProtectionHook. If set to TRUE , the timing values are still measured but no call of the ProtectionHook occurs.

Table 7-8 Sub-attributes of TASK-> TIMING_PROTECTION=TRUE

7.3.2.3 Task attributes concerning the timing analyzer

The following attributes have to be used when working with the timing analyzer tool. They are used as input for this tool.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ComputationTime	OsTask ComputationTime	-	The worst case execution time (in nanoseconds)
Period	OsTaskPeriod	-	The minimum activation period of the task (in nanoseconds)
Deadline	OsTaskDeadline	-	The deadline of the task (in nanoseconds)
PRIORITY	OsTaskPriority	-	Priority of the task
UseResource Occupation	OsTaskUse Resource Occupation	-	If set to TRUE the occupation of resources can be taken into consideration by the analysis tool.
UseResource Occupation=TRUE/ Resource	OsTaskUse Resource Occupation =TRUE/OsTask Resource	-	Reference to the resource that is occupied.
UseResource Occupation=TRUE/ OccupationTime	OsTaskUse Resource Occupation =TRUE/OsTask OccupationTime	-	Maximum resource occupation time (in nanoseconds)

Table 7-9 Task attributes concerning the timing analyzer

7.3.3 Counter

The Counter container provides the following configuration attributes.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the counter. This name is used for the Alarm configuration.
Comment	n.a.		Any comment.
MINCYCLE	OsCounterMinCycle	-	This attribute specifies the minimum allowed number of ticks for a cyclic alarm linked to the counter.
MAXALLOWED VALUE	OsCounterMaxAllowedValue	-	Maximum value, which is reachable by the counter in counter ticks.
TICKSPERBASE	OsCounterTicksPerBase	-	This attribute specifies the number of hardware timer ticks required to reach a counterspecific unit. E.g. if you have a periodic tick timer, which is running with 16MHz and it is configured to trigger a timer interrupt with 1kHz. You have 16000 ticks per base.
TYPE	OsCounterType	SOFTWARE, HARDWARE	Defines the type of the counter. Possible settings are SOFTWARE or HARDWARE . SOFTWARE means the counter is incremented by means of the system service IncrementCounter, which has to be called by the application. HARDWARE means the counter is incremented by MICROSAR OS internally.
DRIVER	OsDriver	-	This Container contains the information who will drive the counter. This configuration is only valid if the counter has OsCounterType set to HARDWARE . Sub-Attributes are hardware dependent (see [5]).
TIMECONSTANT	OsTimeConstant	-	This Container allows the user to define constants, to be used e.g. to compare physical time values with timer tick values.
TIMECONSTANT/ CONSTNAME	OsConstName	-	The name, to be used by the application to get OsTimeValue in counter units.
TIMECONSTANT/ VALUE	OsTimeValue	-	This attribute contains the value of the constant in seconds.
SECONDSPERTICK	OsSecondsPerTick	-	This attribute contains the time of one counter tick in seconds.
ACCESSING_	OsCounter Accessing	-	Defines access rights of an application

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
APPLICATION	Application		for this counter. This attribute can be used multiply, so different applications might have access rights to this counter. This attribute can only be used in scalability classes SC3 and SC4.

Table 7-10 Attributes of COUNTER




Figure 7-2 Relation between Physical Units, Counter Units and Driver Units



Note

If the OS supports High-Resolution, there is no periodic counter tick. The OS programs the driver to interrupt on demand (e.g. next Alarm, next Expiry Point, etc.). Therefore, the counter has the same resolution as the driver ($OsCounterTicksPerBase$ is 1).

7.3.4 Alarm

The action of an alarm has to be defined statically.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the alarm. This name is used as an argument to all alarm related OSEK API functions (e.g. <code>SetRelAlarm</code>).
Comment	n.a.	--	Any comment
COUNTER	OsAlarmCounter Ref		Reference to the counter that drives the alarm.
ACTION	OsAlarmAction	> OIL: SETEVENT, ACTIVATETASK,	See chapter 7.3.4.1 for more information.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
		ALARMCALLBACK, INCREMENTCOUNTER > XML: Choice container: OsAlarmActivateTask, OsAlarmCallback, OsAlarmIncrementCounter, OsAlarmSetEvent	
AUTOSTART	OsAlarmAutostart	TRUE FALSE	> OIL: If set to TRUE , the alarm will be activated at startup of the system. > XML: If attribute is present, the alarm will be activated at startup of the system. See chapter 7.3.4.2 for more information about the sub-attributes and chapter 3.2.1.3 for more information about static alarms.
ACCESSING_APPLICATION	OsAlarmAccessingApplication		Defines access rights of an application for this alarm. This attribute can be used multiply, so different applications might have access rights to this alarm. This attribute can be used in scalability classes SC3 and SC4 only.

Table 7-11 Attributes of ALARM

7.3.4.1 ACTION / OsAlarmAction

> Attribute / ChoiceContainer is set to **ACTIVATETASK** / **OsAlarmActivateTask**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TASK	OsAlarmActivateTaskRef	-	Task to be activated

Table 7-12 Sub-attributes of ACTION = ACTIVATETASK

> Attribute / ChoiceContainer is set to **SETEVENT** / **OsAlarmSetEvent**:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TASK	OsAlarmSetEventTaskRef	-	Task to which the event should be sent
EVENT	OsAlarmSetEventRef		Event to be sent to the specified task

Table 7-13 Sub-attributes of ACTION = SETEVENT

> Attribute / ChoiceContainer is set to ALARMCALLBACK / OsAlarmCallback:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ALARMCALLBACK NAME	OsAlarmCallbackName	-	Name of the callback function to be activated

Table 7-14 Sub-attributes of ACTION = ALARMCALLBACK

> Attribute / ChoiceContainer is set to INCREMENTCOUNTER / OsAlarmIncrementCounter:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
COUNTER	OsAlarmIncrementCounterRef	-	Name of the counter to be incremented

Table 7-15 Sub-attributes of ACTION = ALARMCALLBACK

7.3.4.2 AUTOSTART / OsAlarmAutostart

- > OIL: This attribute can be either `TRUE` or `FALSE`. Depending on the value, there may be different sub-attributes.
- > XML: This attribute can be present in the configuration or it can be omitted. In case this container is present, it has sub-attributes, which are described below.
- > If `AUTOSTART` is set to `TRUE` (OIL) or if the container is present (XML):

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ALARMTIME	OsAlarmAlarmTime	-	The relative or absolute tick value when the alarm expires for the first time. Note that for an alarm which is <code>RELATIVE</code> the value should be

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			bigger than 0.
TYPE	OsAlarmAutostartType	ABSOLUTE RELATIVE	The value corresponds to a call of the API-Functions SetRelAlarm or SetAbsAlarm
CYCLETIME	OsAlarmCycleTime		This attribute defines the cycle time of a cyclic alarm in counter units. A zero value indicates that the alarm is not cyclic.
APPMODE	OsAlarmAppModeRef		Reference to the application modes for which the AUTOSTART shall be performed.

Table 7-16 Sub-attributes of AUTOSTART = TRUE

7.3.5 Resource

Resources have to be defined with the following attributes:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the resource. This name is used as an argument to all resource related OSEK API functions (e.g. <code>GetResource</code>).
Comment	n.a.	--	Any comment
RESOURCE PROPERTY	OsResourceProperty	STANDARD , LINKED , INTERNAL	This attribute can take the following values: > STANDARD: A normal resource that is not linked to another resource and is not an internal resource. > LINKED: A resource that is linked to another resource with the property STANDARD or LINKED. > INTERNAL: An internal resource that cannot be accessed by the application.
ACCESSING_APPLICATION	OsResourceAccessingApplication		Defines access rights of an application for this resource. This attribute can be used multiply, so different applications might have access rights to this resource. This attribute can only be used in scalability classes SC3 and SC4.
RESOURCE PROPERTY =LINKED / LINKED RESOURCE	OsResourceLinkedResourceRef		> OIL: If the resource property is set to LINKED, the LINKEDRESOURCE attribute holds a reference to a resource. > XML: This attribute holds a reference to a resource.

Table 7-17 Attributes of RESOURCE

7.3.6 Event

Events in the OSEK operating system are always implemented as bits in bit-fields. The user could use bit-masks like '0x0001', but to achieve portability between different OSEK implementations, the user should use event names, which are mapped to defined bits by the code generator.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the event. This name is used as an argument to all event related OSEK-API-functions (e.g. <code>SetEvent</code>).
Comment	n.a.	--	Any comment
MASK	OsEventMask	-	> OIL: <code>Eventmask</code> or <code>AUTO</code> > XML: If <code>EventMasks</code> shall be defined automatically this attribute shall be omitted

Table 7-18 Sub-attributes of EVENT



Caution

If the user selects `AUTO` for the mask, the code generator will search for free bits in the bit mask of the receiving task. It is important to specify each task that receives an event, otherwise the code generator will generate wrong bit-masks.

7.3.7 ISR

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the interrupt service routine.
Comment	n.a.	--	Any comment
CATEGORY	OsIsrCategory	-	> OIL: Number of category for the interrupt service routine (1-2) > XML: this attribute can be <code>CATEGORY_1</code> or <code>CATEGORY_2</code>
RESOURCE	OsIsrResourceRef	-	Reference to a resource that is occupied by this ISR. This attribute can be used multiply if more than one <code>RESOURCE</code> has to be assigned. Remark: This attribute is only available if the implementation supports resource management for ISRs. Details are described in the platform-specific part of this documentation [4].
TIMING_PROTECTION	OsIsrTimingProtection	-	Selects timing protection for the ISR. See chapter 7.3.7.2 for information about the sub-

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			attributes.
EnableNesting	OsIsrEnableNesting	-	If set to TRUE the OS will call the user ISR in a way that interrupts will be enabled again during user ISR. Thus, it is possible that the user ISR can be interrupted by other ISRs.
UseSpecialFunctionName	OsIsrUseSpecialFunctionName	-	Normally the attribute Name/Short-Name defines the C-Name of the ISR. Since this name must be unique, it would not be possible to map different interrupt Sources to a single ISR. This can be done by this attribute. If this attribute is set to TRUE , it is possible to define the function name of the ISR in a separate sub-attribute. These names do not have to be unique.
ACCESSING_APPLICATION	OsIsrAccessingApplication	-	Defines access rights of an application for this ISR. This attribute can be used multiply, so different applications might have access rights to this alarm. This attribute can be used in scalability classes SC3 and SC4 only.

Table 7-19 Attributes of ISR

7.3.7.1 UseSpecialFunctionName / OsIsrUseSpecialFunctionName

If this attribute is set to **TRUE** a function name can be specified which is taken as ISR name instead of the **Name (OIL) / Short-Name (XML)** attribute.

This can be used to map several interrupt sources to one ISR routine.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
FunctionName	OsIsrFunctionName	-	Name of the ISR routine.

Table 7-20 Sub-attributes of UseSpecialFunctionname / OsIsrUseSpecialFunctionName

**Example**

Given two Interrupts MyISR1 and MyISR2. Both shall trigger the same ISR routine. Activate SpecialFunctionName for MyISR2, and set FunctionName to "MyISR1". Now, MyISR2 is mapped onto the MyISR1 routine, which is implemented as usual:

```
ISR(MyISR1)
{
    ...
}
```

**Note**

The `ISR()` macro *MUST* be used for the definition of category 2 ISR handlers. If this is not possible, a wrapper using this macro can be used to call the respective ISR handler:

```
ISR(MyISR1) /* "MyISR1" is the configured */
{
    /* FunctionName in OIL or XML */
    MyISRHandlerFunction(); /* "MyISRHandlerFunction" is */
}                          /* the name of the actual ISR */
                          /* handler provided by the */
                          /* application */
```

7.3.7.2 TIMING_PROTECTION / OsIsrTimingProtection

- > OIL: This attribute has to be set to `TRUE` to switch on timing protection. The sub-attributes are only visible if `TIMING_PROTECTION` is `TRUE`.
- > XML: This attribute has to be present to switch on timing protection.

Please note that timing protection can only be switched on in the scalability classes SC2 and SC4.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
EXECUTIONTIME	OsIsrExecutionBudget	-	The parameter contains the maximum allowed execution time of the interrupt. > OIL: the times are given in nanoseconds. > XML: the times are given in seconds.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TIMEFRAME	OsIsrTimeFrame	-	This parameter contains the minimum inter-arrival time between successive interrupts > OIL: the times are given in nanoseconds. > XML: the times are given in seconds.
MAXOSINTERRUPTLOCKTIME	OsIsrOsInterruptLockBudget	-	This parameter contains the maximum time for which the ISR is allowed to lock all Category 2 interrupts (via <code>SuspendOSInterrupts()</code>). > OIL: the times are given in nanoseconds. > XML: the times are given in seconds.
MAXALLINTERRUPTLOCKTIME	OsIsrAllInterruptLockBudget	-	This parameter contains the maximum time for which the ISR is allowed to lock all interrupts (via <code>SuspendAllInterrupts()</code> or <code>DisableAllInterrupts()</code>) > OIL: the times are given in nanoseconds. > XML: the times are given in seconds.
LOCKINGTIME	OsIsrResourceLock	-	> OIL: This is a (empty) list of all lock times, in nanoseconds > XML: This container holds resource lock times, in seconds. Resource lock times are the maximum times an ISR is allowed to hold a resource.
OnlyMeasure	OsOnlyMeasure	TRUE FALSE	If set to <code>FALSE</code>, timing values of this ISR are measured and violations against the configured values lead to a call of the <code>ProtectionHook</code>. If set to <code>TRUE</code>, the timing values are still measured but no call of the <code>ProtectionHook</code> occurs. The value of this attribute might be overridden by the OS attribute <code>TimingMeasurement</code>, as described in chapters 7.3.1.4 and 3.2.4.2.

Table 7-21 Sub-attributes of `TIMING_PROTECTION` / `OsIsrTimingProtection`

7.3.7.2.1 LOCKINGTIME / `OsIsrResourceLock`

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
LOCKINGTIME= RESOURCELOCK/ RESOURCELOCK TIME	OsIsrResourceLockBudget	-	The parameter contains the maximum allowed time an ISR is allowed to hold a resource > OIL: the times are given in nanoseconds. > XML: the times are given in seconds.
LOCKINGTIME= RESOURCELOCK/	OsIsrResourceLockResourceRef		Holds the reference to this resource

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
RESOURCE			

Table 7-22 Sub-attributes of LOCKINGTIME / OsIsrResourceLock

7.3.7.3 ISR Attributes concerning the Timing Analyzer

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ComputationTime	OsIsrComputationTime	-	The worst case execution time (in nanoseconds)
Period	OsIsrPeriod		The minimum activation period of the ISR (in nanoseconds)
Deadline	OsIsrDeadline		The deadline of the ISR (in nanoseconds)
AnalysisPriority	OsIsrAnalysisPriority		The <code>AnalysisPriority</code> corresponds to the Task attribute <code>PRIORITY</code> / <code>osTaskPriority</code>. The <code>AnalysisPriority</code> is an extension of the priority values from tasks to ISRs, so all ISR priorities must have higher values as all task priorities to get correct analysis results. (Some OS Implementations use an attribute similar to <code>priority</code> for the hardware interrupt level. Therefore to the timing analysis an own attribute was introduced).
UseResourceOccupation	OsIsrUseResourceOccupation		If set to <code>TRUE</code> the occupation of resources can be taken into consideration by the analysis tool.
UseResourceOccupation=TRUE/Resource	OsIsrUseResourceOccupation=TRUE/OsIsrResource		Reference to the resource that is occupied.
UseResourceOccupation=TRUE/OccupationTime	OsIsrUseResourceOccupation=TRUE/OsIsrOccupationTime		Maximum resource occupation time (in nanoseconds)

Table 7-23 ISR attributes concerning the timing analyzer

7.3.8 COM

The section COM is not used by MICROSAR OS.

7.3.9 NM

The section NM is not used with the current MICROSAR OS implementation.

7.3.10 APPMODE / OsAppMode

Application modes have to be defined with the following attributes:

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the application mode. This name is used as an argument to all related OSEK-API-functions and for the definition of the AUTOSTART functionality of tasks and alarms.
Comment	n.a.	--	Any comment
n.a.	OsAppModeId		Internal ID of an Appmode. The value of this attribute is ignored by MICROSAR OS.

Table 7-24 Attributes of Appmode / OsAppMode

7.3.11 Application / OsApplication

The object APPLICATION is meant for the usage with scalability classes SC3 and SC4.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	--	Freely selectable name, not used by the code generator.
Comment	n.a.	--	Any comment.
n.a.	OsApplication Hooks	TRUE, FALSE	> OIL: not available > XML: container for switches concerning the hook routines
STARTUPHOOK	OsAppStartup Hook	TRUE, FALSE	If set to TRUE, the application specific hook routine <code>StartupHook_<Name></code> is called at system startup (<Name> is the value of APPLICATION attribute Name). (XML: is contained in <code>OsApplicationHooks</code>)
ERRORHOOK	OsAppErrorHook	TRUE, FALSE	If set to TRUE, the application specific hook routine <code>ErrorHook_<Name></code> is called if an error occurs inside this application (<Name> is the value of APPLICATION attribute Name). (XML: is contained in <code>OsApplicationHooks</code>)
SHUTDOWNHOOK	OsAppShutdown Hook	TRUE,	If set to TRUE, the application specific hook routine <code>ShutdownHook_<Name></code> is called at

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
		FALSE	system shutdown (<Name> is the value of APPLICATION attribute Name). (XML: is contained in OsApplicationHooks)
TRUSTED	OsTrusted	TRUE , FALSE	> OIL: Defines whether the application is trusted or not. See chapter 7.3.11.1 for information about the sub-attributes. > XML: This is only a boolean which marks the Application as trusted application
HAS_RESTART TASK	n.a.	TRUE , FALSE	> OIL: If this attribute is set to TRUE the Application uses a restart task. See chapter 7.3.11.2 for information about the sub-attributes.
n.a.	OsRestartTask	-	> OIL: there is no comparable attribute since the restart task reference is a sub-attribute of HAS_RESTARTTASK. > XML: Reference to restart task for this application.
TASK	OsAppTaskRef	-	Reference to all tasks belonging to this application.
ISR	OsAppIsrRef	-	Reference to all ISRs belonging to this application.
ALARM	OsAppAlarmRef	-	Reference to all alarms belonging to this application.
SCHEDULETABLE	OsAppSchedule TableRef	-	Reference to all schedule tables belonging to this application.
COUNTER	OsAppCounterRef	-	Reference to all counters belonging to this application.
n.a.	OsApplication TrustedFunction	-	Container that is used to define trusted functions.
NonTrusted_Function	OsApplicationNon Trusted_Function	-	List of non-trusted functions provided by this application (only for non-trusted applications).

Table 7-25 Attributes of Application / OsApplication

7.3.11.1 Trusted Functions

- > OIL: trusted functions are defined as sub-attributes of 'TRUSTED=TRUE'.
- > XML: there are containers for trusted functions.

The preconditions for editing the sub-attributes in the next table are TRUSTED=TRUE/TRUSTED_FUNCTION=TRUE for OIL and the existence of (at least one) OsApplicationTrustedFunction container.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TRUSTED_FUNCTION =TRUE/TRUSTED_FUNCTION =TRUE/NAME	OsTrustedFunction Name	-	List of trusted functions provided by this application.
TRUSTED_FUNCTION =TRUE/TRUSTED_FUNCTION =TRUE/Params	OsApplication Params	-	Parameter (arguments) of trusted function. Empty string means void. Used for stub generation only. See attribute <code>GenerateStub</code> .
TRUSTED_FUNCTION =TRUE/TRUSTED_FUNCTION =TRUE/ReturnType	OsApplication ReturnType	-	Return value data type of trusted function. Empty string means void. Used for stub generation only. See attribute <code>GenerateStub</code> .
TRUSTED_FUNCTION =TRUE/GenerateStub	OsApplication GenerateStub	-	If set to <code>TRUE</code> , stub functions are generated for all trusted functions of this application.

Table 7-26 Sub-attributes for trusted functions

7.3.11.2 HAS_RESTARTTASK

This is an OIL attribute that has no equivalent attribute in XML. Its sub-attribute is only available if `HAS_RESTARTTASK = TRUE`.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
RESTARTTASK	n.a.	-	Reference to restart task for this application.

Table 7-27 Sub-attributes for Application->HAS_RESTARTTASK=TRUE

7.3.12 Scheduletable

Schedule tables have to be defined with the following attributes.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
Name	Short-Name	-	Name of the <code>SCHEDULETABLE</code> . This name is used as an argument to all related OSEK API functions.
Comment	n.a.	--	Any comment

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
COUNTER	OsScheduleTable CounterRef	-	Defines the counter used as time basis for this schedule table.
REPEATING	OsScheduleTable Repeating	-	If selected, the schedule table is performed periodically after it is started. If deselected, the schedule table is performed once per activation.
DURATION	OsScheduleTable Duration	-	Defines the length of the schedule table in ticks, based on the underlying counter. This is the time from the first expiry point to the end of the schedule table or in the case of a periodic schedule table, between two subsequent first expiry points. The length is defined in units of ticks of the underlying counter.
AUTOSTART	OsScheduleTable Autostart	-	> OIL: If set to TRUE, the schedule table is activated at startup of the operating system. > XML: If attribute is present, the schedule table is activated at startup of the operating system. See chapter 7.3.13.1 for more information about the sub-attributes.
LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION	OsScheduleTable Sync	-	Defines, whether the schedule table shall be synchronized to a global time source. This attribute is meant for the usage with scalability classes SC2 and SC4. Sub-attributes are described in chapter 7.3.13.6.
EXPIRY_POINT	OsScheduleTable ExpiryPoint	-	Defines an expiry point for this schedule table
ACCESSING_APPLICATION	OsSchTbl Accessing Application	-	Defines access rights of an application for this schedule table. This attribute can be used multiply, so different applications might have access rights to this schedule table. This attribute can be used in scalability classes SC3 and SC4 only.

Table 7-28 Attributes of SCHEDULETABLE

7.3.12.1 AUTOSTART / OsScheduleTableAutostart

- > OIL: If this attribute is set to **TRUE** sub-attributes are visible and the schedule table is auto started.
- > XML: If this container is present in the configuration the schedule table is auto started

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
APPMODE	OsScheduleTable AppModeRef	-	Defines an application mode in which the schedule table is started automatically. This attribute might be defined several times to start the schedule table in several application

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
			modes.
TYPE	OsScheduleTableAutostartType	ABSOLUTE RELATIVE SYNCHRON	Defines the method how the schedule table is autostarted.
TYPE=ABSOLUT/ ABSVALUE	OsScheduleTableStartValue	-	Absolute autostart tick value when the schedule table starts. Only used if the <code>OsScheduleTableAutostartType</code> is ABSOLUTE .
TYPE=RELATIVE/ REOFFSET	OsScheduleTableStartValue	-	Relative offset in ticks when the schedule table starts. Only used if the <code>OsScheduleTableAutostartType</code> is RELATIVE .

Table 7-29 Sub-attributes for auto start of a schedule table

7.3.12.2 EXPIRY_POINT / OsScheduleTableExpiryPoint

An expiry point consists of a sequence of actions which are performed on a given tick time of the schedule table. There are the following sub-attributes. Some of them also have sub-attributes.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
ACTION	n.a.	> OIL : ACTIVATETASK SETEVENT ADJUST	> OIL: a list of actions
OFFSET	OsScheduleTblExpPointOffset	-	Defines the time at which the defined actions occur in ticks based on the underlying counter. The time is absolute to the start of the schedule table and is given in ticks of the underlying counter.
ACTION=ADJUST	OsScheduleTblAdjustableExpPoint	-	> XML: containers for holding the sub-attributes in case of expiry point action ADJUST
ACTION=ACTIVATETASK	OsScheduleTableTaskActivation	-	> XML: containers for holding the sub-attributes in case of expiry point action ACTIVATETASK
ACTION=SETEVENT	OsScheduleTableEventSetting	-	> XML: containers for holding the sub-attributes in case of expiry point action SETEVENT

Table 7-30 Sub-attributes of expiry points

7.3.12.3 Expiry point action ADJUST

- > OIL: the following attributes are visible if the expiry point action is **ADJUST**
- > XML: the following attributes are located in the container
`OsScheduleTblAdjustableExpPoint`

Those attributes are only relevant in SC2 or SC4 if synchronization mechanisms are used.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
MAXLENGTHEN	OsScheduleTable MaxLengthen		The maximum positive adjustment that can be made to the expiry point offset to achieve synchronization in ticks based on the underlying counter.
MAXSHORTEN	OsScheduleTable MaxShorten	-	The maximum negative adjustment that can be made to the expiry point offset to achieve synchronization in ticks based on the underlying counter.

Table 7-31 Sub-attributes of expiry point action ADJUST

7.3.12.4 Expiry point action ACTIVATETASK

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TASK	OsScheduleTable ActivateTaskRef		Reference to the task to be activated.
Cyclic	OsScheduleTable Cyclic	TRUE , FALSE	> OIL: If set to TRUE, this action is repeatedly added to the schedule table. > XML: This is a choice container. If set to TRUE the action will be repeatedly added to the schedule table. The cycle time is located in a sub-attribute. See chapter 3.2.6.3 for more details.
Cyclic=TRUE/Cycle Time	OsScheduleTable CycleTime		If the action is declared as cyclic, this attribute holds the cycle time in counter ticks.

Table 7-32 Sub-attributes of expiry point action ACTIVATETASK

7.3.12.5 Expiry point action SETEVENT

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
TASK	OsScheduleTable SetEventTaskRef	-	Task to which the event should be sent

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
EVENT	OsScheduleTable SetEventRef	-	Event to be sent to the specified task
Cyclic	OsScheduleTable Cyclic	TRUE, FALSE	> OIL: If set to TRUE, this action is repeatedly added to the schedule table. > XML: This is a choice container. If set to TRUE the action will be repeatedly added to the schedule table. The cycle time is located in a sub-attribute. See chapter 3.2.6.3 for more details.
Cyclic=TRUE/Cycle Time	OsScheduleTable CycleTime	-	If the action is declared as cyclic, this attribute holds the cycle time in counter ticks.

Table 7-33 Sub-attributes of expiry point action SETEVENT

7.3.12.6 LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION / OsScheduleTableSync

- > OIL: If set to **TRUE**, the synchronization of this schedule table is switched on and the sub-attributes will be visible.
- > XML: If this attribute is present in the configuration the synchronization is used for this schedule table.

This is only relevant in SC2 and SC4.

Attribute Name		Values	Description
OIL	XML	The default value is written in bold	
SYNC_STRATEGY	OsScheduleTbl SyncStrategy	EXPLICIT IMPLICIT NONE	Defines the synchronization strategy of this schedule table. > EXPLICIT: The schedule table is driven by an OS counter, but processing needs to be synchronized with a different counter, which is not an OS counter object. > IMPLICIT: The counter driving the schedule table is the counter with which synchronisation is required > NONE: no synchronization is applied at all
SYNC_STRATEGY=EXPLICIT/PRECISION	OsScheduleTbl ExplicitPrecision	-	Defines the synchronization tolerance (in ticks) for this schedule table. If the absolute value of the deviation between the schedule table counter and the synchronization counter is smaller than this value schedule table state is set to SCHEDULETABLE_RUNNING_AND_SYNCHRONOUS

Table 7-34 Sub-attributes SCHEDULETABLE-> LOCAL_TO_GLOBAL_TIME_SYNCHRONIZATION = TRUE

8 System Generation

This chapter describes the generation of the executable program. The definition of the OIL / XML file was described in the chapter 7 Configuration. The general steps programming an application using the OSEK operating systems are illustrated in chapter 7.1 Configuration and generation process.

The dependencies on include files are described in chapter 5.2 Include Structure.

8.1 Code Generator

The code generator `GENxxxx.EXE` is delivered with the MICROSAR OS package (xxxx is replaced by the hardware platform name). The code generator is implemented as a 32-bit Windows console application and can be started from the OIL Configurator or directly from the command line.

The code generator has different command-line options. When started without any parameters, a list of all parameters is printed:

```
GENxxxx.EXE, Version: 6.00, Vector Informatik GmbH, 2012
Usage: GENxxxx.EXE [options] <Filename>
-s : print symboltable
-r <Filename> : write errors into file
-g : generate code
-d <Pathname> : path to write generated code
-m : prints list of known implementations
-i <Pathname>: include path for implementation files
-x : include path equals to generator exe path
-f <Filename>: read options and filename from command file
-y : perform a syntax check on OIL file
```

8.1.1 Generated Files

The code generator generates several files as described in chapter 5.1.2 Dynamic Files.

The files always have the same name. They are written to the generation path specified in the OIL Configurator or with the command line option -d.

The '.c' modules have to be compiled and linked to the application.

8.1.2 Automatic Documentation

Automatic documentation of the generation process is provided by two list files, which are generated by the code generator. A basic list file is generated in text format. The more detailed list file is generated in HTML format and can be used to publish a system design in the internet or an intranet. Both files have the same name as the OIL file, i.e.:

- > <OILFileName>.lst (basic list file in text format)
- > <OILFileName>.htm (extended list file in HTML format)

The files are located in the directory of the OIL file.

8.1.3 Conditional Generation

If MICROSAR OS is configured using an OIL file, the OS object provides the attribute `ConditionalGenerating`. If AUTOSAR ECUC files are used for configuration, the parameter for conditional generation is not located in the OS configuration but in the BSWMD file of the Board, as other modules also use this parameter.

If conditional generation is selected, the generated files are overridden only if the OS configuration has changed since the last generator run. This allows using the file modification date of the generated files to decide which modules need recompilation after configuration changes. Compile times of a complete AUTOSAR stack may be dramatically reduced with this setting in the development cycle.

Setting `ConditionalGenerating = FALSE` forces the MICROSAR OS code generator to generate the files newly on each run. This is the recommended setting for the final, productive build.

8.1.4 Generated files backup

To avoid a mixed set of generated files from various runs of the generator, already existing files are either deleted or renamed before the new generation starts.

Before previously generated files are overwritten in a new run of a generator, the complete file set is renamed to files with the original name plus a ".bak" suffix (backup file set). This file set contains the last valid generated file set even if a consecutive generator run fails for any reason.

8.2 Application Template Generator

The application template generator is not available in current versions of MICROSAR OS.

8.3 Compiler

The supported compiler package has to be installed, and the search path of the compiler, assembler and linker has to be set. If special options are required, they are described in the hardware specific manual.

8.3.1 Include Paths

The operating system is delivered with include files in the subdirectory `root\HwPlatform\include` (osCAN style) or `root\BSW\Os` (MICROSAR style).

9 AUTOSAR Standard Compliance

9.1 Deviations

Currently no known deviations

9.2 Limitations

9.2.1 API Function OS_GetVersionInfo

The function

```
void OS_GetVersionInfo(Std_VersionInfoType *version info)
```

is not supported by MICROSAR OS. The version information can be collected by the following #defines:

Vendor ID	OS_VENDOR_ID
Module ID	OS_MODULE_ID
Major version number	OS_SW_MAJOR_VERSION
Minor version number	OS_SW_MINOR_VERSION
Patch version number	OS_SW_PATCH_VERSION

9.2.2 Forcible Termination

MICROSAR OS does currently not support forcible termination. The only possible reaction on a protection error is to shutdown the system.

9.2.3 AUTOSAR Debug support

MICROSAR OS does not provide any variables and type definitions for AUTOSAR Debugging (See requirements OS549-551 in [1]). The suggested way to gather information about the internals of the OS is to use the ORTI feature supported by MICROSAR OS.

9.2.4 Port Interface

The Port interface described by requirements OS560, OS561 in [1] is not supported by MICROSAR OS.

9.2.5 NULL Pointer Checks

Null pointer checks described by requirements OS566 in [1] are not implemented in MICROSAR OS.

9.3 Clarifications

9.3.1 CallTrustedFunction if owner application is not APPLICATION_ACCESSIBLE

According to [1], an OS-Application is a collection of Operating System objects. Contrary to what one would suspect during configuration of the OS, the provided list of those

objects does not include trusted functions. Instead, there is a figure that states trusted functions to be a "provided service" of a trusted OS-Application.

Thus, MICROSAR OS assumes OS504 not applicable for trusted functions. Consequently, a trusted function of an OS-Application that is not in the state `APPLICATION_ACCESSIBLE` can still be called. If this behavior is undesired, the trusted function must check the application state of its owner application by itself, and react accordingly.

10 Debugging Support

10.1 Kernel aware Debugging

All implementations of MICROSAR OS support kernel-aware debugging according to the ORTI specification. To use this feature, 'ORTIDebugSupport' must be enabled in the Configuration file. On some platforms, proprietary solutions are available.

Refer to the hardware specific documentation [4] for details.

10.2 Version and Variant Coding

The version and the variant are coded into the generated binary or HEX file. The user has the possibility to read version and variant using an emulator, or if the electronic control unit is accessible via the CCP protocol via the CAN bus.

The generator writes version and variant information into a structure, defined in `osek.h`.

```
typedef struct
{
    osuint8 ucMagicNumber1;      /* magic number: */
    osuint8 ucMagicNumber2;      /* defined as uint8 for independency of */
    osuint8 ucMagicNumber3;      /* byte order */
    osuint8 ucMagicNumber4;

    osuint8 ucSysVersionMaj;     /* version of operating system, Major */
    osuint8 ucSysVersionMin;     /* version of operating system, Minor */
    osuint8 ucGenVersionMaj;     /* version of code generator */
    osuint8 ucGenVersionMin;     /* version of code generator */
    osuint8 ucSysVariant1;       /* general variant coding 1 */
    osuint8 ucSysVariant2;       /* general variant coding 2 */
    osuint8 ucOrtiVariant;       /* ORTI version and variant */

    ...                          /* implementation specific variant coding */
} osVersionVariantCodingType;
```

The structure contains the version of the operating system (major and minor version number), the version of the code generator used (major and minor version number), information about the OS configuration bit-encoded into 8-bit values (`ucSysVariantX`) and information about usage of the OSEK runtime interface (ORTI):

The magic number is defined as 0xAFFFEDEAD and may be used for an identification of the version in hex or binary files.

Bits	Meaning	Possible Values
0..1	Conformance Class	0: BCC1 1: BCC2 2: ECC1 3: ECC2
2	Status Level	0: STANDARD STATUS 1: EXTENDED STATUS
3..4	Scheduling policy	0: non preemptive

Bits	Meaning	Possible Values
		1: full preemptive 2: mixed preemptive
5	Stack Check	0: disabled 1: enabled
6	Error information level	0 STANDARD 1 Modulenames
7	OS internal checks	0 STANDARD 1 Additional

Table 10-1 Bit-definitions of the variant coding, ucSysVariant1

Bits	Meaning	Possible Values
0..1	Scalability Class	0: SC1 1: SC2 2: SC3 3: SC4
2	Usage of Schedule tables	0: no schedule tables in system 1: schedule tables are used
3	Usage of high resolution schedule tables	0: no high resolution tables in system 1: high resolution schedule tables are used
4	Schedule table synchronization	0: synchronization is not used 1: synchronization is used
5	Timing protection	0: timing protection is used 1: timing protection is switched off

Table 10-2 Bit-definitions of the variant coding, osSysVariant2

Bits	Meaning	Possible Values
0..6	ORTI version	0x00: No ORTI used 0x20: ORTI 2.0 used 0x21: ORTI 2.1 used 0x22: ORTI 2.2 used
7	ORTI additional information	0: The ORTI information is restricted to those parts that do not cause runtime or memory overhead 1: The full set of ORTI information is provided by the OS

Table 10-3 Bit definitions of the variant coding, osOrtiVariant

The data for the structure is located in the constant `oskVersionVariant` and specified in the OS module `osek.c`.

The structure also contains implementation specific variant coding which is described in the separate documentation [4].

11 Glossary and Abbreviations

11.1 Abbreviations

Abbreviation	Description
API	Application Programming Interface
AUTOSAR	Automotive Open System Architecture
BSW	Basis Software
CCP	CAN Calibration Protocol
COM	Communication (= module COM in AUTOSAR/MICROSAR)
CPU	Central Processing Unit
ECU	Electronic Control Unit
EPROM	Erasable Programmable Read Only Memory
EEPROM	Electrically Erasable Programmable Read Only Memory
HIS	Hersteller Initiative Software
IRQ	Interrupt ReQuest
ISR	Interrupt Service Routine
MICROSAR	Microcontroller Open System Architecture (the Vector AUTOSAR solution)
NM	Network Management (= module NM in AUTOSAR/MICROSAR)
NMI	Non Maskable Interrupt
OIL	OSEK Implementation Language
ORTI	OSEK RunTime Debugging Interface
OS	Operating System
OSEK	Abbreviation of the German term "Offene Systeme und deren Schnittstellen für die Elektronik im Kraftfahrzeug" - Open Systems and the Corresponding Interfaces for Automotive Electronics
RAM	Random Access Memory
ROM	Read-Only Memory
SC1, SC2, SC3, SC4	Scalability Class 1, -2, -3, -4
SRS	Software Requirement Specification
SWC	Software Component
SWS	Software Specification
WCET	Worst Case Execution Time
XML	Extensible Markup Language

Table 11-1 Abbreviations

11.2 Terms

Terms	Description
Forcible Termination	Forcible termination means that a task, an ISR or even a whole OS application is terminated before it has reached its end. This may be caused by a call of the API function TerminateApplication or by returning certain values in the protection hook.
Killing	The term 'killing' is used as a synonym for forcible termination within this document.
Process	The term 'process' is used within this document as a short form of 'task or ISR'.
Thread	The term 'thread' is used as a synonym of the term 'process' within this document.

Table 11-2 Terms

12 Contact

Visit our website for more information on

- > News
- > Products
- > Demo software
- > Support
- > Training data
- > Addresses

www.vector.com

For support requests you may write to **osek-support@vector.com**